

NOTA DI LAVORO 109.2013

Solar Grid Parity Dynamics in Italy: A Real Option Approach

By Tommaso Biondi, Sinloc, Sistema Iniziative Locali S.p.A Michele Moretto, Department of Economics and Management, University of Padova, Fondazione Eni Enrico Mattei and Centro Studi Levi- Cases

Energy: Resources and Markets

Series Editor: Giuseppe Sammarco

Solar Grid Parity Dynamics in Italy: A Real Option Approach

By Tommaso Biondi, Sinloc, Sistema Iniziative Locali S.p.A Michele Moretto, Department of Economics and Management, University of Padova, Fondazione Eni Enrico Mattei and Centro Studi Levi- Cases

Summary

Over the past three years Italy has witnessed a rapid growth in the photovoltaic energy market, followed by an equally sudden decline when the government decided to reduce the incentives. This sharp change in the trend of the market calls into question the achievement of Grid Parity and the possibility that the market is able to develop independently. Starting from the standard Grid Parity Model, widely used for the photovoltaic (PV) market, we internalize the uncertainty surrounding both the energy price and PV module costs, to forecast the dynamics of the Italian PV market. We show that these sources of uncertainty can delay the Grid Parity timing of several years compared to current forecasts, well describing the current market situation.

Keywords: Photovoltaic Market, Grid Parity

JEL Classification: O3, O31, O32

Address for correspondence:

Michele Moretto University of Padova via del Santo 33 35100 Padova Italy E-mail: michele.moretto@unipd.it

Solar Grid Parity Dynamics in Italy: A Real Option Approach

Tommaso Biondi^{*}

Michele Moretto[†]

November 11, 2013

Abstract

Over the past three years Italy has witnessed a rapid growth in the photovoltaic energy market, followed by an equally sudden decline when the government decided to reduce the incentives. This sharp change in the trend of the market calls into question the achievement of Grid Parity and the possibility that the market is able to develop independently. Starting from the standard Grid Parity Model, widely used for the photovoltaic (PV) market, we internalize the uncertainty surrounding both the energy price and PV module costs, to forecast the dynamics of the Italian PV market. We show that these sources of uncertainty can delay the Grid Parity timing of several years compared to current forecasts, well describing the current market situation.

1 Introduction

Year 2011 was pivotal for the photovoltaic (PV) market in Italy. With about 9 Giga watts of new installations, the Italian photovoltaic capacity has grown by 430% compared to 2010. This was the result of a decrease in the cost of modules and, in particular, by the introduction of an incentive mechanisms by the Italian Government, the Feed In Tariffs (FIT), kept forcedly high from 2005 till 2012¹. For this reason, the past development of the PV market is giving way to a high degree of uncertainty in the future. In the coming years we expect a phase out of the FIT, able to drive the Italian energy system towards the competitiveness of photovoltaic energy. This competitiveness, called Grid Parity, is defined as the intersection between the electricity price and the unit cost of a plant and it represents the break-even point of the investment. Grid Parity, which is gaining more and more attention from photovoltaic industry professionals, is considered as the appropriate time for a cost-neutral investment and it represents the final phase of the expansion of this technology.

However, the Grid Parity provides only a partial view of the problem. The break-even analysis behind the Grid Parity does not take into account two important aspects of the decision to invest in a PV system: the irreversibility of the choice and the uncertainty of some key variables. In the specific, this paper, by using the Real Option Approach, tries to internalize both the uncertainty related to the electricity price and the energy generation cost to assess the effect that these variables have on the optimal investment time.

Internalizing these sources of uncertainty results in a delay of the PV Grid Parity timing with respect to the current forecasts that place it around 2014. In particular, when the high level of uncertainty which is actually surrounding the market is taken into account, Grid Parity is far from being achieved and it can be moved forward by ten years. We show that this result is robust to variations of some key parameters that affect the analysis.

The remainder of the paper is organized as follows. Section 2 discusses the related literature. Section 3 presents empirical evidence, drawn form Italian data, of the dynamics of both the

^{*}Sinloc, Sistema Iniziative Locali S.p.A., Padova, Italy. Email: tommasobiondi@me.com

[†]Department of Economics and Management, University of Padova, Fondazione Eni Enrico Mattei and Centro Studi Levi- Cases. Corresponding address: via del Santo, 33 35100 Padova, Itay. Email: michele.moretto@unipd.it

electricity price and the cost of energy. Section 5 models the value of a PV system in term of Grid Parity and illustrates our main findings through numerical calibrations. Section 6 concludes.

2 Discussion of the related literature

Grid Parity is defined as the time when the unit cost of photovoltaic energy will reach the electricity price. The dynamic model for Grid Parity is based on the historical negative relationship between two trends: the decreasing PV electricity generation costs and the electricity price showing an increasing path over time. The Grid Parity goal is considered as the final phase of PV electricity expansion, representing cost-competitiveness of solar power generation systems. Nowadays, PV power generation is already competitive in many off-grid installations, especially in developing countries, while global competitiveness is expected until 2020 (Acanfora and Alcor 2011, Salvadores and Keppler 2010b).

Renewable energy technologies for producing electricity have received greater attention in recent years, due to the rise of fossil fuel prices and concern for greenhouse gases emissions and climate change. Following the important growth of the green-economy and the astonishing boom of photovoltaic power generation systems, Solar Grid Parity has become a large debated issue. Despite this growing interest – we can find many newspapers' articles speaking about Grid Parity – there is still no much literature available on this. The major references have to be found in the roadmaps of the global energy associations, like the IEA (International Energy Agency), the EPIA (European Photovoltaic Industry Association) and the IRENA (International Renewable Energy Agency), or in some research papers commissioned by the biggest PV module producers and in few specific works commissioned by the governments of some world regions.

A first study on Grid Parity, in chronological order, can be found in Lorenz et al. (2008), which brought out several important issues of great interest at the present time. This article forecasted the high level of competitiveness the market of module producers is affording today, underlying the need to "move production to low-cost countries to maintain a stable market share". This contribution also depicted the need for a sustainable regulatory framework – a necessary tool on the way to PV competitiveness – able to boost market development without doping the PV sector².

Breyer and Gerlach (2010) is the first academic study on Grid Parity. Commissioned by Q-Cells in 2009, the authors make a first global overview on Grid Parity Event Dynamics. The aim of the paper is to define the gradual achievement of Grid Parity in different countries, according to their solar irradiation and to the average value of electricity prices in their domestic market. Italy was considered to be the first to reach Grid Parity in 2010 (high solar irradiation, high electricity prices), followed by Spain, Portugal and Cyprus. Outside Europe, California was expected to reach Grid Parity in 2012, while almost all the central and southern States of the US were supposed to reach the goal before 2020. It is one of the first work to apply learning curves to the Levelised Cost Of Electricity (LCOE), in order to explain the decrease in PV production costs.

Acanfora and Alcor (2011, 2012) set the goal of Grid Parity before 2020 for all European countries, where (again) Italy is indicated as the first to reach it. The analysis by Salvadores and Keppler (2010b) presents the same results. The commercial development of PV plants is divided into three different phases, within the interval 2010 - 2020, when many countries, characterized by good solar resources and high conventional electricity prices, will reach the Grid Parity.

Apart from these works, which provide a comprehensive vision of the phenomenon, there are a few studies focusing on Grid Parity timing in specific countries. Bhandari and Stadler (2009), compute the average cost of a PV power generation system in the region of Cologne (Germany), for both residential consumers and utilities, and compare them to the respective local electricity prices. Considering (the higher) electricity prices for end-users, Grid Parity will be reached between 2013 and 2014. However, taking into account (the lower) wholesale electricity

prices, Grid Parity shifts to 2023. They also present some sensitivity analysis with respect to the PV module economic lifetime. While the standard economic lifetime is placed between 20 and 30 years – 25 are the most-used benchmark – the authors stress the analysis with a 35 to 40 years production period. This increase in the production period, applied to the wholesale Grid Parity model, reduces Grid Parity to 2019 and 2017 respectively. Mitscher and Rutter (2012), make a widespread analysis of the Brazilian case. In particular, the authors stress the need for lower interest rates to reach the Grid Parity. Focusing on the problem of current credit cost on the Brazilian market, they show how a lower cost of credit can be sufficient to achieve Grid Parity in several Brazilian cities, even with the current PV system prices. Further, Ong et al. (2012), concentrate their attention on the United States residential PV market. They perform an interesting sensitivity analysis based on the rate of solar radiations. They found that the current break-even price varies more than a factor of 10 even though the solar resource varies by less than a factor of 2. In line with these findings, they show that only a part of the residential users will have the necessary combination of good solar access and attractive financing options to really consider to invest in a PV system.

Yang (2010) stress the fact that the cost-effectiveness may not guarantee commercial competitiveness. Looking at the case of the Solar Heating Water market in Hawaii, where this technology is considered to be cost-competitive, Yang shows that the break-even point has not been a powerful driver for market expansion. He sets the need of further government interventions to exploit the untapped potential of the solar PV market.

The works that is most closely related to ours is Belien et al. (2013). The authors derive the "the best time to invest" in a PV panel by a profit maximizing investor in Flandres. Even if they compare their work with some Grid Parity studies, they outline how their model is different from a standard Grid Parity approach. First, Grid Parity is not a profit-maximizing model. It focuses only on the break-even point between electricity prices and PV costs. Second, considering subsidies in the analysis, they internalize government choices over the future values of the FIT. Grid Parity should focus on unsubsidized prices to end-users, without taking into account any form of incentive. The authors' results of an optimal investment time around 2012 are in line with the model structure. The power generation plant must be installed as early as possible, given that future FITs are uncertain and expected to end quickly.

Finally, in the same vein, the "Solar Energy Report" by the Politecnico di Milano (2012), sees the Grid Parity as a key point for the determination of a gradual depletion of incentives taking account of the specificities of the different types of plant.³ The Report presents a non-standard formulation of Grid Parity timing. It is not only the time at which electricity prices and the unit cost of PV systems equals, it is viewed as the time in which the investment in PV plants – without incentives – will give a positive Net Present Value.

3 Electricity Prices in Italy

Electricity is usually considered as a "commodity", but it presents some peculiarities that differentiate the behavior of its price from the price all other commodities. The most important difference is probably the non-storability. Electricity cannot be physically stored in a direct way and production and consumption have to be continuously balanced. Therefore, supply and demand shocks cannot be easily smoothed out and they have a direct effect on equilibrium prices. Furthermore, electricity is a primary commodity, so its demand is highly inelastic. These features, coupled with the fact that the price is highly weather dependent, contribute to explain the observed high volatility.⁴

We use 93 monthly data on Italian electricity prices (PUN, Prezzo Unico Nazionale), starting from April 2004, the first operating month of the Italian Power Exchange (IPEX), to December 2011.

As we can see from Figure 1, after three years of growth, in 2007 we can notice the first



Figure 1: IPEX Price, April 2004 - December 2011 (Monthly data from www.gse.it)

decline of the PUN. This is primarily due to the relationship between electricity prices and Brent prices. Although the level of oil prices in 2007 is steadily increased, this growth has been compensated by two different phenomena: the significant strengthening of the Euro against the U.S. Dollar and the delay with which the variations in Brent prices reflect on Italian electricity prices⁵. There is some evidence of a lagged relationship between oil prices and electricity prices, due to the contractual structure of fuel supply. Furthermore, electricity prices depend on the marginal class of power generation plants – i.e. Natural Gas (NG) power plants. Given that the cost structure of NG power plants is dominated by NG fuel cost, their strong correlation with oil prices reflects on electricity prices. In line with this lagged relationship, we can notice peak values of the PUN in 2008, followed by a strong price decrease in 2009. This last phenomenon is the result of the decrease in fuel prices and electricity consumption caused by the economic crisis - in 2009 the PUN reaches the lowest values since 2005. In 2010, despite a strong increase in crude oil prices, the PUN has maintained its lower levels, with a moderate increase at the end of the year. Finally, the graph shows an important upward trend in 2011. This growth is partially mitigated by a persistent level of overcapacity, which has been boosted by the important increase in photovoltaic plants.

Denoting by P_t the IPEX price we test whether it follows a Geometric Brownian motion (GBM) and then the appropriate parameter values will be calculated. The GBM is a simple parsimonious process, which requires only the computation of two parameters (drift and volatility) to be fitted, i.e.⁶:

$$dP_t = \alpha_P P_t dt + \sigma_P P_t dB_t \quad \text{with } P_{t_0} = P_0 \tag{1}$$

where dB_t is the increment of a standard Wiener process (Brownian motion), α_P is the drift term and σ_P the instantaneous volatility of the process. Applying Itô's formula, we rewrite the basic stochastic equation (1) as follows:

$$d\ln P_t = \left(\alpha_P - \frac{\sigma_P^2}{2}\right)dt + \sigma_P \, dB_t \tag{2}$$

where the increments of $\ln P_t$ are normally independent identically distributed with mean $\left(\alpha_P - \frac{\sigma_P^2}{2}\right) dt$ and variance $\sigma_P^2 dt$. Using STATA software we test the independence assumption by plotting the autocorrelations of the log returns $r_t = \frac{\ln P_{t+1}}{\ln P_t}$:

Figure 2 shows that we do not have significant autocorrelations till the 12th lag. All the other values are below the confidence interval. This is a usual behavior for electricity prices, which are characterized by seasonality. To test for the normality of electricity prices returns, we plot in Figure 3 the sample data of log returns against the standard normal distribution.

The quantiles of the log return distribution are plotted on the Y-axis and the quantiles of the standard normal distribution are plotted on the X-axis. Figure 3, shows that the distribution of



Figure 2: IPEX price - Autocorrelogram



Figure 3: IPEX Price - Testing for normality

log-returns fits well the normal distribution⁷. Finally, we run the Dickey Fuller unit root test to support the assumption that P_t is a GBM. The Dicky-Fuller critical F – value at the 5% level (for number of observations lower than 80) – is -2.706, so the null hypothesis of GBM cannot be rejected (See Appendix A).

Having established that the increments of $\ln P_t$ exhibit GBM, we proceeded by estimating the relevant trend and uncertainty parameters α_P and σ_P . For the the volatility we calculated $\sigma_P = \sum_{i=1}^n \frac{(r_i - \hat{m})^2}{n}$, where \hat{m} is the sample mean of r_t . The monthly volatility is equal to 10,09% that corresponds to 34,95% in annual terms⁸. This value is consistent with the estimates in Escribano et al. (2011) and Crespo et al. (2012). To estimate the drift α_P , we exploit the equation of log-returns to set a linear regression as follow:

$$r_t = \beta t + \varepsilon_t$$

where: $\beta = \alpha_P - \frac{\sigma_P^2}{2}$ and $\varepsilon_t = \sigma_P(B_{t+1} - B_t)$. By running OLS we obtain a monthly drift equal to 0,509%. This corresponds to a growth rate of 6,11% in annual terms, which is quite above the value for Italy by Acanfora and Alcor (2012).

As usual for many commodities the electricity price is known to have a mean reverting behavior (Escribano et al. 2011). When a shift in demand increases the price, there is an economic incentive for more expensive generators to start producing, which, in turn, reverts the dynamics of prices. However, although a significant autocorrelation at the 12th lag can be an indication of

Source	SS	df	MS			Numbe	r of	obs	=	92
Model Residual	.00096849 1.02747232	1 90	.000968 .0114163	349 359		F(1 Prob R-squ	, > F ared	90)	= =	0.08
Total	1.02844081	91	.011301	547		Adj R Root	-squ MSE	ared	=	-0.0102 .10685
RENDIMENTO	Coef.	Std.	Err.	t	P> t	[9	5% C	onf.	In	terval]
mese _cons	0001222 .011226	.0004	195 –(273 (0.29 0.49	0.772 0.624	0 0	0095 3412	55 44		0007112 0565764

this effect, the time series of the PUN is too short to exploit such a behavior. Therefore, instead of estimating a mean-reverting process, we decided to lower the GBM trend which tends to be too high. We do this by correcting α_P by a measure of the speed the process takes to converge to the mean if it had been of mean-reverting type. For example in a Ornstein-Uhlenbeck process the conditional distribution of P_t at time t is normal with mean $E(P_t) = P_0 e^{-\eta t} + (1 - e^{-\eta t})\overline{P}$, where \overline{P} is the "long run mean" to which the process tends to revert and η is the speed of reversion. By using the IPEX data we estimate $\eta = 0.0252$ (in annual term)⁹, then the adjusted drift α_P becomes 0.0359 which is in line with Acanfora and Alcor (2012) estimates.

3.1 IPEX price and what the end user pays

. reg RENDIMENTO mese

The price that results from daily exchanges on the electricity market is only a fraction of the whole electricity price paid by end-users, both industrial users and domestic ones. The price paid by consumers includes other variables that should be considered. In the specific we analyses the components of the final prices used by the Italian Authority for Electricity and Gas (AEEG, Autorità garante per l'Energia Electrica ed il Gas), and how these components can be incorporated in the Grid Parity model.

Figure 4 compares the IPEX (red line) with two different quarterly time series about domestic and industrial electricity prices. The domestic price (green line) and the industrial price (violet line), are the average prices calculated as the total amount paid by the end user weighted for the total energy consumption.

The most important factor of final electricity price is the PE (Price of Energy), this represents on average 50% of the final price. The PE is slightly different from the PUN. While the PUN is a market price, obtained from the arithmetical mean of hourly or daily prices, the PE is a weighted average of hourly prices and traded volumes. The PD (Dispatching Price) is the second major component of the final price, it represents the cost of dispatching energy into the grid and presents little changes over time. Then we must add costs for equalization and commercialization of energy, taxes, general system charges and network costs.

The key issue is to understand if we can use the dynamic of the PUN, previously described as a GBM, to identify the movements of the real price paid by end users, which can be identified with the average price published by the AEEG ¹⁰. The answer has to be found in the nature of the different components of the end-user price. In fact, while the PED = PE + PD (Price of Energy + Dispatching Price), is strictly linked to the PUN (see GME (2011)), it is impossible to find a dynamic for the other components. They are strictly exogenous and depend mainly on political choices.

So, for matter of tractability, we take the PUN as a good proxy for the dynamics of PED



Figure 4: PUN comparison - data from http://www.autorita.energia.it

while, as starting point P_0 , we use the "Residential User" and "Utility" prices taken from the AEEG publications (www.autorita.energia.it). Those prices exclude taxes and are computed as an average of the 2011 end-users price. In the following Table we sum up the value of the drift and diffusion terms of price dynamics. The drift terms are presented for the GBM and for the Adj-GBM case.

Table 2: Drift and diffusion terms of electricity prices dynamic

	GE	BM	ADJ.		
	α	σ	α	σ	P 2011
RESIDENTIAL	6,11%	34,95%	3,59%	34,95%	0,18
UTILITIES	6,11%	34,95%	3,59%	34,95%	0,13

4 PV Electricity Generation Costs

To analyse the dynamics of the generation costs of a PV plant we use the LCOE (Levelised Cost of Electricity). The LCOE is an easy tool used to compare the unit costs of different power generation technologies along their economic lifetime. It can be used even if different scales of operation, investment or operating time periods exist. It captures capital costs, on-going system-related costs and fuel costs – along with the amount of electricity produced – and converts them into a common metric (See Appendix B).

The LCOE is an important tool for both policy makers and private investors to understand the main cost drivers of electricity systems. However a full analysis of an investment project would complement the LCOE with a more comprehensive risk analysis, where multiple risks are taken into account. In this respect, as it will be explained in the following paragraphs, our grid parity analysis will be made according to two different perspectives. We consider the investment decision by a public institution ("Public Analysis" case), and compare it to the investment choice by a private investor ("Private Investor Analysis" case).

The values of LCOE are taken from two different sources. A first set of data is taken from Marchesi et al. (2010). This study has been commissioned to the Politecnico di Milano by AEEG. A second set of data is taken by a comprehensive study on the unit cost of different power generation technologies prepared by Salvadores and Keppler (2010a) for the IEA.

The LCOE of a PV system is highly sensitive to variations in the load factor and in the construction costs¹¹. The load factor, or capacity factor, is particularly important since it defines the amount of electricity produced per unit of generating capacity. It has a high impact on the unit cost because the percentage of fixed investment costs is really high for PV power plants. Variation of the load factor is markedly skewed to the right, revealing that plants are particularly sensitive to decreases in the load factor.

Construction costs account for nearly 95% of the whole cost of a PV plant. One of the key factors which drives construction costs is the scale of the installation: small residential PV plants present higher investment costs per kw/h compared to bigger utility scale plants. The discount rate is the third variable in order of importance. This is due to the short construction times of PV power generation technologies. The incidence of the economic lifetime variations has to be considered for the asymmetric distribution of its effects. While early retirement significantly increases the LCOE, lifetime extension have little or no impact. Clearly, early retirement have a strong impact on the ability to repay the initial capital investment. For this purpose, the lifetime considered in the work by Marchesi et al. (2010) is prudentially fixed around 20 years, while most studies use 25 or even 30 years. Finally, the absence of fuel costs is one of the major advantages of renewable energy sources, which are not influenced by the volatility of fuel prices.

4.1 The LCOE

The set of data from the work by Politecnico di Milano are used to run the "Public Analysis" case (Table 3). The low discount rate (i.e. 4%), used in the computation, well reflects the point of view of a public investor. Furthermore, this work takes into account the important effect of plant size: the LCOE is calculated for both 3kw (RESIDENTIAL) and 1Mw (UTILITY) installation.¹² The overall PV system cost highly depends on the size of the system and on whether the system is ground-or-roof-mounted-residential plants.

Table 3: Data from Marchesi et al. (2010)

Plant size	Discount rate	Economic lifetime	Capacity factor	Capital Expenditures°	0&M*	Assurance Costs*	LCOE 2010**
3 Kw	4%	20	14%	5.996	108	51	0,531
1000 Kw	4%	20	14%	3.425	39	9	0,257

(°) expressed in €/Kw

(*) expressed in €/Kw year

(**) expressed in €/Kwh

The data from Salvadores and Keppler (2010a) are used to run the "Private Investor Analysis" case (Table 4). These authors use two different discount factors: 5% and 10%, that best capture a risk premium. In the remain of the paper, the first hypothesis will be called IEA5 and the second IEA10. As we said before, the 10% discount rate is considered to internalize the technology and market risks so that a higher discount rate results in a higher LCOE¹³.

4.2 Learning Curves

To predict the dynamics of LCOE we follow the learning curve approach. In the specific, the learning curve approach is an empirical-based methodology, designed to describe the law of cost reduction for a specific industry, based on the assumption that at each doubling of cumulated output costs decrease by a stable percentage¹⁴.

There are several reasons that contributes to the ample diffusion of learning curves: i) the readiness of the empirical time series required for its computation – cumulative capacity and

Table 4:	Data fro	m Salvadores	and Keppler ((2010a))
----------	----------	--------------	---------------	---------	---

Discount rate	Economic lifetime	Capacity factor	Capital Expenditures°	0&M*	LCOE 2010 **
5%	25	16%	6.592	54	0,31
10%	25	16%	6.592	54	0,46
(0)	- 1				

(°) expressed in €/Kw

(*) expressed in €/Kw year

(**) expressed in €/Kwh

costs – facilitates the capability to test the model; ii) they are capable to express with a single parameter the complex process of innovation; iii) they are consistent with the theory that firms learn on past experience and iv) the learning rate is not usually linked to a time variable, but to variations in cumulative production and thus seems to be more suitable for forecasts on future costs. However, the experience curve approach presents also many cons. The decrease in costs is described by a unique parameter and so results are highly sensitive to the learning rate used, which is not able to describe discontinuities in costs. The experience curve does not consider the knowledge acquired from other sources like R&D expenditures and ignores changes in the quality of the output. Moreover, industry structure affects the learning rate and so, for an industry that is becoming more and more competitive like the photovoltaic one, the experience curve could over-estimate the rate of technical progress¹⁵.

While there is an ample literature on the advantage and use of learning curves, few sources have done an accurate analysis on how to use the learning curve approach for the PV industry Acanfora and Alcor (2011), Nemet (2006).

Following this approach, in Appendix C, we express the PV unit cost dynamics on both the average growth rate of the PV industry, GR, and the learning coefficient LN. The latter is calculated from the slope of the learning curve, called progress ratio (PR), that express the percentage of costs decrease at each doubling of cumulated capacity. That is:

$$LCOE_t = LCOE_0 e^{\alpha_C t} \tag{3}$$

where $\alpha_C = LN \cdot GR$ and $LN = \frac{\ln PR}{\ln 2}$.

To properly use (3) we need to calibrate α_C . Then we test if $LCOE_{2030}$ (the expected levelised cost for PV in 2030) is in line with the projected values of IEA, where $LCOE_0$ refers to the level of the italian Levelised Cost of Electricity in 2010.

As the industry has grown PV module prices have shown an important decline (Figure 5)¹⁶. In particular, from the first statistical data dating back to 1976 to the beginning of the 2000s, module prices decrease shows a learning rate, LR = (1 - PR), of about 22%. An excursion from this historical rate occurred due to supply bottlenecks and market dynamics – the so-called polysilicon-shortage – from 2003 to the end of 2008. Since then the learning curve returned toward its historic level, reaching a LR of about 19%. Nowadays, the IEA and EPIA expect further costs reduction due to increased production capacities, improved supply chains and economies of scale. Following Crespo et al. (2012), we use an average LR of 20%, which implies a PR of $80\%^{17}$.

Let's now consider the GR. Although the short-term expectations about the Italian PV market could be very volatile, a long-term definition of the expected dynamic of the market could be more reliable.¹⁸ In particular, we use two different GRs. In a first CONSERVATIVE scenario, we set GR = 10%. This is based on the forecasts of the 2012 Solar Energy Report for the Italian PV industry growth till 2020. In a second, more "optimistic", scenario we set



Figure 5: Learning curve dynamic – Data from Breyer and Gerlach (2010)

GR = 18%, considering the possibility of a new photovoltaic development in Italy boosted by the adoption of Smart Grids (SMART GRIDS scenario). This second scenario is in line with the EPIA expectations till 2020 (EPIA, 2012)¹⁹. Finally, by using the GR of the Italian PV industry in 2011, we update our starting point from 2010 to 2011.

Plugging the values for LN and GR in (3), in Table 5 we show our projections for the four cases considered. The 2020 LCOE projections made by the IEA are between $0.09 \in /K$ wh and $0.19 \in /K$ wh for the UTILITY sector and $0.12 \in /K$ wh and $0.23 \in /K$ wh for the RESIDENTIAL sector. Furthermore, both the SMART GRIDS scenario and the CONSERVATIVE one are in line with the IEA expectations²⁰, except for the RESIDENTIAL value, which is slightly over the range in the CONSERVATIVE case. Finally LCOE expectations for 2030 are within $0.07 \in /K$ wh and $0.15 \in /K$ wh that is the range proposed by the IEA.

Table 5: LCOE projections

CONSERVATIVE SCENARIO -	GR=10%	SMART GRIDS SCENARIO - GR=20%		
OUTPUTS	LCOE 2030	OUTPUTS	LCOE 2030	
RESIDENTIAL	0,17	RESIDENTIAL	0,10	
UTILITY	0,08	UTILITY	0,05	
IEA5	0,10	IEA5	0,06	
IEA10	0,15	IEA10	0,09	

Finally, Bosetti et al. (2012), by interviewing some of the major European PV market experts, calculate a range of values for LCOE in 2030. In this respect, most experts project that $LCOE_{2030}$ will lay between $0.05 \in /\text{Kwh}$ and $0.11 \in /\text{Kwh}$. These estimates, that are more optimistic than the ones by IEA, give further support to our learning model.

We conclude this section adding a volatility term to equation (3) to account for possible deviations of the learning rate from its historical trend. Deviations from the historical learning rate can be explained by variations in PV module costs, mainly due to silicon supply and demand conditions. However, since an estimate of the volatility of PV module prices is very difficult to compute we will use, as a proxy, the stock prices volatility of the four biggest global producers of PV modules (See Table 6).

Table 6: Weighted volatilities of the four major PV module producers, data from www.yahoofinance.com

LCOE VOLATILITY				
	VOL	MARKET SHARE	AJUSTED MARKET SHARE	VOLATILITY
SUNTECH	51%	6%	29%	14%
FIRST	69%	6%	29%	20%
YINGLI	39%	5%	24%	9%
TRINA	58%	4%	19%	11%
		21%	100%	54%

Following the approach used for the electricity price, we have estimated the stock price volatility for Yingli Soalr, First Solar, Suntech and Trina Solar. For the volatility of LCOE we calculate the average volatility of the four companies, weighted for their respective market shares. Table 7 sums up the data involved in the analysis.

 Table 7: Continuous time model inputs

LCOE CONTINUOUS TIME MODEL - INPUTS	DRIFT TERM	VOLATILITY
CONSERVATIVE SCENARIO	-3,22%	54%
SMART GRIDS SCENARIO	-6,44%	54%

This yields²¹:

$$\frac{dLCOE_t}{LCOE_t} = \alpha_C dt + \sigma_C dz, \qquad \text{where } \alpha_C = GR_C LN \tag{4}$$

where $\alpha_C = LN \cdot GR$ and σ_C expresses the module price volatility.

5 Grid Parity Dynamics

Grid Parity models express a break-even point for an investment in PV plants. Grid Parity is usually defined as the time t^* when PV installations become cost neutral and so the electricity price equals the levelised cost of PV generation (i.e. LCOE). Our Grid Parity analysis overcomes this definition. Our model is based on a wider view of Grid Parity timing, where the optimal t^* internalizes the value of the option to have more information about future evolution of both the electricity price and the unit cost of PV generation. In the next section we first calibrate a standard Grid Parity model and then we provide our Real Option Grid Parity model. For both the models we present two different sets of results. First, we analyse the Grid Parity from the point of view of a public investor ("Public"), focusing on residential and utility plants (RESI-DENTIAL, UTILITY). Second, we consider the private investor perspective ("Private"), where the LCOE is calculated using two different discount rates (IEA5, IEA10). Further, we calculate the Grid Parity time t^* considering a learning curve with a GR = 10% (CONSERVATIVE) and with GR = 20% (SMART GRIDS) and for both the GBM case and the Adj-GBM case.

5.1 The Standard Grid Parity Model

The aim of this section is to find the time t^* where the expected value of electricity prices equals the expected cost of PV plants, expressed by the LCOE²².

$$E_0(P_{t^*}) = E_0(LCOE_{t^*})$$
(5)

where $E_0(\cdot)$ is the expectation taken at time t = 0 with respect to (1) and (4) respectively. By substituting and solving for t^* , we get:

$$t^* = \max\left[\frac{\ln\left(\frac{LCOE_0}{P_0}\right)}{\alpha_P - \alpha_C}, 0\right]$$
(6)

Plugging our data into (6) we obtain:

Public Perspective Analysis

Grid Parity will be reached in 2013-2014 by UTILITY, while the RESIDENTIAL sector will reach the Grid Parity between 2016 and 2020.

Table 8: Standard Grid Parity Model - Public Analysis results

GEOMETRIC BROWNIAN MOTION			ADJ GBM			
	CONSERVATIVE	SMART GRIDS		CONSERVATIVE	SMART GRIDS	
RESIDENTIAL	ott-17	apr-16	RESIDENTIAL	dic-19	mag-17	
UTILITY	giu-13	gen-13	UTILITY	gen-14	mag-13	

In particular, the results for UTILITY are quite homogeneous. Given that electricity prices are already very close to the utilities' LCOEs, a different growth rate has not so much influence on Grid Parity timing. This result is coherent with the phase out of the Italian FIT program, where the end of the incentive schemes is more gradual for residential customers. On the other side, the RESIDENTIAL sector is strongly influenced by forecasts on future developments of the PV industry. Since the initial gap between prices and costs is higher, a higher growth rate has an important effect on Grid Parity timing. Specifically, when we take into account a lower drift for electricity prices (i.e. in Adj-GBM case), the gap between CONSERVATIVE and SMART GRIDS increases.

Accoding to Politecnico di Milano (2012) and Acanfora and Alcor (2011), our model concludes that residential customers should need some form of public intervention in the following years to reach Grid Parity: only through a sustained growth rate they will afford a cost-competitive investment. For this reason, the introduction of smart grids might have an important role on future expansions of the PV industry.

Private Investor Analysis

Table 9 shows that the results of the IEA5 scenario are in line with the EPIA forecasts, which consider the period between 2013 and 2015 for the ground-mounted PV systems to be cost-competitive. However, using the Adj-GBM, which uses a (lower) more reasonable growth rate in the price of electricity, we obtain a substantial delay.

Table 9:	Standard	Grid	Parity	Model -	Private	Analysis	results
			•/			•/	

	GEOMETRIC BROWNIAN N	NOTION		ADJ GBM	
	CONSERVATIVE	SMART GRIDS		CONSERVATIVE	SMART GRIDS
IEA5	giu-15	lug-14	IEA5	ott-16	mar-15
IEA10	set-19	set-17	IEA10	ago-22	feb-19

A delay is also obtained when LCOE considers a higher discount rate (IEA10). Note, however, that in the case of Adj-GBM a higher growth rate could anticipate the Grid Parity by about three years in the CONSERVATIVE case²³.

5.2 A Stochastic Model

The standard Grid Parity model presents two main shortcomings. First, it does not consider that an investment in a photovoltaic power plant is irreversible (construction costs account for 95% of the whole cost of a PV plant). Second, it does not take into account the opportunity of waiting to have more information about prices and market conditions before making the investment decision. In other words, the standard model ignores to add among the costs the opportunity cost of investing as soon as P equals LCOE.

To overcame these weakness, in this section, we use the Real Option approach to evaluate the Grid Parity timing. Indicating with F(P, LCOE), the value of the opportunity to invest in a PV project, this is given by:

$$F(P, LCOE) = E_0 \left[e^{-\mu t^{**}} \left(P_{t^{**}} - LCOE_{t^{**}} \right) \right]$$
(7)

where $\mu > 0$ is the risk-adjusted discount rate, t^{**} is the (stochastic) Grid Parity time defined as $t^{**} = \inf\{t \ge 0 : F(P_{t^{**}}, LCOE_{t^{**}}) = P_{t^{**}} - LCOE_{t^{**}}\}$, and $E_0(\cdot)$ is the expectation operator taken with respect to (1) and (4)²⁴. It is evident from (7) that the condition that identifies the Grid Parity is $P_{t^{**}} = LCOE_{t^{**}} + F(P_{t^{**}}, LCOE_{t^{**}})$, i.e. the price has to be equal the full cost (LCOE + opportunity costs) of making the investment. Standard arguments lead to a solution for (7) taking the following functional form (see Appendix D):

$$F(P, LCOE) = AP^{\beta}LCOE^{1-\beta}$$
(8)

where A is a positive constant and β is equal to:

$$\beta = \frac{\frac{1}{2}(\sigma_P^2 + \sigma_C^2) - (\alpha_P - \alpha_C) + \sqrt{\left(\frac{1}{2}(\sigma_P^2 + \sigma_C^2) - (\alpha_P - \alpha_C)\right)^2 + 2(\sigma_P^2 + \sigma_C^2)(\alpha_C - \mu)}}{\tilde{\sigma}^2} > 1,$$

while the optimal threshold is given by:

$$\frac{P^{**}}{LCOE^{**}} = \frac{\beta_1}{\beta_1 - 1}.$$
(9)

For the Grid Partiy t^{**} we should calculate the time that the ratio $\frac{P}{LCOE}$ takes to reach the investment trigger (9). In this regard, since $\frac{P}{LCOE}$ is stochastic t^{**} is stochastic as well, therefore we need to refer to the probability distribution of t^{**} . In particular, we calculate the average time (See Appendix D):

$$E(t^{**}) = m^{-1} \left[\ln \left(\frac{\beta_1}{\beta_1 - 1} \right) - \ln \left(\frac{P_0}{LCOE_0} \right) \right]$$
(10)

and the 95% confidence interval $E(t^{**}) \pm 1,96\sqrt{Var(t^{**})}$, where $m = \sigma_C^2 + \alpha_P - \alpha_C - \frac{1}{2}(\sigma_P^2 + \sigma_C^2)$ and $Var(t^{**})$ is the variance of the distribution of t^{**} .

To complete the analysis we need to compute the risk-adjusted cost of capital μ . We do this by using the Capital Asset Pricing Model formula $\mu = r + \mathbf{B}(MRP)$, where MRP is the market risk premium , **B** measures the systematic risk and r is the risk free interest rate. Following Fernandez et al. (2011), we use 5.50% for the Italian market risk premium. For the risk-free interest rate we take the average of the last 10 years interest rates on the Italian BTP (maturity 15 year) as published by the Italian "Dipartimento del Tesoro", i.e. r = 4.70%. Finally, for **B** we calculate the average unlevered betas of three representative European companies that produce electrical energy from renewable sources (see Table 10). Putting all this information toghether we obtain $\mu = 10.07\%$

Table 10: Beta estimation - Data from www.yahoofinance.com

	COUNTRY	BETA LEVERED	DEBT/EQUITY*	BETA DEBT	BETA UNLEVERED
THEOLIA	FRANCE	1,59	1,16	0,71	1,12
TERNA ENRGY	GREECE	0,98	0,49	0,15	0,71
GREEN TECH	DENMARK	1,67	0,81	0,41	1,11
AVERA	GE BETA				0.98

*debt/equity has been taken from the annual reports of the single companies or, alternatively, from yahoo finance data

Public Perspective Analysis

Table 11 shows the results for (10). Taking into account the opportunity cost of investing led, on average, to a ten years postponement of the equality between prices and full costs of the investment. In the specific, the optimal investment timing for RESIDENTIAL customers falls in between 2025 and 2027, while for UTILITY installations the best time to invest falls in between 2023 and 2025.

 Table 11: Stochastic Grid Parity Model - Public Analysis results

GEON	IETRIC BROWNIAN M	NOTION		ADJ GBM			
	CONSERVATIVE	SMART GRIDS		CONSERVATIVE	SMART GRIDS		
RESIDENTIAL	giu-27	giu-25	RESIDENTIAL	feb-27	feb-27		
UTILITIES	mar-25	lug-23	UTILITIES	giu-24	giu-24		

Yet, moving from the CONSERVATIVE scenario to the SMART GRID one the uncertainty surrounding P and LCOE has the same impact on UTILITY and RESIDENTIAL installations. The effect of the growth rate is smoothed with respect to the standard Grid Parity model and the difference between the GBM and Adj-GBM is virtually zero.

Private Investor Analysis

Even for a private investor the optimal investment timing will be postponed with respect to to the one calculated with the standard model. In particular the average time ranges between 2022 and 2024 in the lower 5% discount rate scenario and it is postponed till 2028 when LCOE is calculated with a 10% discount rate. In both cases, a 10% increase in the learning rate anticipates by two years the investment decision (see Table 12).

Table 12: Stochastic Grid Parity Model - Private Analysis results

	GEOMETRIC BROWNIAN N	NOTION		ADJ GBM			
	CONSERVATIVE	SMART GRIDS		CONSERVATIVE	SMART GRIDS		
IEA5	giu-24	nov-22	IEA5	set-25	set-25		
IEA10	giu-28	apr-26	IEA10	apr-28	apr-28		

The above results show how the Grid Parity is mainly driven by uncertainties over prices and costs. To highlight this effect in Figure 6 we conduct some comparative statics analysis with respect to $Var(t^{**})$. According to the Real Options approach, the average time reduces as the uncertainty decreases up to converge to the deterministic case represented by the Standard



Figure 6: Sensitivity analysis with respect to price volatility.

Model. Finally, we conclude showing in Figure 7, for all cases, the respective 95% confidence intervals. Comparing the confidence intervals of the Conservative scenario and the Smart Grids one, we can see that, when the assumed growth rate of the PV industry is higher, confidence intervals are lower. Our expectations are more precise.



(a) Confidence Intervals for the Conservative Scenario - GBM framework.



(b) Confidence Intervals for the Smart Grids Scenario - GBM framework.

6 Final Remarks

Calibration of the standard Grid Parity model confirms literature's findings. Due to relatively high electricity prices and good solar irradiation, the PV Grid Parity is going to be reached soon in Italy. In the case of a private investor, for example, the Grid Parity can be reached in 2015 while considering a public perspective, the Grid Parity can be reached by 2014.

However, the break-even analysis behind the standard model does not take into account two important aspects of a decision to invest in a PV system: the sunkness of the investment cost and the uncertainty related to both the electricity prices and the energy generation costs.

In this paper we take into account both of these aspects by calibrating a Real Option model of the Grid Parity. The high volatility of energy prices and the uncertain future path of module costs give rise to a high value to wait before investing in a PV plant. Our stochastic model changes substantially the investment decision, well describing the current market situation. In the case of the private investor, for example, Grid Parity can be postponed until 2025, while considering a public perspective, the optimal time to invest in a PV system can be postponed up to ten years.

A The Dickey Fuller test

The simplest way to test for a unit root is by running the following regression:

$$p_t - p_{t-1} = \alpha + \theta p_{t-1} + e_t$$
. (A.1)

where p_t is the natural logarithm of electricity prices P_t and $E(e_t | p_{t-1}, p_{t-2}, \ldots, p_0) = 0$ in accordance with the use of a Wiener process. The process has a unit root if and only if $\theta = 0$. Yet, if $\alpha = 0$ and $\theta = 0$, p_t follows a random walk without drift, while if $\alpha \neq 0$ and $\theta = 0$, p_t is a random walk with drift²⁵. The null hypothesis is that p_t has a unit root $H_0: \theta = 0$ against $H_1: \theta < 0$. We dispose of 8 years monthly data on electricity prices, from April 2004 to December 2011, taken from the statistical publications of the GME (Gestore Mercati Energetici). As shown in Table 13 given a critical value of -2, 706 for the test, we fail to reject the null hypothesis that the process has a unit root at the 5% significance level.

Table 13

Z(t)	-2.706	-3.538	-2.906	-2.588
	Test Statistic	1% Critical Value	5% Critical Value	10% Critical Value
Augmented	Dickey-Fuller test	for unit root	Number of obs	= 80
. dfuller	LOGPRICE, lags(12)			

MacKinnon approximate p-value for Z(t) = 0.0729

We obtain the same results running the regression (A.2) where we include 12 additional lags to control for autocorrelation:

$$\Delta p_{t} = \alpha + \theta p_{t-1} + \sum_{i=1}^{12} \gamma_{i} \,\Delta p_{t-i} + e_{t}.$$
(A.2)

where rendregress is the log returns of electricity prices, ptmeno1 is p_{t-1} and the other values presents the γ_i coefficients of Δp_{t-1} . The coefficient of p_{t-1} is statistically different from 0, i.e. $\theta = -0,223$ with a t – statistics of -2,71. Note that only the γ_i at the 12th lag is statistically significant.

B Cost components for photovoltaic energy systems

We define the LCOE as the cost that, if assigned to every unit of energy produced by the system over the lifetime period, will equal the total lifetime cost, when discounted back to the base year. That is:

$$\sum_{t=1}^{N} \frac{Electricity_t \cdot LCOE}{(1+r)^t} = \frac{\sum_{t=1}^{N} (Capex_t + Opex_t + Assurance_t)}{(1+r)^t}$$

or

$$LCOE = \frac{\sum_{t=1}^{N} (Capex_t + O\&Mpex_t + Assurance_t) \cdot (1+r)^{-t}}{\sum_{t=1}^{N} Electricity_t \cdot (1+r)^{-t}}$$
(B.1)

Table 14:

	reg	rendregress	ptmeno1	deltapt1	deltapt2	deltapt3	deltapt4	deltapt5	deltapt6	deltapt7	deltapt8	deltapt9	del
>	tapt	10 deltapt1	1 deltap	t12									

Source	SS	df	MS		Number of obs	= 80
Model Residual	.28375555 .48028634	13 66	.02182735 .007277066		F(13, 66) Prob > F R-squared	= 3.00 = 0.0017 = 0.3714
Total	.764041889	79	.009671416		Adj R-squared Root MSE	= 0.2476 = .08531
rendregress	Coef.	Std. E	rr. t	P> t	[95% Conf.	Interval]
ptmeno1 deltapt1 deltapt2 deltapt3 deltapt4 deltapt5 deltapt6 deltapt7 deltapt8 deltapt10 deltapt11 deltapt12	2228634 .0155378 .0890547 0701103 .0862973 .1762118 .151459 .0744898 .0348012 0588186 .0476605 0580206 .2885621	.082348 .124074 .120867 .119114 .113483 .113209 .114986 .116227 .114382 .11229 .109822 .109822 .097706	$\begin{array}{rrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrrr$	1 0.009 3 0.901 4 0.464 9 0.558 6 0.450 6 0.124 2 0.192 4 0.524 0 0.762 2 0.602 3 0.666 8 0.566 5 0.004	3872768 2321847 152265 3079297 1402792 049818 0781191 1575662 1935703 2830194 1716067 2586058 .0934969	0584499 .2632603 .3303744 .1677991 .3128738 .4022417 .381037 .3065458 .2631727 .1653822 .2669277 .1425645 .4836273
_cons	.9485971	.348174	46 2.72	2 0.008	.2534441	1.64375

where r is the discount factor (assumed to be constant), N is the economic life of the system, $Electricity_t$ is the electricity produced by the plant in year t, $Capex_t$ are annualized capital expenditures²⁶, $O\&Mpex_t$ are the operating and maintenance costs for each year and $Assurance_t$ is the annual assurance cost. The capital cost, Capex, can be divided in two major components: the price of the PV module and the Balance Of System costs (BOS). The price of the PV module clearly depend on the price of silicon, while the BOS costs are linked to the price of the inverter, the costs for the structural installation and other wiring and installation costs. The price of the module is typically between a third and a half of the total capital cost and has been one of the driving forces of PV costs reduction. O&Mpex costs have a low incidence on LCOE, photovoltaic is well known to have low annual operational costs and low needs for maintenance during its life²⁷. Finally, it is worth mentioning the important cost of assurance needed to cover the risk that the modules are stolen.

Further, we have to consider two important parameters that influence the output (*Electricity*): the level of solar irradiation and the efficiency of solar cells. They will be both synthetized by the net Capacity Factor. The net Capacity Factor is the ratio of the actual output of a power plant over a period of time and its potential output if it had operated at full nameplate capacity the entire time (www.nrc.gov). Both solar irradiation and the efficiency of solar cells contribute to its variations and so the latitude of the installation site is crucial for the cost of PV systems.

Finally, given that LCOE is based on a DCF analysis, where the costs are computed discounting annual flows to a common basis, we have to take into consideration the time value of money. This value is not necessarily the same for all investors and it is influenced by a variety of factors, such as the investor rate of return, risk premium, planning horizon and others.

C A continuous-time learning model

The base formulation of a learning curve (see Nemet 2006), takes the cost of the N-th unit produced as a proxy of the cumulated experience, while the dependent variable is the cumulated production, which provides a measure of learning and technological improvement. That is:

$$C_N = C_0 N^{LN} \tag{C.1}$$

where C_N is the cost of the N - th unit produced, C_0 is the cost of the first unit, N is the cumulated production and LN is the learning curve coefficient. Assuming that costs decrease by a fixed amount every time quantity doubles, we are able to express the slope of the learning curve, called progress ratio (PR), by the percentage of costs decrease at each doubling of cumulated capacity. That is, $PR = 2^{LN}$ or, $LN = \frac{\ln PR}{\ln 2}$.

Let now define the annual capacity installations of the photovoltaic industry as follows:

$$W_s = W_{s-1}(1 + GR), \qquad s \ge 1$$
 (C.2)

where W_s is the capacity installed in year s and GR is the average growth rate of the PV industry, assumed to be constant. The cumulative capacity up to t > s can be calculated as:

$$W_t = W_0 \sum_{s=0}^t (1 + GR)^s$$

Substituting this definition of cumulative capacity in equation (C.2), and considering LCOE as the unit cost, we can write the learning relationship as follow²⁸.

$$LCOE_t = LCOE_0 \left(\sum_{s=0}^t (1+GR)^s\right)^{LN}$$
(C.3)

This discrete-time learning model is the same used by Breyer and Gerlach (2010), derived from Wright (1936) (the so-called Wright's cumulative model). Taking m as the detection frequency of the growth rate – usually expressed in annual terms – we can rewrite the previous expression as follows:

$$LCOE_t = LCOE_0 \left(\sum_{s=0}^t \left(1 + \frac{GR}{m} \right)^{sm} \right)^{LN}.$$
 (C.4)

Letting $m \to \infty$ equation (C.4) reduces to:

$$LCOE_{t} = LCOE_{0} \left(\int_{0}^{s} e^{GRs} ds \right)^{LN}$$

= $LCOE_{0} e^{LN \ln\left(\frac{1}{GR}(e^{GRt} - 1)\right)}.$ (C.5)

Now, from (C.5) it is easy to show that the rate of change is equal to:

$$\frac{dLCOE_t}{LCOE_t} = LN \, GR \frac{e^{GRt}}{e^{GRt} - 1} dt$$

which is driven by both the average growth rate of the PV industry GR and the learning curve coefficient LN. Since $\frac{e^{GRt}}{e^{GRt}-1} \rightarrow 1$ as t increases, for the sake of simplicity, we reduce the LCOE's rate of change as:

$$\frac{dLCOE_t}{LCOE_t} = \alpha_C dt, \qquad \text{where } \alpha_C = LN \, GR \tag{C.6}$$

D Equations (9) and (10)

Writing C for LCOE, equation (7) becomes:

$$F(P,C) = E_0 \left[e^{-\mu t^{**}} \left(P_{t^{**}} - C_{t^{**}} \right) \right].$$

The general solution for F(P, C) as well as the optimal Grid Parity threshold $P_{t^{**}} - C_{t^{**}}$ can be obtained by verifying that the expected change of F(P, C) satisfies a second-order linear differential equation under some suitable boundary conditions at t^{**} . By applying a standard dynamic programming approach, the project's value, F(P, C), solves the following Bellman equation:

$$\mu F(P, C)dt = E_0 [dF(P, C)].$$
(D.1)

Using Itô's Lemma, we can expand dF(P, C) and rearrange (D.1) as follows:

$$\frac{1}{2}(\sigma_P^2 P^2 F_{PP} + \sigma_C^2 C^2 F_{CC}) + P \alpha_P F_P + C \alpha_C F_C - \mu F = 0$$
(D.2)

where F_{PP} , F_{CC} , F_P and F_C are the first and second partial derivative with respect P and C. Since F(P,C) is homogeneous of degree 1 in (P,C) allows us to reduce it to one dimension. The optimal decision should therefore depend only on the ratio $p \equiv \frac{P}{C}$, i.e.:

$$F(P,C) = Cf\left(\frac{P}{C}\right) = Cf(p)$$

where f is now the function to be determined. Successive differentiation gives

$$F_P(P,C) = f'(p), \qquad F_C(P,C) = f(p) - pf'(p)$$

$$F_PP(P,C) = \frac{f''(p)}{C} \qquad F_PC(P,C) = -\frac{pf''(p)}{C}, \qquad F_CC(P,C) = \frac{p^2f''(p)}{C}.$$

Substituting these into (D.2) and grouping terms, we get:

$$\frac{1}{2} \left(\sigma_P^2 + \sigma_C^2 \right) p^2 f''(p) + (\alpha_P - \alpha_C) p f'(p) + (\alpha_C - \mu) f(p) = 0.$$
(D.3)

This is an ordinary differential equation for the unknown function f(p) of the scalar independent variable p. Its boundary conditions can be defined as follows:

$$f(p) = p - 1 \tag{D.4}$$

$$f'(p) = 1, \qquad f(p) - pf'(p) = -1.$$
 (D.5)

The solution of (D.3) takes the form:

$$f(p) = Ap^{\beta} \tag{D.6}$$

where $\beta > 1$ is the positive root of the quadratic equation $\frac{1}{2}(\sigma_P^2 + \sigma_C^2)x(x-1) + (\alpha_P - \alpha_C)x + (\alpha_C - \mu) = 0$, and the optimal threshold is given by:

$$p^{**} = \frac{P^{**}}{C^{**}} = \frac{\beta}{\beta - 1}.$$
 (D.7)

We are now able to compute the average time that the process p_t takes to reach the trigger p^{**} , starting from a point $p_t < p^{**}$. By applying Itô's Lemma to $\ln p_t$ we get:

$$d\ln p = \left(\sigma_C^2 + \alpha_P - \alpha_C - \frac{1}{2}(\sigma_C^2 + \sigma_P^2)\right)dt - \sigma_C dz_C + \sigma_P dz_F$$

The mean time that $\ln p_t$ takes to reach the upper trigger $\ln p^{**}$ for the first time is given by:

$$E(t^{**}) = m^{-1} \log\left(\frac{\frac{\beta}{\beta-1}}{p_0}\right),\tag{D.8}$$

where *m* is the constant drift $(\sigma_C^2 + \alpha_P - \alpha_C - \frac{1}{2}(\sigma_C^2 + \sigma_P^2))$, $p_0 = \frac{P_0}{C_0}$ and the variance is $Var(t^{**}) = \frac{(p^{**} - p_0)(\sigma_C^2 + \sigma_P^2)}{2(\sigma_C^2 + \alpha_P - \alpha_C - \frac{1}{2}(\sigma_C^2 + \sigma_P^2))^3} {^{29}}$.

References

- A. Acanfora and E. Alcor. Solar photovoltaics competing in the energy sector on the road to competitiveness. Technical report, European Photovoltaic Industry Association, Semptember 2011.
- A. Acanfora and E. Alcor. Global market outlook for photovoltaics until 2016. Technical report, European Photovoltaic Industry Association, May 2012.
- M. Bazilian, I. Onyeji, M. Liebreich, and I. MacGill. Re-considering the economics of photovoltaics power. *United Nations Industrial Development Organization*, 2009.
- J. Belien, L. De Boeck, J. Colpaert, and G. Cooman. The best time to invest in photovoltaic panels in flandres. *Renewable Energy*, 50:348 358, February 2013.
- R. Bhandari and I. Stadler. Grid parity analysis of solar photovoltaic systems in germany using experience curves. *Solar Energy*, 83(9):1634–1644, 2009.
- Valentina Bosetti, Michela Catenacci, Giulia Fiorese, and Elena Verdolini. The future prospect of pv and csp solar technologies: An expert elicitation survey. *Fondazione ENI Enrico Mattei*, 2012.
- C. Breyer and A. Gerlach. Global overview on grid-parity event dinamics. Technical report, Q-cells, Valencia, September 2010.
- D. R. Cox and H. D. Miller. The teory of stochastic processes. Chapman and Hall, 1997.
- L. Crespo, Z. Dobrotkova, C. Philibert, C. Richter, and G. Simbolotti. Renewable energy cost analysis - solar photovoltaics. Technical report, IRENA: International Renewable Energy Agency, June 2012.
- S. B. Darling, F. You, T. Veseka, and A. Velosa. Assumptions and the levelized cost of energy for photovoltaics. *Energy & Environmental Science*, 4:3133–3139, 2011.
- A. Dmouj. Stock Price Modelling: Theory and practice. PhD thesis, Vrije Universiteit in Amsterdam, November 2006.
- A. Escribano, J.I. Pena, and P. Villaplana. Modelling electricity prices: International evidence. Oxford Bullettin of Economics and Statistics, 73(5):622 – 650, October 2011.
- P. Fernandez, J. Agiuremalloa, and L. Corres. Market risk premium used in 56 countries in 2011: A survey with 6.014 answers. Working Paper, May 2011.
- GME. Relazione annuale. Technical report, GME, 2011.
- P. Lorenz, D. Pinner, and T. Seitz. The economics of solar power. *The McKinsey Quarterly*, 2008.

- R. Marchesi, P. Bombarda, A. Casalegno, L. Colombo, and A. Rota. Costi di produzione di energia elettrica da fonti rinnovabili. Report ordered by aeeg to politecnico di milano - dipartimento di energia, Politecnico di Milano - Dipartimento di Energia, 2010.
- M. Mitscher and R. Rutter. Economic performance and policies for grid-connected residential solar photovoltaic system in brazil. *Energy Policy*, 48:688 – 694, July 2012.
- G. F. Nemet. Beyond the learning curve: factors influencing cost reductions in photovoltaics. Energy Policy, 34:3218 – 3232, 2006.
- S. Ong, P. Denholm, and N. Clark. Grid parity for residential photovoltaics in the united states: Key drivers and sensitivities. Technical report, National Renewable Energy Laboratory, 2012.
- Politecnico di Milano. Solar energy report: Il sistema industriale italiano nel business dell'energia solare. Technical report, Dipartimento di Ingegneria Gestionale, 2012.
- R. Renò. I prezzi dell'energia elettrica: proprietà e modelli. PhD thesis, Università di Siena, 2006.
- M. S. Salvadores and J. H. Keppler. Projected costs of generating electricity. Technical report, IEA: International Energy Agency and NEA: Nuclear Energy Agency, 2010a.
- M. S. Salvadores and J. H. Keppler. Technology roadmaps: Solar photovoltaic energy. Technical report, International Renewable Energy Agency, 2010b.
- Theodore Paul Wright. Factors affecting the cost of airplanes. *Journal of Aeronautical Sciences*, 3:122–128, 1936.
- C. J. Yang. Reconsidering solar grid parity. Energy Policy, 38:3270 3273, 2010.

Notes

¹The first Conto Energia was issued with, D.L. 387 2003 and Decreto Attuativo July 28, 2005; the fifth Conto Energia was issued with, D.M. July 5, 2012.

²This article outlined three key points for governments and regulators to set a sustainable PV-support program. First, Governments had to "Clarify objectives", before establishing the support policy, deciding the goals of the public intervention. Second, Governments had to "reward production, not capacity", creating the incentives to increase cost-efficiency. Third, Governments had to "phase out subsidies carefully", to avoid creating a vicious cycle after the reaching of Grid Parity.

³Different types of plants will reach Grid Parity in different moments.

 $^4\mathrm{The}$ annual volatility is around 30% , see Renò (2006) and Dmouj (2006).

⁵See Escribano et al. (2011) and for the Italian case the annual reports by GME (Gestore Mercati Energetici). ⁶Assuming that the state variable follows a lognormal random walk is standard in real-option models. However, alternative processes, such as mean-reverting, can be used. This would complicate the analysis, without

significantly changing the results . ⁷The log returns of Italian electricity prices present some border values, which are higher than the standard

normal distribution. This is in line with the general observation about the presence of fat tails in different financial time series.

⁸We can easily transform monthly data in an annual data by the following formula:

$$\sigma_{yearly} = \sqrt{12 : \sigma_{monthly}^2}$$

⁹The parameter η can be calculate by using the formula $-\log(\theta + 1)$, where θ is the coefficient of p_{t-1} in the regression A.2 in the Appendix A (see Dixit and Pindyck 1994, pp. 74-79)

¹⁰As Breyer and Gerlach (2010), we are using the end user price to compute our Grid Parity. Clearly, the break even point for industrial or domestic consumers have to be computed on their reference prices.

¹¹The values of LCOE depend mainly on the assumptions made for its calculation. For an accurate analysis of costs concerning the photovoltaic power generation plants, it is useful to present the effects of the variation of

single cost component on LCOE. The sensitivity results reported in this paper are taken from the Salvadores and Keppler (2010a) and from Darling et al. (2011)

 12 As matter of fact, a minimum and a maximum LCOE are calculated for each plant size. We take the average to have a single value.

¹³For the sake of completeness, it is important to mention some key methodology assumptions used in both studies. PV modules can be divided in two different categories: thin film modules and crystalline silicon modules. Being this lasts the most diffused on the market, both studies refer only to this category. For the assurance cost, the estimates are based on direct and indirect damages coverage and theft coverage. For the choice of the capacity factor, both works consider 1250 hours of operation per year and a capacity factor of 14-16%. Clearly, being Italy a peninsula with different levels of solar radiations, southern regions have higher capacity factors than the northern ones. This important issue is not at stake in our model. Finally, it is important to underline that taxes are excluded from the computation of the LCOE.

¹⁴For more details about the learning curve approach see Nemet (2006).

¹⁵From 2004 to the third quarter of 2008 the price of PV modules remained flat, despite manufactures were making continuous improvements and scale to reduce their costs. This was due to the fact that German and Spanish tariff incentives allowed project developers to buy the technology at those prices. The 18 largest quoted solar companies followed by Bloomberg made average operating margins of 15% Bazilian et al. (2009). When the Spanish incentive regime ended abruptly at the end of September 2008 global demand had a sudden deceleration, while silicon availability increased. This sudden need to compete on prices pushed PV constructors to reduce margins. They were able to drop their prices by 50% and still make a positive margin, given the costs reductions achieved in past years. In addition, following the understanding and comfort of PV deployment risks, financing costs were falling. Nowadays, the recent excess production capacity can push the price to fall to the level of marginal production costs, having important implication on future PV module prices. In Germany Q-cells and Solon have announced bankruptcy between the end of 2011 and April 2012 and the U.S. First Solar closed its European operation in April 2012. For this main reasons, some have argued that prices are below sustainable levels and might even gave to rise slightly. However, technological advancements, process improvements and changes in the structure of the industry suggest that further price reductions are likely to occur in coming years Bazilian et al. (2009)

¹⁶PV learning curves are computed at module level, because module costs account for nearly a half of the total LCOE.

¹⁷The progress ratio is equal 1 minus the learning ratio, it express the cost decrease of the future years at each doubling of cumulated output.

¹⁸In the 2012 "Solar Energy Report", there is a medium term punctual forecast on the possible PV installations for 2012 and 2013. The expectations for 2012 define a 20% increase of the PV market, with the construction of 2,7 GW of new plants. For 2013, taking into account the interactions between the actual "5th Conto Energia" and the end of the incentive system, the market is expected to growth by 10%, with 1.475 Mw of new installed plants.

¹⁹Both GRs are adjusted for taking account that (3) expresses the dynamic of LCOE in continuous time.

 $^{20}\mathrm{IEA5}$ and IEA10 are both referred to the Utility sector.

 $^{21}\mathrm{We}$ work under the assumption of a GBM.

 22 This model is equal to the one used by Breyer and Gerlach (2010)

 $^{23}{\rm This}$ result is a consequence of the learning curve which expresses an historical 20% learning rate for the PV industry.

 24 We assume that correlation between (1) and (4) is null throughout the whole analysis.

 25 The equivalent of the GBM in discrete time.

 26 The annualized capital expenditures are obtained trough the use of the capital recovery factor (CRF), the CRF simply converts a present value into a stream of equal annual payments over a specified time period at a given discount rate.

 $^{27}\mathrm{In}$ the study made by the Politecnico di Milano, O&Mpex costs are on average 1,5% of the total costs for PV.

 28 What we do, in practice, is to transform a volume-dependent formula, usually used to express learning curves, in a time-dependent formula, which is more suitable for our analysis.

²⁹Obviously m should be positive; otherwise $E(t^{**}) = \infty$ (see Cox and Miller (1997) p. 221-222).

NOTE DI LAVORO DELLA FONDAZIONE ENI ENRICO MATTEI

Fondazione Eni Enrico Mattei Working Paper Series

Our Note di Lavoro are available on the Internet at the following addresses: http://www.feem.it/getpage.aspx?id=73&sez=Publications&padre=20&tab=1 http://papers.ssrn.com/sol3/JELJOUR_Results.cfm?form_name=journalbrowse&journal_id=266659 http://ideas.repec.org/s/fem/femwpa.html http://www.econis.eu/LNG=EN/FAM?PPN=505954494

http://ageconsearch.umn.edu/handle/35978

http://www.bepress.com/feem/

NOTE DI LAVORO PUBLISHED IN 2013

CCSD CCSD	1.2013 2.2013	Mikel Bedayo, Ana Mauleon and Vincent Vannetelbosch: <u>Bargaining and Delay in Trading Networks</u> Emiliya Lazarova and Dinko Dimitrov: <u>Paths to Stability in Two-sided Matching with Uncertainty</u>
CCSD CCSD	3.2013 4.2013	Luca Di Corato and Natalia Montinari: <u>Flexible Waste Management under Uncertainty</u> Sergio Currarini, Elena Fumagalli and Fabrizio Panebianco: <u>Games on Networks: Direct Complements and</u>
ES	5.2013	Indirect Substitutes Mirco Tonin and Michael Vlassopoulos: <u>Social Incentives Matter: Evidence from an Online Real Effort</u>
CCSD	6 2012	Experiment Mary Sarr and Tim Swanson: Corruption and the Currey The Distator's Choice
CCSD	7 2013	Michael Hoel and Aart de Zeeuw: Technology Agreements with Heterogeneous Countries
CCSD	8 2013	Robert Pietzcker, Thomas Longden, Wenving Chen, Sha Fu, Elmar Kriegler, Page Kyle and Gunnar Luderer:
CCJD	0.2013	Long-term Transport Energy Demand and Climate Policy: Alternative Visions on Transport Decarbonization in Energy Economy Models
CCSD	9.2013	Walid Oueslati: Short and Long-term Effects of Environmental Tax Reform
CCSD	10.2013	Lorenza Campagnolo, Carlo Carraro, Marinella Davide, Fabio Eboli, Elisa Lanzi and Ramiro Parrado: <u>Can</u>
CCSD	11.2013	William A. Brock, Anastasios Xepapadeas and Athanasios N. Yannacopoulos: <u>Robust Control of a Spatially</u> <u>Distributed Commercial Fishery</u>
ERM	12.2013	Simone Tagliapietra: <u>Towards a New Eastern Mediterranean Energy Corridor? Natural Gas Developments</u> Between Market Opportunities and Geopolitical Risks
CCSD	13.2013	Alice Favero and Emanuele Massetti: <u>Trade of Woody Biomass for Electricity Generation under Climate</u>
CCSD	14.2013	Alexandros Maziotis, David S. Saal and Emmanuel Thanassoulis: <u>A Methodology to Propose the X-Factor in</u>
CCSD	15 2013	Alexandros Maziotis David S. Saal and Emmanuel Thanassoulis: Profit. Productivity. Price and Quality
CCSD	15.2015	Performance Changes in the English and Welsh Water and Sewerage Companies
CCSD	16.2013	Caterina Cruciani, Silvio Giove, Mehmet Pinar and Matteo Sostero: <u>Constructing the FEEM Sustainability</u>
CCSD	17.2013	Ling Tang, Qin Bao, ZhongXiang Zhang and Shouyang Wang: <u>Carbon-based Border Tax Adjustments and</u>
CCSD	18.2013	Giulia Fiorese, Michela Catenacci, Valentina Bosetti and Elena Verdolini: <u>The Power of Biomass: Experts</u>
		Disclose the Potential for Success of Bioenergy Technologies
CCSD	19.2013	Charles F. Mason: <u>Uranium and Nuclear Power: The Role of Exploration Information in Framing Public</u> <u>Policy</u>
ES	20.2013	Nuno Carlos Leitão: <u>The Impact of Immigration on Portuguese Intra-Industry Trade</u>
CCSD	21.2013	Thierry Bréchet and Henry Tulkens: <u>Climate Policies: a Burden or a Gain?</u>
ERM	22.2013	Andrea Bastianin, Marzio Galeotti and Matteo Manera: <u>Biofuels and Food Prices: Searching for the Causal</u> Link
ERM	23.2013	Andrea Bastianin, Marzio Galeotti and Matteo Manera: <u>Food versus Fuel: Causality and Predictability in</u> Distribution
ERM	24.2013	Anna Alberini, Andrea Bigano and Marco Boeri: <u>Looking for Free-riding: Energy Efficiency Incentives and</u> Italian Homeowners
CCSD	25.2013	Shoibal Chakravarty and Massimo Tavoni: <u>Energy Poverty Alleviation and Climate Change Mitigation: Is</u>
FRM	26.2013	Manfred Hafner and Simone Taglianietra: East Africa: The Next Game-Changer for the Global Gas Markets?
CCSD	27.2013	Li Ping, Yang Danhui, Li Pengfei, Ye Zhenyu and Deng Zhou: <u>A Study on Industrial Green Transformation in</u>
CCSD	28.2013	Francesco Bosello, Lorenza Campagnolo, Carlo Carraro, Fabio Eboli, Ramiro Parrado and Elisa Portale:
CCSD	29,2013	Stéphane Hallegatte: An Exploration of the Link Between Development Economic Growth and Natural Risk
CCSD	30.2013	Klarizze Anne Martin Puzon: <u>Cost-Reducing R&D in the Presence of an Appropriation Alternative: An</u>
		Application to the Natural Resource Curse
CCSD	31.2013	Johannes Emmerling and Massimo Tavoni: <u>Geoengineering and Abatement: A 'flat' Relationship under</u> <u>Uncertainty</u>

ERM	32.2013	Marc Joëts: Heterogeneous Beliefs, Regret, and Uncertainty: The Role of Speculation in Energy Price
EC	22 2012	Dynamics Carlo Alternante and Armando Bungir Business Croups as Hierarchies of Firms: Determinants of Vertical
ES	55.2015	Carlo Altomonie and Armando Rungi: <u>Dusiness Groups as Hierarchies of Firms: Determinants of Vertical</u>
CCSD	34 2013	Inegration and Performance Joëlle Noailly and Roger Smeets: Directing Technical Change from Fossil-Fuel to Renewable Energy
CCSD	01.2010	Innovation: An Empirical Application Using Firm-Level Patent Data
CCSD	35.2013	Francesco Bosello, Lorenza Campagnolo and Fabio Eboli: <u>Climate Change and Adaptation: The Case of</u>
		Nigerian Agriculture
CCSD	36.2013	Andries Richter, Daan van Soest and Johan Grasman: <u>Contagious Cooperation, Temptation, and Ecosystem</u>
		<u>Collapse</u>
CCSD	37.2013	Alice Favero and Robert Mendelsohn: <u>Evaluating the Global Role of Woody Biomass as a Mitigation</u>
CCCD	20 2012	<u>Strategy</u> Exist De Cien Michael Colomba Flanc Vandelini and Colombia Vaiete Example to avier Developments in
CCSD	38.2013	An Major Economics: Structural Change or Technology Improvement?
FS	39 2013	<u>An Major Economies, Structural Change of Technology Improvement:</u> Nuno Carlos Leitão, Bogdan Dima and Dima (Cristea) Stefana: Marginal Intra-industry Trade and
LJ	55.2015	Adjustment Costs in Labour Market
CCSD	40.2013	Stergios Athanassoglou: <u>Robust Multidimensional Welfare Comparisons: One Vector of Weights, One Vote</u>
CCSD	41.2013	Vasiliki Manousi and Anastasios Xepapadeas: <u>Mitigation and Solar Radiation Management in Climate</u>
		Change Policies
CCSD	42.2013	Y. Hossein Farzin and Ronald Wendner: Saving Rate Dynamics in the Neoclassical Growth Model -
		Hyperbolic Discounting and Observational Equivalence
CCSD	43.2013	Valentina Bosetti and Elena Verdolini: <u>Clean and Dirty International Technology Diffusion</u>
CCSD	44.2013	Grazia Cecere, Susanna Mancinelli and Massimiliano Mazzanti: <u>Waste Prevention and Social Preferences:</u>
	45 2012	Ine Role of Intrinsic and Extrinsic Motivations Mattee Manara, Marcalla Nicolini and Ilaria Vignati: Eutures Price Velatility in Commodities Markets: The
	43.2013	Role of Short Term vs Long Term Speculation
ERM	46.2013	Lion Hirth and Inka Ziegenhagen: Control Power and Variable Renewables A Glimpse at German Data
CCSD	47.2013	Sergio Currarini and Francesco Feri: Information Sharing Networks in Linear Quadratic Games
CCSD	48.2013	Jobst Heitzig: Bottom-Up Strategic Linking of Carbon Markets: Which Climate Coalitions Would Farsighted
		Players Form?
CCSD	49.2013	Peter Coles and Ran Shorrer: Optimal Truncation in Matching Markets
CCSD	50.2013	Heinrich H. Nax, Bary S. R. Pradelski and H. Peyton Young: <u>The Evolution of Core Stability in Decentralized</u>
CCCD	54 0040	Matching Markets
CCSD	51.2013	Manuel Forster, Michel Grabisch and Agnieszka Rusinowsk: <u>Anonymous Social Influence</u>
FS	52.2015	Nizar Allouch: The Cost of Segregation in Social Networks
LJ	55.2015	Information Acquisition
ES	54.2013	Roberta Distante, Ivan Petrella and Emiliano Santoro: Asymmetry Reversals and the Business Cycle
CCSD	55.2013	Thomas Michielsen: Environmental Catastrophes under Time-Inconsistent Preferences
ERM	56.2013	Arjan Ruijs and Herman Vollebergh: Lessons from 15 Years of Experience with the Dutch Tax Allowance for
		Energy Investments for Firms
ES	57.2013	Luciano Mauro and Francesco Pigliaru: <u>Decentralization, Social Capital and Regional Convergence</u>
CCSD	58.2013	Alexandros Maziotis, Elisa Calliari and Jaroslav Mysiak: <u>Robust Institutions for Sustainable Water Markets:</u>
CCED	50 2012	A Survey of the Literature and the Way Forward
CCSD	59.2015	Enrica De Cian, Fabio Sterra and Massimo Tavoni: <u>The Influence of Economic Growth, Population, and</u>
CCSD	60 2013	Eabio Sferra and Massimo Tavoni: Endogenous Participation in a Partial Climate Agreement with Open
CCSD	00.2010	Entry: A Numerical Assessment
ES	61.2013	Daniel Atzori: The Political Economy of Oil and the Crisis of the Arab State System
ERM	62.2013	Julien Chevallier and Benoît Sévi: <u>A Fear Index to Predict Oil Futures Returns</u>
CCSD	63.2013	Dominik Karos: <u>Bargaining and Power</u>
CCSD	64.2013	Carlo Fezzi, Ian J. Bateman, and Silvia Ferrini: Estimating the Value of Travel Time to Recreational Sites
		Using Revealed Preferences
ES	65.2013	Luca Di Corato, Michele Moretto and Sergio Vergalli: Long-run Investment under Uncertain Demand
ES	66.2013	Michele Moretto, Paolo Panteghini and Sergio Vergalli: <u>Lax Competition, Investment Irreversibility and the</u>
CCSD	67 2013	Provision of Public Goods Dennis Guignet and Anna Alberini: Can Preperty Values Capture Changes in Environmental Health Picks?
CCSD	07.2013	Evidence from a Stated Preference Study in Italy and the UK
ES	68.2013	William Brock. Anastasios Xepapadeas and Athanasios Yannacopoulos: Adjustment Costs and Long Run
		Spatial Agglomerations
ES	69.2013	Sasan Bakhtiari, Antonio Minniti and Alireza Naghavi: <u>Multiproduct Multinationals and the Quality of</u>
		Innovation
CCSD	70.2013	Rafael González-Val and Fernando Pueyo: Trade Liberalisation and Global-scale Forest Transition
CCSD	71.2013	Elena Claire Ricci: <u>Smart-Grids and Climate Change. Consumer adoption of smart energy behaviour: a</u>
	70.0040	system dynamics approach to evaluate the mitigation potential
	72.2013	valentina posetti and Marco Manezzon: <u>Laxing Carbon under Market Incompleteness</u>
CC3D	13.2013	Environmental Externality in the Lagoon of Marano and Grado
		<u>environmental externativ in the lagoon of marano and Orado</u>

CCSD	74.2013	Herman R.J. Vollebergh and Edwin van der Werf: <u>The Role of Standards in Eco-innovation: Lessons for</u> Policymakers
FS	75 2013	<u>Cérard Mondello: Ambiguous Beliefs on Damages and Civil Liability Theories</u>
CCSD	76.2013	Roberto Antonietti and Alberto Marzucchi: <u>Green Investment Strategies and Export Performance: A Firm-</u>
		level Investigation
CCSD	77.2013 78.2013	A.K.S. Chand, Sergio Currarini and Giovanni Ursino: <u>Cheap Talk with Correlated Signals</u> Ebru A. Gencer: <u>An Overview of Urban Vulnerability to Natural Disasters and Climate Change in Central</u>
		America & the Caribbean Region
CCSD	79.2013	Libo Wu, Changhe Li, Haoqi Qian and ZhongXiang Zhang: <u>Understanding the Consumption Behaviors on</u> Electric Vehicles in China - A Stated Preference Analysis
ES	80.2013	Andries Richter and Johan Grasman: <u>The Transmission of Sustainable Harvesting Norms When Agents Are</u>
CCSD	81.2013	Jonathan Colmer: Climate Variability, Child Labour and Schooling: Evidence on the Intensive
ERM	82.2013	Anna Alberini, Will Gans and Charles Towe: <u>Free Riding, Upsizing, and Energy Efficiency Incentives in</u>
CCCP	00.0040	Maryland Homes
CCSD	83.2013	Inge van den Bijgaart, Reyer Gerlagh, Luuk Korsten and Matti Liski: <u>A Simple Formula for the Social Cost of</u> <u>Carbon</u>
CCSD	84.2013	Elena Claire Ricci: <u>An Integrated Assessment of Super & Smart Grids</u>
CCSD	85.2013	Laura Diaz Anadon, Gregory Nemet and Elena Verdolini: <u>The Future Costs of Nuclear Power Using Multiple</u> Expert Elicitations: Effects of RD&D and Elicitation Design
CCSD	86.2013	Carlo Carraro, Massimo Tavoni, Thomas Longden and Giacomo Marangoni; The Optimal Energy Mix in
		Power Generation and the Contribution from Natural Gas in Reducing Carbon Emissions to 2030 and Beyond
FS	87.2013	Ho Fai Chan, Bruno S. Frey, Jana Gallus and Benno Torgler: External Influence as an Indicator of Scholarly
20	07.12010	Importance
CCSD	88.2013	Marianna Gilli, Susanna Mancinelli and Massimiliano Mazzanti: Innovation Complementarity and
		Environmental Productivity Effects: Reality or Delusion? Evidence from the EU
CCSD	89.2013	Adrien Vogt-Schilb and Stéphane Hallegatte: Marginal Abatement Cost Curves and the Optimal Timing of
	00 2012	Mitigation Measures
ERIVI	90.2015	their Welfare optimal Deployment
CCSD	01 2013	<u>Uterr Wenare-Optimiar Deproyment</u> Massimiliano Mazzanti and Antonio Musolesi: Nonlinearity, Heterogeneity and Unobserved Effects in the
CCSD	91.2013	CO2-income Relation for Advanced Countries
CCSD	92 2013	ZhongXiang Zhang: Energy and Environmental Issues and Policy in China
CCSD	93 2013	Choronal 2 Inang, Energy and Environmental issues and Foncy in China Giacomo Marangoni and Massimo Tayoni: The Clean Energy R&D Strategy for 2°C
CCSD	94 2013	Carlo Ferzi and Jan Bateman: The Impact of Climate Change on Agriculture: Nonlinear Effects and
CCSD	51.2015	Aggregation Bias in Ricardian Models of Earm Land Values
CCSD	95.2013	Paolo D. Farah and Riccardo Tremolada: A Comparison Between Shale Gas in China and Unconventional
CCDD	50.2010	Fuel Development in the United States: Health Water and Environmental Risks
CCSD	96.2013	Florens Flues, Dirk Rübbelke and Stefan Vögele: Energy Efficiency and Industrial Output: The Case of the
		Iron and Steel Industry
CCSD	97.2013	Gregor Schwerhoff: Leadership and International Climate Cooperation
CCSD	98.2013	Francisco Alvarez and Francisco J. André: <u>Auctioning vs. Grandfathering in Cap-and-Trade Systems with</u>
		Market Power and Incomplete Information
CCSD	99.2013	Mattia Amadio, Jaroslav Mysiak, Silvano Pecora and Alberto Agnett: Looking Forward from the Past:
		Assessing the Potential Flood Hazard and Damage in Polesine Region by Revisiting the 1950 Flood Event
CCSD	100.2013	Carlo Orecchia and Ramiro Parrado: <u>A Quantitative Assessment of the Implications of Including non-CO2</u>
		Emissions in the European ETS
CCSD	101.2013	Yaella Depietri, Lorenzo Guadagno and Margaretha Breil: <u>Urban Watershed Services For Improved</u>
EDM	100 0010	Ecosystem Management and Risk Reduction, Assessment Methods and Policy Instruments: State of the Art
ERM	102.2013	Magali Dauvin: <u>Energy Prices and the Real Exchange Rate of Commodity-Exporting Countries</u>
ERM	103.2013	Chiara Franco and Giovanni Marin: The Effect of Within-Sector, Upstream and Downstream Energy Taxes
CCCD	104 2012	on Innovation and Productivity
CCSD	104.2013	Francesco Bosello and Enrica De Cian: <u>Climate Change, Sea Level Rise, and Coastal Disasters. A Review of</u>
FC	105 2012	Modeling Practices
ES	105.2013	L. Sella, G. Vivaldo, A. Groth and M. Ghil: <u>Economic Cycles and Their Synchronization: A Survey of Spectral</u>
FC	100 0012	<u>Properties</u>
ES	105.2013	veronica Konchi: <u>The Dawn of Italian Industry in Argentina: Pirelli in Buenos Aires (1898-1910)</u>
CCSD	107.2013	Svenja Hector: Accounting for Different Uncertainties: Implications for Climate Investments?
CCSD	108.2013	ivierance meugues: Ine Global Emission Game: On the Impact of Strategic Interactions Between Countries on
	100 2012	the Existence and the Properties of Nash Equilibria
EKIVI	109.2013	i ommaso biondi and iviicnele ivioretto: <u>Solar Grid Parity Dynamics in Italy: A Real Option Approach</u>