

A Service of

ZBW

Leibniz-Informationszentrum Wirtschaft Leibniz Information Centre for Economics

Kimms, Alf; Drexl, Andreas

Working Paper — Digitized Version Multi-level lot sizing: A literature survey

Manuskripte aus den Instituten für Betriebswirtschaftslehre der Universität Kiel, No. 405

Provided in Cooperation with: Christian-Albrechts-University of Kiel, Institute of Business Administration

Suggested Citation: Kimms, Alf; Drexl, Andreas (1996) : Multi-level lot sizing: A literature survey, Manuskripte aus den Instituten für Betriebswirtschaftslehre der Universität Kiel, No. 405, Universität Kiel, Institut für Betriebswirtschaftslehre, Kiel

This Version is available at: https://hdl.handle.net/10419/149036

Standard-Nutzungsbedingungen:

Die Dokumente auf EconStor dürfen zu eigenen wissenschaftlichen Zwecken und zum Privatgebrauch gespeichert und kopiert werden.

Sie dürfen die Dokumente nicht für öffentliche oder kommerzielle Zwecke vervielfältigen, öffentlich ausstellen, öffentlich zugänglich machen, vertreiben oder anderweitig nutzen.

Sofern die Verfasser die Dokumente unter Open-Content-Lizenzen (insbesondere CC-Lizenzen) zur Verfügung gestellt haben sollten, gelten abweichend von diesen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

Terms of use:

Documents in EconStor may be saved and copied for your personal and scholarly purposes.


You are not to copy documents for public or commercial purposes, to exhibit the documents publicly, to make them publicly available on the internet, or to distribute or otherwise use the documents in public.

If the documents have been made available under an Open Content Licence (especially Creative Commons Licences), you may exercise further usage rights as specified in the indicated licence.



WWW.ECONSTOR.EU

Manuskripte aus den Instituten für Betriebswirtschaftslehre der Universität Kiel





No. 405

;

Multi–Level Lot Sizing: A Literature Survey

A. Kimms and A. Drexl

September 1996

Alf Kimms, Andreas Drexl

Lehrstuhl für Produktion und Logistik, Institut für Betriebswirtschaftslehre, Christian-Albrechts-Universität zu Kiel, Olshausenstr. 40, 24118 Kiel, Germany email: Kimms@bwl.uni-kiel.de

Drexl@bwl.uni-kiel.de

URL: http://www.wiso.uni-kiel.de/bwlinstitute/Prod ftp://ftp.wiso.uni-kiel.de/pub/operations-research

Abstract

Lot sizing certainly belongs to the most established production planning problems. First scientific reports of this subject date from the beginning of the 20th century and at least one chapter about lot sizing can be found in almost every good textbook about production research issues. But, as we will show, some topics of practical importance such as multilevel lot sizing where capacity is scarce and demand is time variant have first been successfully attacked in the recent past. Furthermore, lot size and sequence decisions are usually not integrated as it ought to be for the short-term planning. This paper reviews the history of multi-level lot sizing from the very early work to the state-of-the-art.

1 Scope of the Review

The huge amount of literature can be classified into several categories. We discriminate three important criteria.

First, publications may assume stochastic or deterministic data. The focus here is on deterministic cases. We refer to [14, 39, 76, 81, 108, 194] for an introduction into the problems associated with stochastic data.

Second, authors assume a single- or a multi-level production. Approaches of the former type do not fit for multi-level structures by definition. Hence, we do not give a comprehensive overview of single-level lot sizing here. [7, 16, 17, 64, 66, 73, 119, 177] contain reviews. However, modifications of single-level heuristics may be used to attack multi-level problems, e.g. on a level-by-level basis. Such methods are called improved heuristics. Subsequent sections deal with these.

Last, demand may be assumed to be dynamic or stationary. In a stationary situation, the demand occurs continuously and with a constant rate. Usually, an infinite planning horizon comes along with stationary demand. This is appropriate for mass production for instance. In most cases, the common basis is an economic order quantity (EOQ) policy [1, 93] with no capacity considerations, or the economic lot sizing problem (ELSP) [66] where capacity limits are taken into account. There is a vast amount of literature about multi-level lot sizing for stationary demand. Most of it is based on EOQ-like assumptions. But, these approaches are of minor help in the dynamic case. Hence, it is sufficient to cite some work without going into the details: [10, 11, 18, 26, 37, 38, 43, 46, 55, 56, 68, 69, 71, 70, 75, 78, 82, 83, 87, 90, 91, 100, 102, 101, 103, 104, 105, 109, 131, 136, 133, 137, 138, 139, 140, 153, 154, 158, 159, 160, 161, 170, 171, 172, 175, 173, 174, 176, 192, 193].

In the subsequent sections we should have a closer look at the multi-level lot sizing literature where data are deterministic and demand is dynamic. Though our interest lies in capacitated situations primarily, uncapacitated cases are closely related and shall therefore be reviewed, too.

2 Contributions of General Interest

This is of course not the first review of (multi-level) lot sizing. So, let us start with a look at the history of surveys. A very brief survey was given by Jacobs and Khumawala [106] with seven references only. Research issues for multi-level lot sizing are discussed by Collier in [53]. DeBoth et al. [61] review dynamic lot sizing. The review of Bahl et al. [16] probably is the one that is most often referenced. Fleischmann [73] gives insight how operations research methods were applied to different production planning problems. So he does for lot sizing. Gupta and Keung [85] also provide a review. Goyal and Gunasekaran [79] provide a collection of literature about multi-level production/inventory systems. Recently, Kuik et al. [119] report on different assumptions for lot sizing, among them multi-level lot sizing, too, and conclude: "Clearly, work in this area has only begun." In the textbooks written by Domschke et al. [64] and Tempelmeier [177] we also find notable subsections explaining multi-level lot sizing research.

The most basic problem in material requirements planning (MRP) introduced by multi-level structures is the parts requirement (or explosion) problem which is that of computing the total number of parts needed to fulfill demand. In this context, the low level code (or explosion level) of an item is defined as the number of arcs on the longest path from that particular item to an end item. Especially in the presence of positive component inventory levels, the determination of the so-called net requirement has attracted early researchers. Vazsonyi [183] gives a mathematical statement. Elmaghraby [65] is among the first who present an algorithm. Thompson [181] follows up and coins the notion of a technological order which is a partial order on the basis of the low level codes of the items. Both of them use matrix operations to compute net requirements. Nowadays, this problem does no longer exist since efficient methods using the low level codes of the items are available.

The bill of material (BOM) is a formal statement of the successor-predecessor relationship of items and thus defines the gozinto-structure. Special cases of acyclic structures are those where each item has at most one successor (socalled assembly structures), and those where each item has at most one predecessor (so-called divergent, distribution, or arborescence structures, respectively). Structures which belong to the assembly as well as to the distribution type are called serial (or linear). A gozinto-structure that is neither assembly nor divergent is general. Collier [51, 52] is the only who tries to define a measure of complexity for gozinto-structures by making use of the information in the BOM. He introduces the degree of commonality index which reflects the average of the number of successors per component part.

3 Dynamic Demand, Unlimited Capacity

Clark and Scarf [44] provide an early analysis of optimal lot sizing policies in a distribution network. They also invent the notion echelon stock for what is in inventory plus what is in transit but not sold. Veinott [184] formulates lot sizing as minimizing a concave function over the solution set of a Leontief substitution system. His work is a generalization of Zangwill's paper [198]. For serial gozinto-structures Zangwill [199] presents a dynamic programming approach based on a reinterpretation of the constraints as flow constraints in a single-source network. Love [126] uses these results and considers serial structures under certain assumptions about the costs related to different production levels. He presents a dynamic programming algorithm, too, to find so-called nested extreme optimal schedules where the attribute nested means that production for an item in a certain period implies production for all successor items in the same period. Crowston and Wagner [54] extend Love's model and develop dynamic programming and B&B-methods for assembly systems. On the basis of Veinott's and Zangwill's results, Kalymon [112] decomposes problems with divergent gozinto-structures into a series of single-item problems. He uses an enumeration procedure to determine the sequence in which these single-item problems are then solved.

Steinberg and Napier [166] determine optimal solutions for general gozintostructures with standard MIP-solvers on the basis of a network model. The production quantities may be constrained by an item-specific upper bound. An alternative formulation with a less cumbersome notation is given by McClain et al. [132]. In response, Steinberg and Napier [167] make clear that the alternative formulation is more compact, but that there is no evidence which proves greater computational efficiency.

Rao [147] uses Bender's decomposition to compute optimal solutions for problems with general gozinto-structures.

Krajewski et al. [116] perform a computational study and by using its outcome they determine the parameters of three regression models with least squares estimators. For instance, they specify the average size of unreleased orders for each item as a function of the number of product levels above the item, the total number of components for the item, the number of immediate components, and the general lot size for the system (which is a binary variable indicating small or large lots).

Bitran et al. [30] suggest a planning approach where the gozinto-structure is aggregated into just two levels. Then, the two-level problem is solved and the solution is eventually disaggregated. However, they do not consider setups which makes both, the two-level planning problem as well as the disaggregation, become linear with continuous decision variables only.

Bahl and Ritzman [15] formulate a non-linear mixed-integer program for simultaneous master production scheduling, lot sizing, and capacity requirements planning. They also develop a heuristic. The traditional level-by-level approach is retained. Furthermore, they assume a lot-for-lot policy for all component parts. In fact, they reduce the multi-level problem to a single-level one under these assumptions.

By means of simulation studies Biggs [22] examines the interaction effect of different lot sizing and sequencing rules when used conjunctively. In a first step, he solves a multi-level lot sizing problem using a single-level lot sizing rule on a level-by-level basis. Note that the same rule is applied to all levels. For each period he computes a sequence of different items with a simple priority rule, afterwards. The test-bed consists of six lot sizing rules combined with five sequencing rules. The performance is analyzed using several criteria, among them the total number of setups for instance. As an outcome of this study, it turns out that interaction effects between lot size and sequence decisions do exist, but, "... a total explanation will have to wait for future research...".

Billington et al. [28] discuss how to reduce the size of problem instances by means of gozinto-structure compression. A similar idea is published by Axsäter and Nuttle [12, 13] where assembly structures are taken into account only. Zangwill [200] analyzes problems with serial gozinto-structures to find out at which levels inventory cannot occur. Though his motivation is to give advice where to invest for setup cost reduction in order to enable just-in-time production and to achieve zero inventories irrespective of demand, the information obtained can also be used to compress the gozinto-structure.

When testing six single-level heuristics on a level-by-level basis using the same lot sizing rule on each level, Benton and Srivastava [19] find out that neither the depth nor the breadth of a gozinto-structure has a significant effect on the performance of lot sizing. Afentakis [3] conducts a computational study which contradicts this result. The reason might be that Benton and Srivastava use gozinto-structures with up to five levels and six items while Afentakis uses structures with up to 45 levels and 200 items. Sum et al. [169] provide a study which confirms Afentakis. They employ 11 lot sizing rules on a level-by-level basis tested on 1980 instances. By the way, a heuristic that is introduced by Bookbinder and Koch [35] performs best. An analysis of variance reveals the impact of the number of items, the number of levels, and the average number of immediate successors per item [51]. It is interesting to note that the ranking of the rules remains stable.

Simplistic applications of single-level lot sizing rules are also described by Berry [20] and Biggs et al. [21, 24, 25]. Another evaluation of the level-by-level technique is done by Veral and LaForge [185]. Choi et al. [42], Collier [49, 50], Ho [99], LaForge [120, 121], and Lambrecht et al. [123] provide computational studies, too.

A study in which single-level lot sizing rules are applied to a multi-level structure in a level-by-level manner is done by Yelle [195]. He uses four different simple lot sizing rules and a two-level test-bed. His basic idea is to apply different rules to different levels. This study is extended by Jacobs and Khumawala [107] who add three more single-level methods plus a multi-level

algorithm proposed by McLaren [135] which in turn bases on the single-level Wagner-Whitin procedure [6, 72, 189, 190]. Tests with a three-level test-bed are done by Choi et al. [41].

Blackburn and Millen [31] apply single-level heuristics level-by-level to assembly structures using the same rule for all levels. Three heuristics are tested this way. Following the ideas of New [141] and McLaren [135], they modify the cost parameters of the items in order to take the multi-level structure indirectly into account. Five types of modifications are tested. Closely related to their lot sizing approach is the one of Rehmani and Steinberg [149] who keep the cost parameters, but, modify the computation of some derived values that guide a single-level heuristic.

Gupta et al. [84] compare the cost modification approach with others. Studies of Wemmerlöv [191] also examine the impact of cost modifications.

Raturi and Hill [148] introduce something similar to capacity constraints into the model of Blackburn and Millen. But, capacity usage is only estimated on the basis of average demand. They heuristically compute shadow prices for the capacities and derive modified setup costs from that. Eventually, the lot sizing problem is solved using the Wagner-Whitin procedure level by level.

An extension of Blackburn and Millen's approach for general gozinto-structures is presented by Dagli and Meral [57]. The combination of lot sizing and capacity planning is treated in [33] where the subject is confined to assembly structures. The impact of a rolling horizon is discussed in [32].

Combining the idea of using different single-level heuristics at different levels with the idea of modifying the cost parameters is evaluated by Blackburn and Millen [34]. Seven algorithms are used in six combinations. In all tests they choose one algorithm for the end item level and another algorithm for the remaining levels.

While the above level-by-level algorithms construct a solution in one pass, Graves [80] presents a multi-pass procedure. Assuming that external demand occurs for end items only, the basic idea is to perform a single pass, and then to modify the cost parameters (how this is done is of no relevance here). Afterwards, he solves the single-item problems for those items again for which external demand exists. If nothing changes for these items the procedure terminates. If there are any changes in the production plan then the whole procedure repeats using the modified cost parameters this time. A proof of convergence is given.

Another multi-pass heuristic is invented by Peng [143] who uses the Wagner-Whitin procedure to generate an initial solution. This solution is then repeatedly reviewed to combine lots until no further cost savings can be achieved.

Moving away from level-by-level lot sizing, Lambrecht et al. [124] compare level-by-level approaches with a period-by-period approach. The latter one computes production quantities for the first period and for all items before the second period is concerned. This is going on period by period. All computational tests are restricted to assembly structures. As a result, the period-by-period approach seems to be competitive. A somehow similar method proposes Afentakis [3]. Starting with solving the lot sizing problem consisting of the first period only, he generates a solution which includes the next period by augmenting the intermediate result. This is done until all periods are covered. While Afentakis uses the term sequential approach instead of level-by-level, he now calls his method a parallel one instead of period-by-period. The proposed method decidedly outperforms all (five) single-level methods that are used level-by-level in his study.

Rosling [152] gives an uncapacitated plant location reformulation of the problem with assembly structures. On the basis of this new MIP-model, he develops an optimal procedure.

Heinrich [96, 95] presents a heuristic for general gozinto-structures which operates in two phases. First, the dynamic multi-level lot sizing problem is reduced into a problem with constant demand (using the average demand for each item for instance). Using modified cost parameters, the resulting problem is then solved with a deterministic search in the set of feasible reorder points. In the second phase, the resulting production amounts are modified to meet the demand of the original problem instance.

Coleman and McKnew [48] keep the idea of level-by-level methods alive and design a new heuristic based on an earlier work [47]. Although their computational study gives promising results, they fail to compete with sophisticated, established methods (e.g. [80]). A study by Simpson and Erenguc [163] indicates that, if this is done, the new heuristic appears rather poor.

Gupta and Brennan [84] evaluate level-by-level approaches if backorders are allowed. Other improved heuristics for models with backlogging are discussed by Vörös and Chand [187].

Afentakis et al. [5] efficiently compute optimal solutions for assembly structures. The proposed method is of the B&B-type. Based on a MIP-reformulation, lower bounds are determined with a Lagrangean relaxation of those constraints which represent the multi-level structure. As a result, a set of single-item, uncapacitated lot sizing problems is to be solved. This is done with a shortest path algorithm. Optimal solutions for general gozinto-structures are determined by Afentakis and Gavish in [4] by transforming complex structures into assembly structures where some items occur more than once. Chiu and Lin [40] also compute optimal solutions for assembly structures with dynamic programming. Their idea is based on a graphical interpretation of Afentakis' reformulation. A level-by-level heuristic with postprocessing operations is described as well.

Kuik and Salomon [117] apply a stochastic local search method, namely simulated annealing, to multi-level lot sizing. This approach can handle general gozinto-structures. A comparison with other approaches is not done.

Salomon [156] suggests a decomposition of the multi-level problem into several single-item problems. Roughly speaking, this is achieved by eliminating inventory variables by substitution, doing a Lagrangean-like relaxation of inventory balances, and adding some new constraints. He then solves the singleitem problems with some lot sizing algorithm sequentially, and upon termination updates the Lagrangean multipliers to repeat the process.

Joneja [110] considers assembly gozinto-structures. By adapting results from lot sizing with stationary demand [153], he develops a so-called cluster algorithm and proves worst case performance bounds. The projection of this work to serial structures closely relates to Zangwill's paper [200]. Roundy [155] presents two cluster algorithms for general structures and worst case bounds for these. In a computational study, one of them turns out to be slightly better than Afentakis' method [3].

McKnew et al. [134] present a linear zero-one-model for multi-level lot sizing. Assembly gozinto-structures are assumed. They claim that the LPrelaxation of the model always yields integer solutions. Rajagopalan [145] arguments that they are wrong. But, his counter-example is false.¹

Pochet and Wolsey [144] consider general gozinto-structures and derive cutting planes to ease the computational effort when standard solvers are running.

Atkins [9] suggests a way to compute lower bounds for problems with assembly structures. His basic idea is to convert an assembly structure into a set of serial structures by finding all paths from the lowest level to end items. Some items may now appear in more than one serial structure having their own identity. In such a case the original setup costs are split up and assigned to the (new) items. Eventually, the approach in [126] can be used to solve the resulting instances which, in summary, gives a lower bound.

Simpson and Erengue [163] invent a neighborhood search procedure and slightly outperform [80], [48], and three other improved heuristics. Lower bounds are obtained with a Lagrangean relaxation.

Richter and Vörös [150] are trying to find a so-called setup cost stability region which is defined as the set of all setup cost values for which a given solution remains optimal. Recently, Vörös [188] analyzes the sensitivity of the setup cost parameters for facilities in series and computes stability regions with a dynamic programming procedure.

Arkin et al. [8] give a classification of the complexity of uncapacitated, multilevel lot sizing problems. Optimization problems with general gozinto-structures and no setup times are proven to be NP-hard.

4 Dynamic Demand, Scarce Capacity

Lambrecht and Vander Eecken [122] consider a serial structure and formulate an LP-model on the basis of a network representation. Setups are not part of their focus which is the reason for having continuous variables only (such approaches are used for master production scheduling). Furthermore, capacity constraints exclusively restrict the production amounts of the end item. Optimal solutions are computed by means of extreme flow considerations. A similar problem is

¹See [145], page 1025: The determinant of the submatrix in the example evaluates to 1 and not to 2 as stated in the paper. Hence, there is no contradiction to total unimodularity.

concerned by Gabbay [74] who has several serial structures being processed in parallel in mind. In contrast to Lambrecht and Vander Eecken he assumes capacity limits on all levels. Zahorik et al. [197] generalize Gabbay's work, but still assume serial structures. Assembly structures are investigated by Afentakis [2] who transforms the problem into a job shop scheduling problem.

A first MIP-model is formulated by Haehling von Lanzenauer [88]. Remarkably to note that he considers lot sizing and scheduling simultaneously. Another early multi-level lot sizing model is that of Elmaghraby and Ginsberg [67]. An LP-model for master production scheduling in a multi-level system is given in [89].

Gorenstein [77] provides a case description for planning tire production with three levels. He formulates a MIP-model, but does not present any methods. In a short note he points out that LP-based rounding methods could work fine. Vickery and Markland [186] report about experiences in using MIP-model formulations being solved with standard solvers in a real-world situation. Their field of application is a pharmaceutical company.

Zäpfel and Attmann [196] present some kind of a tutorial for multi-level lot sizing. They assume several serial gozinto-structures being processed in parallel. A MIP-model is given on the basis of which a fixed charge problem reformulation and examples are discussed.

Ramsey and Rardin [146] consider serial structures and propose several heuristics. The basic assumption in this work is that items do not share common resources. Two of the heuristics are LP-based methods where a particular choice of the arc weights in a network flow representation makes the solution of the LP-network-problem become a feasible solution. One out of the two LP-based procedures uses the optimal solution of the uncapacitated problem [199] to set the arc weights. Two other heuristics are ad hoc approaches. One makes the multi-level problem collapse into a single-level problem by making additional assumptions. The other one is a greedy heuristic. A computational study shows that the greedy heuristic gives the best results, although the idea of collapsing the gozinto-structure leads to much shorter execution times. Both LP-based approaches are worse with respect to the run-time as well as with respect to the deviation from a lower bound.

Biggs [23] informally discusses the problem of scheduling component parts in order to meet the demand for the end items. In a computational study he uses, among others, the total number of setups to evaluate several rules. As a result, he states that "...the use of the various rules did cause the system to respond differently...".

Harl and Ritzman [92] use modifications of uncapacitated, single-level heuristics to develop a capacity-sensitive multi-level procedure.

Billington et al. [27, 29] assume a general gozinto-structure. Some (potentially all) items share a single common resource with scarce capacity. Beside a MIP-formulation they also present a heuristic to solve the problem. The basic working principle of the heuristic is a B&B-strategy. The B&B-method enumerates over the setup variables. At each node lower bounds are computed by relaxing capacity and multi-level constraints. The uncapacitated, single-level subproblem is then heuristically solved being embedded into a Lagrangean-like iteration.

Hechtfischer [94] heuristically solves problems with an assembly structure. Similar to Billington et al. he assumes that (some) items share a single common resource. But additionally, all items which require the resource must have the same low level code. Basically, his approach follows traditional MRP II ideas and operates level-by-level. If production amounts exceed the available capacity, some items are shifted into earlier periods. Guided with a Lagrangean-like penalty expression, the whole procedure iterates until a maximum number of iterations is performed.

Salomon [156] introduces a simulated annealing and a tabu search heuristic for the problem earlier defined by Billington et al. [29]. Furthermore, he discusses LP-based heuristics for assembly structures. Among traditional rounding approaches, he also presents combinations of simulated annealing and tabu search, respectively, with LP-based rounding. Reprints of parts of this outlet are [118] and [157].

Roll and Karni [151] attack the multi-level lot sizing problem with a single resource as well. In contrast to Billington et al. they do not consider setup times. Starting with a first feasible solution, they pass multiple phases making changes to intermediate solutions to gain improvements.

Toklu and Wilson [182] assume assembly gozinto-structures. Furthermore, only end items require a single commonly used scarce resource. They develop a heuristic for this type of problem.

Maes et al. [127, 128, 129] suggest LP-based rounding heuristics for assembly type problems based on the solution of the LP-relaxation of a reformulation as a plant location model [152]. Their ideas cover simple single-pass heuristics fixing binary variables to 1, or fixing them to 1 or to 0, respectively, meanwhile solving a new LP-relaxation in-between. Another suggestion is that of curtailed B&B-procedures.

Mathes [130] extends the MIP-model given by Afentakis et al. [5] and introduces capacity constraints whereby items do not share common resources (socalled dedicated machines). Several valid constraints are derived to improve the run-time performance of standard solvers.

Stadtler [164, 165] compares the impact of different MIP-model formulations on the performance of standard solvers. His assumptions are quite unrestrictive: general gozinto-structures, multiple resources which are shared in common, and positive setup times. Due to his assumption that an unlimited amount of overtime per period is allowed, there exists no feasibility problem which would make the development of heuristics really hard.

Helber [97, 98] develops heuristics for the multi-level lot sizing problem. He assumes general gozinto-structures. Items may share common resources, but no item requires more than one resource. Positive setup times are allowed. Among the proposed procedures are simulated annealing, tabu search, and genetic algorithms which guide a search in the space of setup patterns on the basis of which production plans are derived. Tempelmeier and Helber [180] test a modification of the Dixon-Silver heuristic [63]. Derstroff and Tempelmeier [62, 178, 179] use a Lagrangean relaxation of capacity constraints and inventory balances to provide a lower bound. Within each iteration an upper bound can be computed by solving an uncapacitated, multi-level problem on a level-by-level basis using the objective function including the penalty expressions for evaluation. A postprocessing stage is used to smooth capacity violations.

Clark and Armentano [45] present a heuristic for general gozinto-structures which operates in two phases. First, the Wagner-Whitin procedure is used to solve the uncapacitated problem on a level-by-level basis. Second, production in overloaded periods is shifted into earlier periods to respect the capacity constraints. Interesting to note is that items may require more than just one resource.

Following the successive planning idea, Sum and Hill [168] perform lot sizing and scheduling. They discriminate orders and operations where each order is fulfilled by doing a plenty of operations. They have both, a network (i.e. gozinto-structure in our terminology) of orders and for each order a subnetwork of operations. Operations are scheduled with a modified version of a resource constrained project scheduling algorithm [60, 142]. After this is done, they merge and/or break some orders which results in a new network and the whole process repeats until the recent solution is not improved. The key element of lot sizing is the merging and breaking part in this approach. The decision what to merge or to break, respectively, relies on a simple priority rule.

Dauzère-Péres and Lasserre [58, 59, 125] take an integrated approach in lot sizing and scheduling into account. In a first step they make lot sizing decision regarding capacity constraints. Then, they determine a sequence given fixed lot sizes. Afterwards, a new lot sizing problem is solved with new precedence constraints among items which share the same resource. These precedence relations stem from the sequence decisions just made. The whole procedure is repeated until a stopping criterion is met. For solving the lot sizing and the scheduling subproblems, respectively, they employ methods from the literature.

Haase [86] gives a MIP-model for multi-level lot sizing and scheduling with a single bottleneck facility. Solution methods are, however, not provided.

Brüggemann and Jahnke [36] employ simulated annealing to find suboptimal solutions for lot sizing and scheduling problems with batch production. However, their heuristic works only for two-level gozinto-structures. The underlying idea is to proceed level by level again.

Jordan [111] considers batching and scheduling. Due to restrictive assumptions, he is able to compute optimum results for small instances.

Kimms [115] tackles the problem of multi-level lot sizing and scheduling under quite general assumptions. The gozinto-structures may be of the general type and several scarce resources may impose capacity restrictions (singlemachine cases are discussed in [113, 114]). Several heuristics are developed, among them regret based random sampling, a cellular automaton, a genetic algorithm, disjunctive arc based tabu search, and a so-called demand shuffle procedure which, by the way, performs best. The basic idea of demand shuffle is to combine random sampling with a problem specific data structure manipulation. Roughly speaking, this data structure contains the information until when certain (external or internal) demand is to be met. Manipulating this data structure basically equals modifying the deadline of some demand artificially.

5 Intermediate Results

Under unconstrained capacities most authors favorite level-by-level approaches which are easy to implement and which can make use of many single-level heuristics as well as efficient exact methods. However, recent research indicates that other ideas are superior [155, 163]. Due to its complexity [8], optimal solution procedures are unlikely to be able to solve medium- to large-sized problem instances. Hence, heuristics will dominate for practical purposes. Definitely, this holds for problems under capacity constraints.

Reviewing the work on capacitated, multi-level lot sizing reveals that most researchers consider very restrictive cases. Most of them assume a single resource only. Also, a lot of work does not deal with general gozinto-structures. Exceptions can be found in very recent outlets only [62, 97, 98, 178, 179, 180].

Although the importance of considering multi-level lot sizing and scheduling simultaneously was recognized rather early [88], research in this field has just begun. A first step away from pure successive MRP II concepts towards taking interaction effects of lot sizing and scheduling into account is done with iterative procedures [58, 59, 125, 168]. Models and methods which solve the combined problems in one step are presented in [115].

Acknowledgement

This work was done with partial support from the DFG-project Dr 170/4-1.

References

- [1] ANDLER, K., (1929), Rationalisierung der Fabrikation und optimale Losgrösse, München, Oldenbourg
- [2] AFENTAKIS, P., (1985), Simultaneous Lot Sizing and Sequencing for Multistage Production Systems, IIE Transactions, Vol. 17, pp. 327-331
- [3] AFENTAKIS, P., (1987), A Parallel Heuristic Algorithm for Lot-Sizing in Multi-Stage Production Systems, IIE Transactions, Vol. 19, pp. 34-42

- [4] AFENTAKIS, P., GAVISH, B., (1986), Optimal Lot-Sizing Algorithms for Complex Product Structures, Operations Research, Vol. 34, pp. 237-249
- [5] AFENTAKIS, P., GAVISH, B., KARMARKAR, U., (1984), Computationally Efficient Optimal Solutions to the Lot-Sizing Problem in Multistage Assembly Systems, Management Science, Vol. 30, pp. 222-239
- [6] AGGARWAL, A., PARK, J.K., (1993), Improved Algorithms for Economic Lot-Size Problems, Operations Research, Vol. 41, pp. 549-571
- [7] AKSOY, Y., ERENGUC, S.S., (1988), Multi-Item Inventory Models with Coordinated Replenishments: A Survey, International Journal of Production Research, Vol. 22, pp. 923-935
- [8] ARKIN, E., JONEJA, D., ROUNDY, R., (1989), Computational Complexity of Uncapacitated Multi-Echelon Production Planning Problems, Operations Research Letters, Vol. 8, pp. 61-66
- [9] ATKINS, D.R., (1994), A Simple Lower Bound to the Dynamic Assembly Problem, European Journal of Operational Research, Vol. 75, pp. 462-466
- [10] ATKINS, D.R., QUEYRANNE, M., SUN, D., (1992), Lot Sizing Policies for Finite Production Rate Assembly Systems, Operations Research, Vol. 40, pp. 126-141
- [11] ATKINS, D. R., SUN, D., (1995), 98%-Effective Lot Sizing for Series Inventory Systems with Backlogging, Operations Research, Vol. 43, pp. 335-345
- [12] AXSÄTER, S., NUTTLE, H.L.W., (1986), Aggregating Items in Multi-Level Lot Sizing, in: Axsäter, S., Schneeweiss, C, Silver, E., (eds.), Multi-Stage Production Planning and Inventory Control, Lecture Notes in Economics and Mathematical Systems, Vol. 266, Springer, Berlin, pp. 109-118
- [13] AXSÄTER, S., NUTTLE, H.L.W., (1987), Combining Items for Lot Sizing in Multi-Level Assembly Systems, International Journal of Production Research, Vol. 25, pp. 795-807
- [14] AXSÄTER, S., ROSLING, K., (1994), Multi-Level Production-Inventory Control: Material Requirements Planning or Reorder Point Policies?, European Journal of Operational Research, Vol. 75, pp. 405-412
- [15] BAHL, H.C., RITZMAN, L.P., (1984), An Integrated Model for Master Scheduling, Lot Sizing and Capacity Requirements Planning, Journal of the Operational Research Society, Vol. 35, pp. 389-399
- [16] BAHL, H.C., RITZMAN, L.P., GUPTA, J.N.D., (1987), Determining Lot Sizes and Resource Requirements: A Review, Operations Research, Vol. 35, pp. 329-345

- [17] BAKER, K.R., (1990), Lot-Sizing Procedures and a Standard Data Set: A Reconsiliation of the Literature, Journal of Manufacturing and Operations Management, Vol. 2, pp. 199-221
- [18] VAN BEEK, P., BREMER, A., VAN PUTTEN, C., (1985), Design and Optimization of Multi-Echelon Assembly Networks: Savings and Potentialities, European Journal of Operational Research, Vol. 19, pp. 57-67
- [19] BENTON, W.C., SRIVASTAVA, R., (1985), Product Structure Complexity and Multilevel Lot Sizing Using Alternative Costing Policies, Decision Sciences, Vol. 16, pp. 357–369
- [20] BERRY, W.L., (1972), Lot Sizing Procedures for Material Requirements Planning Systems: A Framework for Analysis, Production and Inventory Management Journal, Vol. 13, No. 2, pp. 19-35
- [21] BIGGS, J.R., (1975), An Analysis of Heuristic Lot Sizing and Sequencing Rules on the Performance of a Hierarchical Multi-Product, Multi-Stage Production Inventory System Utilizing Material Requirements Planning, Ph.D. dissertation, Ohio State University
- [22] BIGGS, J.R., (1979), Heuristic Lot-Sizing and Sequencing Rules in a Multistage Production-Inventory System, Decision Sciences, Vol. 10, pp. 96-115
- [23] BIGGS, J.R., (1985), Priority Rules for Shop Floor Control in a Material Requirements Planning System under Various Levels of Capacity, International Journal of Production Research, Vol. 23, pp. 33-46
- [24] BIGGS, J.R., GOODMAN, S.H., HARDY, S.T., (1977), Lot Sizing Rules in a Hierarchical Multi-Stage Inventory System, Production and Inventory Management Journal, Vol. 18, No. 1, pp. 104-115
- [25] BIGGS, J.R., HAHN, C.K., PINTO, P.A., (1980), Performance of Lot-Sizing Rules in an MRP System with Different Operating Conditions, Academy of Management Review, Vol. 5, pp. 89-96
- [26] BIGHAM, P.E., MOGG, J.M., (1979), Converging-Branch, Multi-Stage Production Schedules with Finite Production Rates and Startup Delays, Journal of the Operational Research Society, Vol. 30, pp. 737-745
- [27] BILLINGTON, P.J., (1983), Multi-Level Lot-Sizing with a Bottleneck Work Center, Ph.D. dissertation, Cornell University
- [28] BILLINGTON, P.J., MCCLAIN, J.O., THOMAS, L.J., (1983), Mathematical Programming Approaches to Capacity-Constrained MRP Systems: Review, Formulation and Problem Reduction, Management Science, Vol. 29, pp. 1126-1141

- [29] BILLINGTON, P.J., MCCLAIN, J.O., THOMAS, L.J., (1986), Heuristics for Multilevel Lot-Sizing with a Bottleneck, Management Science, Vol. 32, pp. 989-1006
- [30] BITRAN, G.R., HAAS, E.A., HAX, A.C., (1983), Hierarchical Production Planning: A Two-Stage System, Operations Research, Vol. 30, pp. 232-251
- [31] BLACKBURN, J.D., MILLEN, R.A., (1982), Improved Heuristics for Multi-Stage Requirements Planning Systems, Management Science, Vol. 28, pp. 44-56
- [32] BLACKBURN, J.D., MILLEN, R.A., (1982), The Impact of a Rolling Schedule in Multi-Level MRP Systems, Journal of Operations Management, Vol. 2, pp. 125-135
- [33] BLACKBURN, J.D., MILLEN, R.A., (1984), Simultaneous Lot-Sizing and Capacity Planning in Multi-Stage Assembly Processes, European Journal of Operational Research, Vol. 16, pp. 84–93
- [34] BLACKBURN, J.D., MILLEN, R.A., (1985), An Evaluation of Heuristic Performance in Multi-Stage Lot-Sizing Systems, International Journal of Production Research, Vol. 23, pp. 857-866
- [35] BOOKBINDER, J.H., KOCH, L.A., (1990), Production Planning for Mixed Assembly / Arborescent Systems, Journal of Operations Management, Vol. 9, pp. 7-23
- [36] BRÜGGEMANN, W., JAHNKE, H., (1994), DLSP for 2-Stage Multi-Item Batch Production, International Journal of Production Research, Vol. 32, pp. 755-768
- [37] CHAKRAVARTY, A.K., (1984), Multi-Stage Production/Inventory Deterministic Lot Size Computations, International Journal of Production Research, Vol. 22, pp. 405-420
- [38] CHAKRAVARTY, A.K., SHTUB, A., (1985), An Experimental Study of the Efficiency of Integer Multiple Lot Sizes in Multi-Echelon Production Inventory Systems, International Journal of Production Research, Vol. 23, pp. 469-478
- [39] CHEN, F., ZHENG, Y.S., (1994), Lower Bounds for Multi-Echelon Stochastic Inventory Systems, Management Science, Vol. 40, pp. 1426-1443
- [40] CHIU, H.N., LIN, T.M., (1989), An Optimal Model and a Heuristic Technique for Multi-Stage Lot-Sizing Problems: Algorithms and Performance Tests, Engineering Costs and Production Economics, Vol. 16, pp. 151-160

- [41] CHOI, H.G., MALSTROM, E.M., CLASSEN, R. J., (1984), Computer Simulation of Lot-Sizing Algorithms in Three-Stage Multi-Echelon Inventory Systems, Journal of Operations Management, Vol. 4, No. 4, pp. 259-278
- [42] CHOI, H.G., MALSTROM, E.M., TSAI, R.D., (1988), Evaluating Lot-Sizing Methods in Multilevel Inventory Systems by Simulation, Production and Inventory Management Journal, Vol. 29, pp. 4-10
- [43] CLARK, A.J., (1972), An Informal Survey of Multi-Echelon Inventory Theory, Naval Research Logistics, Vol. 19, pp. 621-650
- [44] CLARK, A.J., SCARF, H., (1960), Optimal Policies for a Multi-Echelon Inventory Problem, Management Science, Vol. 6, pp. 475–490
- [45] CLARK, A.R., ARMENTANO, V.A., (1995), A Heuristic for a Resource-Capacitated Multi-Stage Lot Sizing Problem with Lead Times, Journal of the Operational Research Society, Vol. 46, pp. 1208-1222
- [46] COLE, F., VANDERVEKEN, H., (1982), Deterministic Lot-Sizing Procedures for Multi-Stage Assembly Systems, Engineering Cost and Production Economics, Vol. 7, pp. 37-44
- [47] COLEMAN, B.J., MCKNEW, M.A., (1990), A Technique for Order Placement and Sizing, Journal of Purchasing and Materials Management, Vol. 26, pp. 32-40
- [48] COLEMAN, B.J., MCKNEW, M.A., (1991), An Improved Heuristic for Multilevel Lot Sizing in Material Requirements Planning, Decision Sciences, Vol. 22, pp. 136–156
- [49] COLLIER, D.A., (1980), The Interaction of Single-Stage Lot Size Models in a Material Requirements Planning System, Production and Inventory Management, Vol. 4, pp. 11-20
- [50] COLLIER, D.A., (1980), A Comparison of MRP Lot-Sizing Methods Considering Capacity Change Costs, Journal of Operations Management, Vol. 1, pp. 23-29
- [51] COLLIER, D.A., (1981), The Measurement and Operating Benefits of Component Part Commonality, Decision Sciences, Vol. 12, pp. 85-96
- [52] COLLIER, D.A., (1982), Aggregate Safety Stock Levels and Component Part Commonality, Management Science, Vol. 28, pp. 1296-1303
- [53] COLLIER, D.A., (1982), Research Issues for Multi-Level Lot Sizing MRP Systems, Journal of Operations Management, Vol. 2, pp. 113-123

- [54] CROWSTON, W.B., WAGNER, M.H., (1973), Dynamic Lot Size Models for Multi-Stage Assembly Systems, Management Science, Vol. 20, pp. 14– 21
- [55] CROWSTON, W.B., WAGNER, M.H., HENSHAW, A., (1972), A Comparison of Exact and Heuristic Routines for Lot-Size Determination in Multi-Stage Assembly Systems, AIIE Transactions, Vol. 4, pp. 313-317
- [56] CROWSTON, W.B., WAGNER, M., WILLIAMS, J.F., (1973), Economic Lot Size Determination in Multi-Stage Assembly Systems, Management Science, Vol. 19, pp. 517-527
- [57] DAGLI, C.H., MERAL, F.S., (1985), Multi-Level Lot-Sizing Heuristics, in: Bullinger, H.J., Warnecke, H.J., (eds.), Towards the Factory of the Future, Berlin, Springer
- [58] DAUZÈRE-PÉRES, S., LASSERRE, J.B., (1994), Integration of Lotsizing and Scheduling Decisions in a Job-Shop, European Journal of Operational Research, Vol. 75, pp. 413-426
- [59] DAUZÈRE-PÉRES, S., LASSERRE, J.B., (1994), An Integrated Approach in Production Planning and Scheduling, Lecture Notes in Economics and Mathematical Systems, Berlin, Springer, Vol. 411
- [60] DAVIS, E.W., PATTERSON, J.H., (1975), A Comparison of Heuristic and Optimum Solutions in Resource-Constrained Project Scheduling, Management Science, Vol. 21, pp. 944-955
- [61] DEBOTH, M.A., GELDERS, L.F., VAN WASSENHOVE, L.N., (1984), Lot Sizing Under Dynamic Demand Conditions: A Review, Engineering Costs and Production Economics, Vol. 8, pp. 165–187
- [62] DERSTROFF, M., (1995), Mehrstufige Losgrössenplanung mit Kapazitätsbeschränkungen, Heidelberg, Physica
- [63] DIXON, P.S., SILVER, E.A., (1981), A Heuristic Solution Procedure for the Multi-Item, Single-Level, Limited Capacity Lot-Sizing Problem, Journal of Operations Management, Vol. 2, pp. 23-39
- [64] DOMSCHKE, W., SCHOLL, A., VOSS, S., (1993), Produktionsplanung Ablauforganisatorische Aspekte, Berlin, Springer
- [65] ELMAGHRABY, S.E., (1963), A Note on the 'Explosion' and 'Netting' Problems in the Planning of Materials Requirements, Operations Research, Vol. 11, pp. 530-535
- [66] ELMAGHRABY, S.E., (1978), The Economic Lot Scheduling Problem (ELSP): Review and Extensions, Management Science, Vol. 24, pp. 587– 598

- [67] ELMAGHRABY, S.E., GINSBERG, A.S., (1964), A Dynamic Model for Optimal Loading of Linear Multi-Operation Shops, Management Technology, Vol. 4, pp. 47-58
- [68] EL-NAJDAWI, M.K., (1989), Common Cycle Scheduling Approach to Lot-Size Scheduling for Multi-Stage, Multi-Product Production Processes, Ph.D. dissertation, University of Pennsylvania
- [69] EL-NAJDAWI, M.K., (1992), A Compact Heuristic for Lot-Size Scheduling in Multi-Stage, Multi-Product Production Processes, International Journal of Production Economics, Vol. 27, pp. 29-41
- [70] EL-NAJDAWI, M.K., (1994), A Job-Splitting Heuristic for Lot-Size Scheduling in Multi-Stage, Multi-Product Production Processes, European Journal of Operational Research, Vol. 75, pp. 365-377
- [71] EL-NAJDAWI, M.K., KLEINDORFER, P.R., (1993), Common Cycle Lot-Size Scheduling for Multi-Product, Multi-Stage Production, Management Science, Vol. 39, pp. 872-885
- [72] FEDERGRUEN, A., TZUR, M., (1991), A Simple Forward Algorithm to Solve General Dynamic Lot Sizing Models with n Periods in $O(n \log n)$ or O(n) Time, Management Science, Vol. 37, pp. 909-925
- [73] FLEISCHMANN, B., (1988), Operations-Research-Modelle und -Verfahren in der Produktionsplanung, Zeitschrift für betriebswirtschaftliche Forschung, Vol. 58, pp. 347-372
- [74] GABBAY, H., (1979), Multi-Stage Production Planning, Management Science, Vol. 25, pp. 1138-1149
- [75] GALLEGO, G., JONEJA, D., (1994), Economic Lot Scheduling Problem with Raw Material Considerations, Operations Research, Vol. 42, pp. 92– 101
- [76] GONÇALVES, J.F., LEACHMAN, R.C., GASCON, A., XIONG, Z.K., (1994), Heuristic Scheduling Policy for Multi-Item, Multi-Machine Production Systems with Time-Varying, Stochastic Demands, Management Science, Vol. 40, pp. 1455-1468
- [77] GORENSTEIN, S., (1970), Planning Tire Production, Management Science, Vol. 17, pp. B72-B82
- [78] GOYAL, S.K., (1976), Note on "Manufacturing Cycle Time Determination for a Multi-Stage Economic Production Quantity Model", Management Science, Vol. 23, pp. 332-333

- [79] GOYAL, S.K., GUNASEKARAN, A., (1990), Multi-Stage Production-Inventory Systems, European Journal of Operational Research, Vol. 46, pp. 1–20
- [80] GRAVES, S.C., (1981), Multi-Stage Lot-Sizing: An Iterative Procedure, in: Schwarz, L.B., (ed.) Multi-Level Production/Inventory Control Systems: Theory and Practice, Studies in the Management Science, Vol. 16, Amsterdam, North-Holland, pp. 95-109
- [81] GRAVES, S.C., MEAL, H.C., DASU, S.D., QUI, Y., (1986), Two-Stage Production Planning in a Dynamic Environment, in: Axsäter, S., Schneeweiss, C., Silver, E., (eds.), Multi-Stage Production Planning and Inventory Control, Berlin, Springer, pp. 9-43
- [82] GRAVES, S.C., SCHWARZ, L.B., (1977), Single Cycle Continuous Review Policies for Arborescent Production/Inventory Systems, Management Science, Vol. 23, pp. 529-540
- [83] GRAVES, S.C., SCHWARZ, L.B., (1978), On Stationarity and Optimality in Arborescent Production/Inventory Systems, Management Science, Vol. 24, pp. 1768-1769
- [84] GUPTA, S.M., BRENNAN, L., (1992), Lot Sizing and Backordering in Multi-Level Product Structures, Production and Inventory Management Journal, Vol. 33, No. 1, pp. 27-35
- [85] GUPTA, Y.P., KEUNG, Y.K., (1990), A Review of Multi-Stage Lot-Sizing Models, International Journal of Production Management, Vol. 10, pp. 57-73
- [86] HAASE, K., (1994), Lotsizing and Scheduling for Production Planning, Lecture Notes in Economics and Mathematical Systems, Vol. 408, Berlin, Springer
- [87] HAEHLING VON LANZENAUER, C., (1967), Optimale Lagerhaltung bei mehrstufigen Produktionsprozessen, Unternehmensforschung, Vol. 11, pp. 33-48
- [88] HAEHLING VON LANZENAUER, C., (1970), A Production Scheduling Model by Bivalent Linear Programming, Management Science, Vol. 17, pp. 105-111
- [89] HAEHLING VON LANZENAUER, C., (1970), Production and Employment Scheduling in Multistage Production Systems, Naval Research Logistics, Vol. 17, pp. 193–198

- [90] HAHM, J., YANO, C.A., (1995), The Economic Lot and Delivery Scheduling Problem: The Common Cycle Case, IIE Transactions, Vol. 27, pp. 113-125
- [91] HAHM, J., YANO, C.A., (1995), The Economic Lot and Delivery Scheduling Problem: Models for Nested Schedules, IIE Transactions, Vol. 27, pp. 126-139
- [92] HARL, J.E., RITZMAN, L.P., (1985), An Algorithm to Smooth Near-Term Capacity Requirements Generated by MRP Systems, Journal of Operations Management, Vol. 5, pp. 309-326
- [93] HARRIS, F.W., (1913), How Many Parts to Make at Once, Factory, The Magazine of Management, Vol. 10, pp. 135–136, 152, reprinted (1990), Operations Research, Vol. 38, pp. 947–950
- [94] HECHTFISCHER, R., (1991), Kapazitätsorientierte Verfahren der Losgrössenplanung, Wiesbaden, Deutscher Universitäts-Verlag
- [95] HEINRICH, C.E., (1987), Mehrstufige Losgrössenplanung in hierarchisch strukturierten Produktionsplanungssystemen, Berlin, Springer
- [96] HEINRICH, C.E., SCHNEEWEISS, C., (1986), Multi-Stage Lot-Sizing for General Production Systems, in: Axsäter, S., Schneeweiss, C., Silver, E., (eds.), Multi-Stage Production Planning and Inventory Control, Berlin, Springer, pp. 150-181
- [97] HELBER, S., (1994), Kapazitätsorientierte Losgrössenplanung in PPS-Systemen, Stuttgart, M & P
- [98] HELBER, S., (1995), Lot Sizing in Capacitated Production Planning and Control Systems, OR Spektrum, Vol. 17, pp. 5–18
- [99] Ho, C., (1993), Evaluating Lot-Sizing Performance in Multi-Level MRP-Systems: A Comparative Analysis of Multiple Performance Measures, International Journal of Operations and Production Management, Vol. 13, pp. 52-79
- [100] HOFMANN, C., (1994), Abstimmung von Produktions- und Transportlosgrössen zwischen Zulieferer und Produzent — Eine Analyse auf der Grundlage stationärer Losgrössenmodelle, OR Spektrum, Vol. 16, pp. 9-20
- [101] HSU, J.I.S., (1984), Economic Production Quantity Determination in the Multistage Process, Production and Inventory Management Journal, Vol. 25, No. 4, pp. 61-70
- [102] HSU, J.I.S., EL-NAJDAWI, M.K., (1990), Common Cycle Scheduling in a Multistage Production Process, Engineering Costs and Production Economics, Vol. 20, pp. 73-80

- [103] HUM, S.H., SARIN, R.K., (1991), Simultaneous Product-Mix Planning, Lot Sizing and Scheduling at Bottleneck Facilities, Operations Research, Vol. 39, pp. 296-307
- [104] IYOGUN, P., ATKINS, D., (1993), A Lower Bound and an Efficient Heuristic for Multistage Multiproduct Distribution Systems, Management Science, Vol. 39, pp. 204-217
- [105] JACKSON, P.L., MAXWELL, W.L., MUCKSTADT, J.A., (1988), Determining Optimal Reorder Intervals in Capacitated Production-Distribution Systems, Management Science, Vol. 34, pp. 938-958
- [106] JACOBS, F.R., KHUMAWALA, B.M., (1980), Multi-Level Lot Sizing: An Experimental Analysis, Proceedings of the American Institute of Decision Sciences, Atlanta, GA, p. 288
- [107] JACOBS, F.R., KHUMAWALA, B.M., (1982), Multi-Level Lot Sizing in Material Requirements Planning: An Empirical Investigation, Computers & Operations Research, Vol. 9, pp. 139-144
- [108] JAHNKE, H., (1995), Produktion bei Unsicherheit Elemente einer betriebswirtschaftlichen Produktionslehre bei Unsicherheit, Physica-Schriften zur Betriebswirtschaft, Vol. 50, Heidelberg, Physica
- [109] JENSEN, P., KAHN, H.A., (1972), Scheduling in a Multi-Stage Production System with Set-Up and Inventory Costs, AIIE Transactions, Vol. 4, pp. 126-133
- [110] JONEJA, D., (1991), Multi-Echelon Assembly Systems with Non-Stationary Demands: Heuristics and Worst Case Performance Bounds, Operations Research, Vol. 39, pp. 512-518
- [111] JORDAN, C., (1995), Batching and Scheduling Models and Methods for Several Problem Classes, Ph.D. dissertation, University of Kiel
- [112] KALYMON, B.A., (1972), A Decomposition Algorithm for Arborescence Inventory Systems, Operations Research, Vol. 20, pp. 860–874
- [113] KIMMS, A., (1996), Multi-Level, Single-Machine Lot Sizing and Scheduling (with Initial Inventory), European Journal of Operational Research, Vol. 89, pp. 86-99
- [114] KIMMS, A., (1996), Competitive Methods for Multi-Level Lot Sizing and Scheduling: Tabu Search and Randomized Regrets, International Journal of Production Research, Vol. 34, pp. 2279–2298
- [115] KIMMS, A., (1996), Multi-Level Lot Sizing and Scheduling Methods for Capacitated, Dynamic, and Deterministic Models, Ph.D. dissertation, University of Kiel

- [116] KRAJEWSKI, L.J., RITZMAN, L.P., WONG, D. S., (1980), The Relationship between Product Structure and Multistage Lot Sizes: A Preliminary Analysis, Proceedings of the American Institute of Decision Sciences, Atlanta, GA, pp. 6-8
- [117] KUIK, R., SALOMON, M., (1990), Multi-Level Lot-Sizing Problem: Evaluation of a Simulated-Annealing Heuristic, European Journal of Operational Research, Vol. 45, pp. 25-37
- [118] KUIK, R., SALOMON, M., VAN WASSENHOVE, L.N., MAES, J., (1993), Linear Programming, Simulated Annealing and Tabu Search Heuristics for Lotsizing in Bottleneck Assembly Systems, IIE Transactions, Vol. 25, No. 1, pp. 62-72
- [119] KUIK, R., SALOMON, M., VAN WASSENHOVE, L.N., (1994), Batching Decisions: Structure and Models, European Journal of Operational Research, Vol. 75, pp. 243-263
- [120] LAFORGE, R.L., (1982), MRP and the Part Period Algorithm, Journal of Purchasing and Materials Management, Vol. 18, pp. 21-26
- [121] LAFORGE, R.L., (1985), A Decision Rule for Creating Planned Orders in MRP, Production and Inventory Management Journal, Vol. 26, pp. 115– 126
- [122] LAMBRECHT, M.R., VANDER EECKEN, J., (1978), A Facilities in Series Capacity Constrained Dynamic Lot-Size Model, European Journal of Operational Research, Vol. 2, pp. 42-49
- [123] LAMBRECHT, M.R., VANDER EECKEN, J., VANDERVEKEN, H., (1981), Review of Optimal and Heuristic Methods for a Class of Facilities in Series Dynamic Lot-Size Problems, in: Schwarz, L.B., (ed.), Multi-Level Production / Inventory Control Systems: Theory and Practice, Studies in the Management Science, Vol. 16, Amsterdam, North-Holland, pp. 69-94
- [124] LAMBRECHT, M.R., VANDER EECKEN, J., VANDERVEKEN, H., (1983), A Comparative Study of Lot Sizing Procedures for Multi-Stage Assembly Systems, OR Spektrum, Vol. 5, pp. 33-43
- [125] LASSERRE, J.B., (1992), An Integrated Model for Job-Shop Planning and Scheduling, Management Science, Vol. 38, pp. 1201–1211
- [126] LOVE, S.F., (1972), A Facilities in Series Inventory Model with Nested Schedules, Management Science, Vol. 18, pp. 327-338
- [127] MAES, J., (1987), Capacitated Lotsizing Techniques in Manufacturing Resource Planning, Ph.D. dissertation, University of Leuven

- [128] MAES, J., MCCLAIN, J.O., VAN WASSENHOVE, L.N., (1991), Multilevel Capacitated Lotsizing Complexity and LP-Based Heuristics, European Journal of Operational Research, Vol. 53, pp. 131-148
- [129] MAES, J., VAN WASSENHOVE, L.N., (1991), Capacitated Dynamic Lot-Sizing Heuristics for Serial Systems, International Journal of Production Research, Vol. 29, pp. 1235-1249
- [130] MATHES, H.D., (1993), Some Valid Constraints for the Capacitated Assembly Line Lotsizing Problem, in: Fandel, G., Gulledge, Th., Jones, A., Operations Research in Production Planning and Control, Berlin, Springer, pp. 444-458
- [131] MAXWELL, W.L., MUCKSTADT, J.A., (1985), Establishing Consistent and Realistic Reorder Intervals in Production-Distribution Systems, Operations Research, Vol. 33, pp. 1316-1341
- [132] MCCLAIN, J.O., MAXWELL, W.L., MUCKSTADT, J.A., THOMAS, L.J., WEISS, E.N., (1982), On MRP Lot Sizing, Management Science, Vol. 28, pp. 582-584
- [133] MCCLAIN, J.O., TRIGEIRO, W.W., (1985), Cyclic Assembly Schedules, IIE Transactions, Vol. 17, pp. 346–353
- [134] MCKNEW, M.A., SAYDAM, C., COLEMAN, B. J., (1991), An Efficient Zero-One Formulation of the Multilevel Lot-Sizing Problem, Decision Sciences, Vol. 22, pp. 280-295
- [135] MCLAREN, B.J., (1976), A Study of Multiple Level Lotsizing Procedures for Material Requirements Planning Systems, Ph.D. dissertation, Purdue University
- [136] MOGG, J.M., BIGHAM, P.E., (1977), Scheduling a Multi-Stage Production System with Startup Delays, Omega, Vol. 6, pp. 183-187
- [137] MOILY, J.P., (1982), Optimal and Heuristic Lot-Sizing Procedures for Multi-Stage Manufacturing Systems, Ph.D. dissertation, University of Wisconsin
- [138] MOILY, J.P., (1986), Optimal and Heuristic Procedures for Component Lot-Splitting in Multi-Stage Manufacturing Systems, Management Science, Vol. 32, pp. 113-125
- [139] MUCKSTADT, J.A., SINGER, H.M., (1978), Comments on "Single Cycle Continuous Review Policies for Arborescent Production/Inventory Systems", Management Science, Vol. 24, pp. 1766-1768

- [140] MÜLLER-MERBACH, H., (1965), Optimale Losgrössen bei mehrstufiger Fertigung, Zeitschrift für wirtschaftliche Fertigung, Vol. 60, pp. 113-118
- [141] NEW, C.C., (1974), Lot-Sizing in Multi-Level Requirements Planning Systems, Production and Inventory Management Journal, Vol. 15, No. 4, pp. 57-72
- [142] PATTERSON, J.H., (1973), Alternate Methods of Project Scheduling with Limited Resources, Naval Research Logistics, Vol. 20, pp. 767-784
- [143] PENG, K., (1985), Lot-Sizing Heuristics for Multi-Echelon Assembly Systems, Engineering Costs and Production Economics, Vol. 9, pp. 51-57
- [144] POCHET, Y., WOLSEY, L.A., (1991), Solving Multi-Item Lot-Sizing Problems Using Strong Cutting Planes, Management Science, Vol. 37, pp. 53-67
- [145] RAJAGOPALAN, S., (1992), A Note on "An Efficient Zero-One Formulation of the Multilevel Lot-Sizing Problem", Decision Sciences, Vol. 23, pp. 1023-1025
- [146] RAMSEY, T.E., RARDIN, R.R., (1983), Heuristics for Multistage Production Planning Problems, Journal of the Operational Research Society, Vol. 34, pp. 61-70
- [147] RAO, V.V., (1981), Optimal Lot Sizing for Acyclic Multi-Stage Production Systems, Ph.D. dissertation, Georgia Institute of Technology
- [148] RATURI, A., S., HILL, A.V., (1988), An Experimental Analysis of Capacity-Sensitive Setup Parameters for MRP Lot Sizing, Decision Sciences, Vol. 19, pp. 782-800
- [149] REHMANI, Q., STEINBERG, E., (1982), Simple Single Pass, Multiple Level Lot Sizing Heuristics, Proceedings of the American Institute of Decision Sciences, Atlanta, GA, pp. 124–126
- [150] RICHTER, K., VÖRÖS, J., (1989), On the Stability Region for Multi-Level Inventory Problems, European Journal of Operational Research, Vol. 41, pp. 169-173
- [151] ROLL, Y., KARNI, R., (1991), Multi-Item, Multi-Level Lot Sizing with an Aggregate Capacity Constraint, European Journal of Operational Research, Vol. 51, pp. 73-87
- [152] ROSLING, K., (1986), Optimal Lot-Sizing for Dynamic Assembly Systems, in: Axsäter, S., Schneeweiss, C., Silver, E.A., (eds.), Multi-Stage Production Planning and Inventory Control, Berlin, Springer, pp. 119-131

- [153] ROUNDY, R.O., (1986), A 98%-Effective Lot-Sizing Rule for a Multi-Product, Multi-Stage Production/Inventory System, Mathematics of Operations Research, Vol. 11, pp. 699-727
- [154] ROUNDY, R.O., (1989), Rounding Off to Powers of Two in Continuous Relaxations of Capacitated Lot Sizing Problems, Management Science, Vol. 35, pp. 1433-1442
- [155] ROUNDY, R.O., (1993), Efficient, Effective Lot Sizing for Multistage Production Systems, Operations Research, Vol. 41, pp. 371-385
- [156] SALOMON, M., (1991), Deterministic Lotsizing Models for Production Planning, Lecture Notes in Economics and Mathematical Systems, Vol. 355, Berlin, Springer
- [157] SALOMON, M., KUIK, R., VAN WASSENHOVE, L.N., (1993), Statistical Search Methods for Lotsizing Problems, Annals of Operations Research, Vol. 41, pp. 453-468
- [158] SCHUSSEL, G., (1968), Job-Shop Lot Release Sizes, Management Science, Vol. 14, pp. B449-B472
- [159] SCHWARZ, L.B., (1973), A Simple Continuous Review Deterministic One-Warehouse N-Retailer Inventory Problem, Management Science, Vol. 19, pp. 555-566
- [160] SCHWARZ, L.B., SCHRAGE, L., (1975), Optimal and System Myopic Policies for Multi-Echelon Production/Inventory Assembly Systems, Management Science, Vol. 21, pp. 1285-1294
- [161] SCHWARZ, L.B., SCHRAGE, L., (1978), On Echelon Holding Costs, Management Science, Vol. 24, pp. 865–866
- [162] SIMPSON, N.C., ERENGUC, S.S., (1994), Multiple Stage Production Planning Research: History and Opportunities, Working Paper, State University of New York at Buffalo
- [163] SIMPSON, N.C., ERENGUC, S.S., (1994), Improved Heuristic Methods for Multiple Stage Production Planning, Working Paper, State University of New York at Buffalo
- [164] STADTLER, H., (1994), Mixed Integer Programming Model Formulations for Dynamic Multi-Item Multi-Level Capacitated Lotsizing, Working Paper, Technical University of Darmstadt
- [165] STADTLER, H., (1995), Reformulations of the Shortest Route Model for Dynamic Multi-Item Multi-Level Capacitated Lotsizing, Working Paper, Technical University of Darmstadt

- [166] STEINBERG, E., NAPIER, H.A., (1980), Optimal Multi-Level Lot Sizing for Requirements Planning Systems, Management Science, Vol. 26, pp. 1258-1271
- [167] STEINBERG, E., NAPIER, H.A., (1982), On "A Note on MRP Lot Sizing", Management Science, Vol. 28, pp. 585–586
- [168] SUM, C.C., HILL, A.V., (1993), A New Framework for Manufacturing Planning and Control Systems, Decision Sciences, Vol. 24, pp. 739-760
- [169] SUM, C.C., PNG, D.O.S., YANG, K.K., (1993), Effects of Product Structure Complexity on Multi-Level Lot Sizing, Decision Sciences, Vol. 24, pp. 1135-1156
- [170] SZENDROVITS, A.Z., (1975), Manufacturing Cycle Time Determination for a Multistage Economic Production Quantity Model, Management Science, Vol. 22, pp. 298-308
- [171] SZENDROVITS, A.Z., (1976), On the Optimality of Sub-Batch Sizes for a Multi-Stage EPQ Model — A Rejoinder, Management Science, Vol. 23, pp. 334-338
- [172] SZENDROVITS, A.Z., (1978), A Comment on "Optimal and System Myopic Policies for Multi-Echelon Production / Inventory Assembly Systems", Management Science, Vol. 24, pp. 863-864
- [173] SZENDROVITS, A.Z., (1981), Comments on the Optimality in Optimal and System Myopic Policies for Multi-Echelon Production/Inventory Assembly Systems, Management Science, Vol. 27, pp. 1081-1087
- [174] SZENDROVITS, A.Z., (1983), Non-Integer Optimal Lot Size Ratios in Two-Stage Production/Inventory Systems, International Journal of Production Research, Vol. 21, pp. 323-336
- [175] SZENDROVITS, A.Z., DREZNER, Z., (1980), Optimizing Multi-Stage Production with Constant Lot Size and Varying Numbers of Batches, OMEGA The International Journal of Management Science, Vol. 8, pp. 623-629
- [176] TAHA, H.A., SKEITH, R.W., (1970), The Economic Lot Size in Multistage Production Systems, AIIE Transactions, Vol. 2, pp. 157-162
- [177] TEMPELMEIER, H., (1995), Material-Logistik Grundlagen der Bedarfsund Losgrössenplanung in PPS-Systemen, Berlin, Springer, 3rd edition
- [178] TEMPELMEIER, H., DERSTROFF, M., (1993), Mehrstufige Mehrprodukt-Losgrössenplanung bei beschränkten Ressourcen und genereller Erzeugnisstruktur, OR Spektrum, Vol. 15, pp. 63-73

- [179] TEMPELMEIER, H., DERSTROFF, M., (1996), A Lagrangean-Based Heuristic for Dynamic Multi-Level Multi-Item Constrained Lotsizing with Setup Times, Management Science, Vol. 42, pp. 738-757
- [180] TEMPELMEIER, H., HELBER, S., (1994), A Heuristic for Dynamic Multi-Item Multi-Level Capacitated Lotsizing for General Product Structures, European Journal of Operational Research, Vol. 75, pp. 296-311
- [181] THOMPSON, G.L., (1965), On the Parts Requirement Problem, Operations Research, Vol. 13, pp. 453-461
- [182] TOKLU, B., WILSON, J.M., (1992), A Heuristic for Multi-Level Lot-Sizing Problems with a Bottleneck, International Journal of Production Research, Vol. 30, pp. 787-798
- [183] VAZSONYI, A., (1958), Scientific Programming in Business and Industry, New York, Wiley
- [184] VEINOTT, A.F., (1969), Minimum Concave-Cost Solution of Leontief Substitution Models of Multi-Facility Inventory Systems, Operations Research, Vol. 17, pp. 262-291
- [185] VERAL, E.A., LAFORGE, R.L., (1985), The Performance of a Simple Incremental Lot-Sizing Rule in a Multilevel Inventory Environment, Decision Sciences, Vol. 16, pp. 57-72
- [186] VICKERY, S.K., MARKLAND, R.E., (1986), Multi-Stage Lot-Sizing in a Serial Production System, International Journal of Production Research, Vol. 24, pp. 517-534
- [187] VÖRÖS, J., CHAND, S., (1992), Improved Lot Sizing Heuristics for Multi-Stage Inventory Models with Backlogging, International Journal of Production Economics, Vol. 28, pp. 283-288
- [188] VÖRÖS, J., (1995), Setup Cost Stability Region for the Multi-Level Dynamic Lot Sizing Problem, European Journal of Operational Research, Vol. 87, pp. 132-141
- [189] WAGELMANS, A., VAN HOESEL, S., KOLEN, A., (1992), Economic Lot Sizing: An O(n log n) Algorithm that Runs in Linear Time in the Wagner-Whitin Case, Operations Research, Vol. 40, pp. S145-S156
- [190] WAGNER, H.M., WHITIN, T.M., (1958), Dynamic Version of the Economic Lot Size Model, Management Science, Vol. 5, pp. 89-96
- [191] WEMMERLÖV, U., (1982), An Experimental Analysis of the Use of Echelon Holding Costs and Single-Stage Lot-Sizing Procedures in Multi-Stage Production/Inventory Systems, International Journal of Production Management, Vol. 2, pp. 42-54

- [192] WILLIAMS J.F., (1981), Heuristic Techniques for Simultaneous Scheduling of Production and Distribution in Multi-Echelon Structures: Theory and Empirical Comparisons, Management Science, Vol. 27, pp. 336-352
- [193] WILLIAMS, J.F., (1982), On the Optimality of Integer Lot Size Ratios in Economic Lot Size Determination in Multi-Stage Assembly Systems, Management Science, Vol. 28, pp. 1341-1349
- [194] YANO, C.A., LEE, H.L., (1995), Lot Sizing with Random Yields: A Review, Operations Research, Vol. 43, pp. 311-333
- [195] YELLE, L.E., (1976), Materials Requirements Lot Sizing: A Multi-Level Approach, International Journal of Production Research, Vol. 19, pp. 223-232
- [196] ZÄPFEL, G., ATTMANN, J., (1980), Losgrössenplanung: Lösungsverfahren für den dynamischen Fall bei beschränkten Kapazitäten und mehrstufiger Fertigung, Das Wirtschaftsstudium, Vol. 9, pp. 122-126 (part I) and pp. 174-177 (part II)
- [197] ZAHORIK, A., THOMAS, L.J., TRIGEIRO, W. W., (1984), Network Programming Models for Production Scheduling in Multi-Stage, Multi-Item Capacitated Systems, Management Science, Vol. 30, pp. 308-325
- [198] ZANGWILL, W.I., (1966), A Deterministic Multiproduct, Multifacility Production and Inventory Model, Operations Research, Vol. 14, pp. 486– 507
- [199] ZANGWILL, W.I., (1969), A Backlogging Model and a Multi-Echelon Model of a Dynamic Economic Lot Size Production System — A Network Approach, Management Science, Vol. 15, pp. 506-527
- [200] ZANGWILL, W.I., (1987), Eliminating Inventory in a Series Facility Production System, Management Science, Vol. 33, pp. 1150-1164