

A Service of

ZBW

Leibniz-Informationszentrum Wirtschaft Leibniz Information Centre for Economics

Lan, Jibin; Jin, Ruifang; Zheng, Zhaoyi; Hu, Mingming

## Article

# Priority degrees for hesitant fuzzy sets: Application to multiple attribute decision making

**Operations Research Perspectives** 

**Provided in Cooperation with:** Elsevier

*Suggested Citation:* Lan, Jibin; Jin, Ruifang; Zheng, Zhaoyi; Hu, Mingming (2017) : Priority degrees for hesitant fuzzy sets: Application to multiple attribute decision making, Operations Research Perspectives, ISSN 2214-7160, Elsevier, Amsterdam, Vol. 4, pp. 67-73, https://doi.org/10.1016/j.orp.2017.05.001

This Version is available at: https://hdl.handle.net/10419/178278

#### Standard-Nutzungsbedingungen:

Die Dokumente auf EconStor dürfen zu eigenen wissenschaftlichen Zwecken und zum Privatgebrauch gespeichert und kopiert werden.

Sie dürfen die Dokumente nicht für öffentliche oder kommerzielle Zwecke vervielfältigen, öffentlich ausstellen, öffentlich zugänglich machen, vertreiben oder anderweitig nutzen.

Sofern die Verfasser die Dokumente unter Open-Content-Lizenzen (insbesondere CC-Lizenzen) zur Verfügung gestellt haben sollten, gelten abweichend von diesen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

#### Terms of use:

Documents in EconStor may be saved and copied for your personal and scholarly purposes.

You are not to copy documents for public or commercial purposes, to exhibit the documents publicly, to make them publicly available on the internet, or to distribute or otherwise use the documents in public.

If the documents have been made available under an Open Content Licence (especially Creative Commons Licences), you may exercise further usage rights as specified in the indicated licence.



ND http://creativecommons.org/licenses/by-nc-nd/4.0/





ELSEVIER

Contents lists available at ScienceDirect

# **Operations Research Perspectives**

journal homepage: www.elsevier.com/locate/orp

# Priority degrees for hesitant fuzzy sets: Application to multiple attribute decision making



## Jibin Lan, Ruifang Jin\*, Zhaoyi Zheng, Mingming Hu

College of Mathematics and Information Science, Guangxi University, Nanning, Guangxi 530004, PR China

#### ARTICLE INFO

Article history: Received 9 October 2016 Revised 16 February 2017 Accepted 1 May 2017 Available online 3 May 2017

Keywords: Priority degree Order relations Hesitant fuzzy sets Multiple attribute decision making

#### 1. Introduction

The fuzzy sets theory introduced by Zadeh [1] has been very successful in dealing with problems involving uncertainty. With an increase in inaccurate and vague information in real life problems, several extensions of the fuzzy set have been developed, one of which is the intuitionistic fuzzy set (IFS) pioneered by Atanassov [2], which has a membership function, a non-membership function and a hesitancy function. Zadeh [3] presented a type-2 fuzzy set that allowed the membership of a given element to be a fuzzy set. The type-n fuzzy set [4] generalized type-2 fuzzy set, thereby permitting the membership to be a type-n-1 fuzzy set. The fuzzy multiset introduced by Yager [5] allowed elements to be repeated more than once.

In practical applications, because of a lack of knowledge, time pressure and other reasons, people do not often agree on specific elements in complex decisions, which means that it is often difficult to reach agreement. For example, two decision makers may discuss the membership degree of an element x to a set A, for which one decision maker wishes to assign 0.4 but the other wishes to assign 0.8. Accordingly, the difficulty in establishing a common membership degree is not because there is a margin of error or some possibility distribution values, but because there is a set of possible values [6]. To deal with such cases, Torra [7] and Torra and Narukawa [8] proposed the concept of the hesitant fuzzy set(HFS), which permitted membership to have a set of possible values.

\* Corresponding author. E-mail addresses: lanjibin@gxu.edu.cn (J. Lan), jinruifang999@163.com (R. Jin).

#### ABSTRACT

In this paper, some drawbacks to existing ordering relations for hesitant fuzzy sets are examined using examples. To overcome these flaws, a priority degree formula for comparing two hesitant fuzzy sets is presented and the desirable priority degree properties studied. Then, based on an introduced priority degree formula, a new hesitant fuzzy multiple attribute decision making methodology is proposed. Finally, a numerical example together with a comparison analysis is given to illustrate the effectiveness and feasibility of the new approach to decision making applications.

© 2017 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license. (http://creativecommons.org/licenses/by-nc-nd/4.0/)

Since the concept of the hesitant fuzzy set was established, it has gained increasing attention [9–17] and has been successfully applied to many uncertain decision making problems. Many studies have also been conducted on the application of HFS aggregation operators [18–20] and distance and similarity measures [21–23] to multi-criteria decision making problems.

Multi-criteria decision making has been widely applied in many scientific fields [24–26], such as medical care [27], engineering [28], social sciences [29] and economics [30]. In general, multiple attribute decision making problems have two phases; aggregation and exploitation. Of these, the aggregation phase is more important, so significant aggregation techniques have been developed for decision-making processes, in which the experts express their assessments using HFSs. Xia and Xu [31] presented a hesitant fuzzy weighted averaging operator and a hesitant fuzzy weighted geometric operator, to which they gave different extensions and generalizations; a generalized hesitant fuzzy weighted averaging operator, a generalized hesitant fuzzy weighted geometric operator, a hesitant fuzzy hybrid averaging operator, and a hesitant fuzzy hybrid geometric operator. Yu et al. [32] proposed a new hesitant fuzzy aggregation operator based on the Choquet integral which included the importance of the elements, their ordered positions and a fuzzy measure. Motivated by the idea of prioritized aggregation operators, Wei [33] proposed a hesitant fuzzy prioritized weighted average and hesitant fuzzy prioritized weighted geometric aggregation operators, which accounted for the different criteria priority levels in multi-criteria decision-making problems. Yu and Zhou [34] defined a generalized hesitant fuzzy Bonferroni mean which extended the Bonferroni mean to a hesitant fuzzy environment. Other extensions of the Bonferroni mean were

http://dx.doi.org/10.1016/j.orp.2017.05.001

2214-7160/© 2017 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license. (http://creativecommons.org/licenses/by-nc-nd/4.0/)

proposed in [35,36]. Xia et al. [37] introduced a new HFS operator by extending the quasi-arithmetic means. Bedregal et al. [38] presented two methodologies to develop triangular hesitant aggregation functions over all THFS. Xu and Xia [39] proposed several distance and similarity measures and studied the properties and relationships between them. Zhou and Li [40] modified the axiom definitions for the distance and similarity measures developed by Xu and Xia [39], and proposed some new distance and similarity measures between HFSs based on Hamming and Euclidean distances. Peng et al. [41] presented a novel generalized hesitant fuzzy synergetic weighted distance measure which reflected both individual distances and their ordered positions. In addition to these, many approaches can be used to deal with multiple attribute decision making problems(see, [42-47]). An exploitation phase was developed to build the preference relations between the alternatives and a nondominant choice degree was applied to obtain a solution set of alternatives for multiple attribute decision making problems.

Ordering relations play an important role in decision making and some HFS ordering relations have been proposed. Rodriguez et al. [48] gave a definition for order relations between HFSs, and then used aggregation operators to determine the order relations between them. Xia and Xu [14] introduced a comparison law by defining a score function to determine the order relations between HFSs. Farhadinia [49] also developed two ordering methods for HFSs. Zhou [50] introduces the intuitionistic fuzzy ordered weighted cosine similarity (IFOWCS) measure by using the cosine similarity measure of intuitionistic fuzzy sets and the generalized ordered weighted averaging (GOWA) operator. Zhou [51] develops the continuous intuitionistic fuzzy ordered weighted distance (C-IFOWD) measure by using the continuous intuitionistic fuzzy ordered weighted averaging (C-IFOWA) operator in the interval distance. Wei et al. [52] define the Shapley value-based  $L_p$ -metric and extend VIKOR method with the  $L_p$ -metric to deal with the correlative multiple criteria decision making (MCDM) problem under hesitant fuzzy environment. Wei et al. [53] developed hesitant fuzzy choquet ordered averaging (HFCOA) operator and hesitant fuzzy choquet ordered geometric (HFCOG) operator, and apply the HF-COA and HFCOG operators to hesitant fuzzy multiple attribute decision making. Zhao et al. [54] utilize Einstein operations to develop hesitant fuzzy Einstein correlated averaging (HFECA) operator and hesitant fuzzy Einstein correlated geometric (HFECG) operator. They can not only consider the importance of the elements or their ordered positions, but also reflect the correlation among the elements or their ordered positions. In addition to these, many aggregation operators and methods can be used to rank HFSs (see, [18,55–58]). However, the existing order relations for HFSs are defective(see examples2-4). For example, Jack and Tom play a game that has three turns. Jack has three cards; a 9 of spades, a 6 of spades and a 3 of spades; and Tom has three cards; an 8 of spades, a 5 of spades and a 2 of spades. The rules of the game are: (1)Each person can only select one of their own cards to play in each turn; (2)The card with the higher points wins in each turn; (3)The person who wins two turns is the final winner. Although Jack's cards have a points' advantage, it is not certain that Jack can win the game, as his winning probability is 0.6667. From the example above, we can construct two HFEs;  $H_1(x) = \{0.9, 0.6, 0.3\}$  and  $H_2(x) = \{0.8, 0.5, 0.2\}$ . From the existing HFS order relations, we have  $H_1(x) \geq H_2(x)$ , which does not conform to the actual situation.

This paper seeks to overcome the flaws outlined above. The remainder of this paper is organized as follows: Section 2 reviews some basic concepts and order relations. Section 3 analyzes the order relations between HFSs, and in Section 4, a priority degree formula for comparing two hesitant fuzzy sets is presented and the desirable priority degree properties studied. In Section 5, based on the proposed formula for the priority degree, a new approach to hesitant fuzzy multiple attribute decision making is developed. Section 6 gives an example to illustrate the rationality and applicability of the new method and in Section 7 conclusions are given.

#### 2. Preliminaries

In this section, the HFS concept and order relations are briefly reviewed.

#### 2.1. Hesitant fuzzy sets

As people are usually hesitant when making decisions, it is often difficult to reach a final agreement. With these difficulties in mind, Torra [59] developed the following hesitant fuzzy set definition:

**Definition 1.** [59] Given a fixed set *X*, then a hesitant fuzzy set (HFS) on *X* is a function that when applied to X returns a subset of values in [0,1].

For convenience, Wei [33] completed the original HFS definition by including the HFS mathematical representation as follows:

 $E = (\langle x, h_E(x) \rangle | x \in X).$ 

where  $h_E(x)$  is a set of some values in [0,1], and denotes the possible membership degree of the element  $x \in X$  to the set *E*;  $h(x) = h_E(x)$  is called a hesitant fuzzy element (HFE).

**Example 1.** Suppose that  $X = \{x_1, x_2, x_3\}$  is the discourse set, and  $h_M(x_1) = \{0.8, 0.5, 0.3\}, h_M(x_2) = \{0.6, 0.4\}$  and  $h_M(x_3) = \{0.6, 0.3, 0.2\}$  are the HFEs for  $x_i(i = 1, 2, 3)$  to a set *E*. Then *E* can be considered a HFS; i.e.

 $E = \{ \langle x_1, \{0.8, 0.5, 0.3\} \rangle, \langle x_2, \{0.6, 0.4\} \rangle, \langle x_3, \{0.6, 0.3, 0.2\} \rangle \}.$ Further operations on HFEs can be seen in [7,14].

#### 2.2. Order relations between HFSs

Order relations play an important role in decision making. We first review some order relations.

**Definition 2.** [60] Given two HFSs,  $H_1$  and  $H_2$  on X of the same cardinality, it is defined that  $H_1 \ge H_2$  if  $H_1(x) \ge H_2(x)$  for all x. Note that  $H_1(x)$  and  $H_2(x)$  are HFEs. Here,  $h_1 \ge h_2$  for HFEs  $h_1$  and  $h_2$  if  $h_1^{\sigma(j)} \ge h_2^{\sigma(j)}$  for all  $j = \{1, \dots, |H_1|\}$ , where  $h^{\sigma(j)}$  is the *j*th element in h when they are ordered in a decreasing order.

**Definition 3.** [60] Let  $\varphi$  be a function on the HFSs such that the cardinality of  $\varphi$  is the same for all HFSs. We then say that  $\varphi$  is monotonic when  $\varphi(E) \ge \varphi(E')$  for all  $E = \{H_1, \dots, H_n\}$  and  $E' = \{H'_1, \dots, H'_n\}$  such that  $H'_i \ge H_i$  for all  $i = \{1, \dots, n\}$ .

**Definition 4.** [60] Let  $E = \{H_1, \dots, H_n\}$  be a set of *n* HFSs and  $\Theta$  a function,  $\Theta$ : [0, 1]<sup>*n*</sup>  $\rightarrow$  [0, 1], we then export the  $\Theta$  on the fuzzy sets to HFSs, which is defined as:

$$\Theta_E = \bigcup_{\gamma \in H_1(\chi) \times \dots \times H_n(\chi)} \{\Theta(\gamma)\}$$
(1)

**Proposition 1.**[60] Let  $E = \{H_1, \dots, H_n\}$  and  $E' = \{H'_1, \dots, H'_n\}$  such that  $H'_i \ge H_i$  for all  $i = \{1, \dots, n\}$ . Then, if  $\Theta$  is a monotonic function,  $\Theta_E$  is monotonic.

In practical applications, situations arise in which the number of the elements in the different hesitant fuzzy elements may vary. For correct operations, Xu and Xia [6] proposed the following regulation: the shorter element is extended by adding the minimum value, the maximum value, or any value until it has the same length as the longer element. The selection of this value depends mainly on the decision makers' risk preferences. Optimists expecting desirable outcomes may add the maximum value, while pessimists expecting unfavorable outcomes may add the minimum value.

When the cardinality between two hesitant fuzzy elements is different, the method in Definition 2 leads to failure. To solve this problem, Xia and Xu [14] established a new order between HFEs by defining the following score function:

**Definition 5.** [14] Let *h* be an HFE, with a score function of *h* defined by

$$s(h) = \frac{1}{l(h)} \sum_{\gamma \in h} \gamma \qquad (2)$$

where l(h) is the number of elements in h.

Let  $h_1$  and  $h_2$  be two HFEs, then if  $s(h_1) > s(h_2)$ , then  $h_1 > h_2$ ; if  $s(h_1) = s(h_2)$ , then  $h_1 = h_2$ .

Except for the score function, the order for the HFSs was defined by Farhadinia<sup>[49]</sup> as follows:

**Definition 6.** [49] Let  $E_1$  and  $E_2$  be two HFSs on X = $\{x_1, x_2, \cdots, x_n\}$ .  $E_1 \succeq E_2$  if and only if  $Score(E_1) \ge Score(E_2)$ .

where  $Score(E_1) = \frac{1}{n} \sum_{i=1}^{n} s(h_{E_1}(x_i))$ and  $Score(E_2) =$  $\frac{1}{n}\sum_{i=1}^{n} s(h_{E_2}(x_i)).$ 

In addition to the score function, many other aggregation operators(see, [54]) can be used for the same purpose.

#### 3. Analysis of the HFS ordering relations

In this section, we analyze the HFS ordering relations using examples.

**Example 2.** Suppose that  $X = \{x\}$ ,  $H_1(x) = \{0.9, 0.6, 0.3\}$  and  $H_2(x) = \{0.8, 0.5, 0.2\}$  are two HFSs on X.

From Definition 2, we have  $H_1(x) \geq H_2(x)$ . In general, aggregation operators are monotonic increasing functions. Using aggregation operators to deal with the ordering of  $H_1(x)$  and  $H_2(x)$ , we also have  $H_1(x) \succeq H_2(x)$ .

TOPSIS can be used to deal with the order relations between  $H_1(x)$  and  $H_2(x)$ . Let  $H^-(x) = \{0, 0, 0\}$  and  $H^+(x) = \{1, 1, 1\}$ . Using the distance formula proposed by Xu and Xia [39], we have

$$d_h(H_1(x), H^-(x)) = 0.6, \quad d_h(H_2(x), H^-(x)) = 0.5.$$

$$d_h(H_1(x), H^+(x)) = 0.4, \quad d_h(H_2(x), H^+(x)) = 0.5.$$

$$\frac{d_h(H_1(x), H^-(x))}{d_h(H_1(x), H^-(x)) + d_h(H_1(x), H^+(x))} = 0.6.$$

$$\frac{d_h(H_2(x), H^-(x))}{d_h(H_2(x), H^-(x)) + d_h(H_2(x), H^+(x))} = 0.5.$$

$$\frac{d_h(H_1(x), H^-(x))}{d_h(H_1(x), H^-(x)) + d_h(H_1(x), H^+(x))} > \frac{d_h(H_2(x), H^-(x))}{d_h(H_2(x), H^-(x)) + d_h(H_2(x), H^+(x))}.$$

from which  $H_1(x) > H_2(x)$ . The same result can be derived using other formulas.

However,  $(u, v) \in H_1(x) \times H_2(x)$  are real elements that satisfy u< v; for example (0.6, 0.8). As in the example in the first section of this paper, it is uncertain whether  $H_1(x) \geq H_2(x)$ . This indicates that using Definition 2 is inflexible when ranking HFSs as significant information may be lost.

**Example 3.** Suppose that  $X = \{x\}$ .  $H_1(x) = \{0.9, 0.4\}$  and  $H_2(x) = \{x\}$ {0.8, 0.5, 0.2} are two HFSs on *X*.

Employing the score function, we have

$$s(H_1(x)) = 0.65, \qquad s(H_2(x)) = 0.3.$$

From Definition 5, we have  $H_1(x) > H_2(x)$ .

In this example, the number of elements in the two hesitant fuzzy sets is different. For correct operations, based on the regulation proposed by Xu and Xia [6], the shorter set is extended by adding the minimum value; that is,  $H_1(x) = \{0.9, 0.4, 0.4\}$ . TOPSIS is then used to deal with the order relations between  $H_1(x)$  and  $H_2(x)$ . Let  $H^-(x) = \{0, 0, 0\}$  and  $H^+(x) = \{1, 1, 1\}$ . Using the distance formula proposed by Xu and Xia [39], we have

$$d_h(H_1(x), H^-(x)) = 0.57, \quad d_h(H_2(x), H^-(x)) = 0.5.$$

$$d_h(H_1(x), H^+(x)) = 0.43, \quad d_h(H_2(x), H^+(x)) = 0.5.$$

 $\frac{d_h(H_1(x), H^-(x))}{d_h(H_1(x), H^-(x)) + d_h(H_1(x), H^+(x))} = 0.57.$ 

$$\frac{d_h(H_2(x), H^-(x))}{d_h(H_2(x), H^-(x)) + d_h(H_2(x), H^+(x))} = 0.5.$$

$$\begin{aligned} &\frac{d_h(H_1(x), H^-(x))}{d_h(H_1(x), H^-(x)) + d_h(H_1(x), H^+(x))} \\ &> \frac{d_h(H_2(x), H^-(x))}{d_h(H_2(x), H^-(x)) + d_h(H_2(x), H^+(x))}. \end{aligned}$$

so we also have  $H_1(x) > H_2(x)$ . The result is the same if other formulas are used to deal with this problem.

However, real elements  $(u, v) \in H_1(x) \times H_2(x)$  exist that satisfy u< v; for example, (0.4,0.8). Therefore, it is uncertain whether  $H_1(x)$  $\geq H_2(x)$ , which indicates that Xia and Xu's [14] comparison law to rank HFSs is also inflexible and significant information loss could occur.

**Example 4.** Suppose that  $X = \{x_1, x_2\}$ .  $E_1 = (\langle x_1, \{0.5, 0.4, 0.3\} \rangle, \langle x_1, x_2 \rangle)$ 

 $\langle x_2, \{0.9, 0.8, 0.7, 0.1\} \rangle$ ,  $E_2 = (\langle x_1, \{0.5, 0.3\} \rangle, \langle x_2, \{0.6, 0.5, 0.3\} \rangle)$ and  $E_3 = (\langle x_1, \{0.8, 0.7, 0.4, 0.3\} \rangle, \langle x_2, \{0.7, 0.4, 0.2\} \rangle)$  are three hesitant fuzzy sets on X.

By employing the score function, we have

$$s(h_{E_1}(x_1)) = 0.4,$$
  $s(h_{E_1}(x_2)) = 0.625,$   
 $s(h_{E_2}(x_1)) = 0.4,$   $s(h_{E_2}(x_2)) = 0.4667,$   
 $s(h_{E_3}(x_1)) = 0.55,$   $s(h_{E_3}(x_2)) = 0.4333.$ 

 $Score(E_1) = 0.5125$ ,  $Score(E_2) = 0.4335$ ,  $Score(E_3) = 0.4917$ .

 $Score(E_1) > Score(E_2) > Score(E_2)$ . According to Definition 6, we have  $E_1 \succ E_3 \succ E_2$ .

Since  $s(h_{E_1}(x_1)) < s(h_{E_3}(x_1))$  and  $s(h_{E_1}(x_2)) > s(h_{E_3}(x_2))$ , elements  $(u_1, v_1) \in h_{E_1}(x_1) \times h_{E_3}(x_1)$  exist to satisfy  $u_1 < v_1$  and  $(u_2, v_2) \in h_{E_1}(x_2) \times h_{E_3}(x_2)$  satisfies  $u_2 < v_2$ ; however, from the decision making viewpoint, it is not clear whether  $E_1 > E_3$ .

Many other aggregation operators (see [61]) have been used to rank HFSs. However, the same situation as shown in the above examples has been encountered, indicating that using aggregation operators to deal with HFS ordering is inflexible and could lead to information loss.

In the following, a priority degree definition for hesitant fuzzy sets is proposed and then a new method is introduced to solve the above problem.

#### 4. Priority degrees for hesitant fuzzy sets

To overcome the current flaws, in this section, a priority degree formula is proposed to deal with the ordering relations between HFSs.

**Definition 7.** Given a fixed set  $X = \{x_1, x_2, \dots, x_n\}$ , suppose that  $E_1 = \{\langle x_i, h_{E_1}(x_i) \rangle | x_i \in X\}$  and  $E_2 = \{\langle x_i, h_{E_2}(x_i) \rangle | x_i \in X\}$  are two hesitant fuzzy sets. The priority degree for  $E_1 \rangle E_2$  is defined by

$$P(E_1 \succ E_2) = \begin{cases} \frac{\sum_{i=1}^n S_1(x_i)}{\sum_{i=1}^n S_1(x_i) + \sum_{i=1}^n S_2(x_i)}, & \sum_{i=1}^n S_1(x_i) + \sum_{i=1}^n S_2(x_i) \neq 0, \\ 0.5, & \sum_{i=1}^n S_1(x_i) + \sum_{i=1}^n S_2(x_i) = 0. \end{cases}$$
(5)

where

 $h_{E_1}(x_i) = \{u_l(x_i) | u_l(x_i) \in [0, 1], l = 1, 2, \cdots, r_i\},\$ 

$$h_{E_2}(x_i) = \{v_t(x_i) | v_t(x_i) \in [0, 1], t = 1, 2, \cdots, s_i\},\$$

$$A_{1}(x_{i}) = \{(u_{l}(x_{i}), v_{t}(x_{i})) | u_{l}(x_{i}) - v_{t}(x_{i}) > 0, (u_{l}(x_{i}), v_{t}(x_{i})) \\ \in h_{E_{1}}(x_{i}) \times h_{E_{2}}(x_{i})\},$$

$$A_{2}(x_{i}) = \{(u_{l}(x_{i}), v_{t}(x_{i})) | u_{l}(x_{i}) - v_{t}(x_{i}) < 0, (u_{l}(x_{i}), v_{t}(x_{i})) \\ \in h_{E_{1}}(x_{i}) \times h_{E_{2}}(x_{i})\},\$$

$$A_{3}(x_{i}) = \{(u_{l}(x_{i}), v_{t}(x_{i})) | u_{l}(x_{i}) - v_{t}(x_{i}) = 0, (u_{l}(x_{i}), v_{t}(x_{i})) \\ \in h_{E_{1}}(x_{i}) \times h_{E_{2}}(x_{i})\},$$

$$S_1(x_i) = \begin{cases} \frac{1}{r_i s_i} \sum_{(u_l(x_i), v_t(x_i)) \in A_1(x_i)} (u_l(x_i) - v_t(x_i)), & A_1(x_i) \neq \phi; \\ 0, & A_1(x_i) = \phi. \end{cases}$$

$$S_{2}(x_{i}) = \begin{cases} \frac{1}{r_{i}S_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{2}(x_{i})} (v_{t}(x_{i}) - u_{l}(x_{i})), & A_{2}(x_{i}) \neq \phi; \\ 0, & A_{2}(x_{i}) = \phi. \end{cases}$$

**Remark 1.**  $S_1(x_i)$  represents the average residual amount for  $h_{E_1}(x_i)$  over  $h_{E_2}(x_i)$ . Corresponding,  $S_2(x_i)$  represents the average residual amount for  $h_{E_2}(x_i)$  over  $h_{E_1}(x_i)$ , and  $P(E_1 > E_2)$  represents the priority degree for  $E_1 > E_2$ . For example,  $P(E_1 > E_2) = 0.5$  indicates that the priority degree for  $E_1 > E_2$  is 0.5. Note that  $E_1 > P(E_1 > E_2)E_2$  does not mean that  $E_1$  is absolutely superior to  $E_2$ ; it just indicates that the priority degree for  $E_2 > E_1$  is  $1 - P(E_1 > E_2)$ .

Let  $X = \{x_1, x_2, \dots, x_n\}$ .  $E_1 = \{\langle x_i, h_{E_1}(x_i) \rangle | x_i \in X\}$ ,  $E_2 = \{\langle x_i, h_{E_2}(x_i) \rangle | x_i \in X\}$  and  $E_3 = \{\langle x_i, h_{E_3}(x_i) \rangle | x_i \in X\}$  are three hesitant fuzzy sets on *X*, where

$$h_{E_1}(x_i) = \{u_l(x_i) | u_l(x_i) \in [0, 1], l = 1, 2, \cdots, r_i\}$$

$$h_{E_2}(x_i) = \{ v_t(x_i) | v_t(x_i) \in [0, 1], t = 1, 2, \cdots, s_i \}$$

$$h_{E_3}(x_i) = \{w_k(x_i) | w_k(x_i) \in [0, 1], k = 1, 2, \cdots, q_i\}$$

$$\bar{u}(x_i) = \frac{1}{r_i} \sum_{l=1}^{r_i} u_l(x_i), \quad \bar{\nu}(x_i) = \frac{1}{s_i} \sum_{t=1}^{s_i} \nu_t(x_i),$$

we can conclude some properties about priority degree as follows: **Property 2.** (*normalization*).  $0 \le P(E_1 \succ E_2) \le 1$ ,  $0 \le P(E_2 \succ E_1) \le 1$ . **Property 3.** (complementarity).  $P(E_1 > E_2) + P(E_2 > E_1) = 1$ .

**Proof.** It is obvious that properties 2–3 hold.  $\Box$ 

**Property 4.** (intuition).  $P(E_1 \succ E_2) = 1$  if and only if  $u_l(x_i) \ge v_t(x_i)$  for all  $x_i$ , l, t and  $\exists l', t', u_{l'}(x_i) > v_{t'}(x_i)$ .

**Proof.**  $u_l(x_i) \ge v_t(x_i)$  for all  $x_i$ , l, t and  $\exists l', t', u_{l'}(x_i) > v_{t'}(x_i) \Leftrightarrow \sum_{i=1}^n S_2(x_i) = 0 \Leftrightarrow P(E_1 \succ E_2) = 1$ .  $\Box$ 

**Property 5.**  $P(E_1 > E_2) \ge \frac{1}{2}$  *if and only if*  $\sum_{i=1}^{n} \bar{u}(x_i) \ge \sum_{i=1}^{n} \bar{v}(x_i)$ .

Proof.

$$\begin{split} P(E_{1} \succ E_{2}) &\geq \frac{1}{2} \Leftrightarrow \sum_{i=1}^{n} S_{1}(x_{i}) \geq \sum_{i=1}^{n} S_{2}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{1}(x_{i})} (u_{l}(x_{i}) - v_{t}(x_{i})) \\ &\geq \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{2}(x_{i})} (v_{t}(x_{i}) - u_{l}(x_{i})) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{1}(x_{i})} u_{l}(x_{i}) + \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{2}(x_{i})} u_{l}(x_{i}) \\ &+ \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{1}(x_{i})} u_{l}(x_{i}) \\ &\geq \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{1}(x_{i})} v_{t}(x_{i}) + \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{2}(x_{i})} v_{t}(x_{i}) \\ &+ \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{1}(x_{i})} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}s_{i}} \sum_{(u_{l}(x_{i}), v_{t}(x_{i})) \in A_{3}(x_{i})} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{r_{i}} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{s_{i}} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{r_{i}} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{s_{i}} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{r_{i}} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{s_{i}} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{r_{i}} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{s_{i}} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{r_{i}} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{s_{i}} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{n} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{s_{i}} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{n} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{n} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{n} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{n} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{n} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^{n} v_{t}(x_{i}) \\ &\Leftrightarrow \sum_{i=1}^{n} \frac{1}{r_{i}} \sum_{l=1}^{n} u_{l}(x_{i}) \geq \sum_{i=1}^{n} \frac{1}{s_{i}} \sum_{l=1}^$$

**Property 6.** (weak transitivity). If  $P(E_1 > E_2) \ge \frac{1}{2}$ ,  $P(E_2 > E_3) \ge \frac{1}{2}$ , then  $P(E_1 > E_3) \ge \frac{1}{2}$ .

**Proof.**  $P(E_1 > E_2) \ge \frac{1}{2} \Leftrightarrow \sum_{i=1}^n \bar{u}(x_i) \ge \sum_{i=1}^n \bar{v}(x_i)$  and  $P(E_2 > E_3) \ge \frac{1}{2} \Leftrightarrow \sum_{i=1}^n \bar{v}(x_i) \ge \sum_{i=1}^n \bar{w}(x_i)$ , we have  $\sum_{i=1}^n \bar{u}(x_i) \ge \sum_{i=1}^n \bar{w}(x_i) \Rightarrow P(E_1 > E_3) \ge \frac{1}{2}$ , so property 6 holds.  $\Box$ 

**Example 5.** The proposed priority degree is employed to deal with **Example 2** above, so we have

$$S_1(x) = 0.2,$$
  $S_2(x) = 0.1,$ 

$$P(H_1(x) > H_2(x)) = 0.6667, \qquad P(H_2(x) > H_1(x)) = 0.3333,$$

$$H_1(x) \succ_{(0.6667)} H_2(x), \qquad H_2(x) \succ_{(0.3333)} H_1(x)$$

The result only show that the priority degree for  $H_1(x) > H_2(x)$  is 0.6667 and the priority degree for  $H_2(x) > H_1(x)$  is 0.3333; however, this does not mean that  $H_1(x)$  is absolutely superior to  $H_2(x)$ .

**Example 6.** The proposed priority degree is employed to deal with **Example 4** above, so we have

$$S_{1}(x_{1}) = 0.05, \qquad S_{1}(x_{2}) = 0.25,$$

$$S_{2}(x_{1}) = 0.05, \qquad S_{2}(x_{2}) = 0.0917,$$

$$P(E_{1} \succ E_{2}) = 0.6792, \qquad P(E_{2} \succ E_{1}) = 0.3208,$$
Similarly,
$$P(E_{1} \succ E_{3}) = 0.5362, \qquad P(E_{3} \succ E_{1}) = 0.4638,$$

$$P(E_{2} \succ E_{3}) = 0.3138, \qquad P(E_{3} \succ E_{2}) = 0.6862.$$

$$E_{1} \succ_{(0.6792)} E_{3} \succ_{(0.6862)} E_{2}, \qquad E_{3} \succ_{(0.6862)} E_{2} \succ_{(0.3208)} E_{1}$$

$$E_{3} \succ_{(0.4638)} E_{1} \succ_{(0.6792)} E_{2}, \qquad E_{2} \succ_{(0.3138)} E_{3} \succ_{(0.4638)} E_{1}$$

	ine razzy accession matima			
	<i>P</i> <sub>1</sub>	<i>P</i> <sub>2</sub>	P <sub>3</sub>	P <sub>4</sub>
$A_1$	{0.5, 0.4, 0.3}	{0.9, 0.8, 0.7, 0.1}	{0.5, 0.4, 0.2}	{0.9, 0.6, 0.5, 0.3}
$A_2$	{0.5, 0.3}	{0.9, 0.7, 0.6, 0.5, 0.2}	{0.8, 0.6, 0.5, 0.1}	{0.7, 0.4, 0.3}
$A_3$	{0.8, 0.7, 0.4, 0.3}	{0.7, 0.4, 0.2}	{0.8, 0.1}	{0.9, 0.8, 0.6}
$A_4$	{0.9, 0.7, 0.6, 0.3, 0.1}	{0.8, 0.7, 0.6, 0.4}	{0.9, 0.8, 0.7}	{0.9, 0.7, 0.6, 0.3}

Table 2

Converted	decision	matrix.

Table 1

Hesitant fuzzy decision matrix

	<i>P</i> <sub>1</sub>	<i>P</i> <sub>2</sub>	<i>P</i> <sub>3</sub>	<i>P</i> <sub>4</sub>
$A_1$	{0.075, 0.06, 0.045}	{0.27, 0.24, 0.21, 0.03}	{0.1, 0.08, 0.04}	{0.315, 0.21, 0.5, 0.105}
$A_2$	{0.075, 0.045}	{0.27, 0.21, 0.18, 0.15, 0.06}	{0.16, 0.12, 0.1, 0.02}	{0.245, 0.14, 0.105}
$A_3$	{0.12, 0.105, 0.06, 0.045}	{0.21, 0.12, 0.06}	{0.16, 0.02}	{0.315, 0.28, 0.21}
$A_4$	$\{0.135, 0.105, 0.09, 0.045, 0.015\}$	{0.12, 0.105, 0.09, 0.06}	{0.135, 0.12, 0.105}	{0.135, 0.105, 0.09, 0.045}

These results only show the degree of priority but not a absolute order relations. Compared with existing HFS order relations, the proposed priority degree formula conforms to the actual situation and has the following advantages: it is flexible, it does not loss decision making information, the results meet the conditions of Property 2. For convenient computation, before a new multiple attribute decision making method is proposed, we first introduce a new HFE operator.

**Definition 8.** For any HFE *h*, a new HFE operator is defined by

$$\lambda \odot h = \cup_{r \in h} \{\lambda r\}, \qquad 0 < \lambda \le 1 \tag{6}$$

#### 5. A new approach to multiple attribute decision making

Multiple attribute decision making has attracted significant attention [62,63] recently due to its practicability. In this section, we develop a new approach to hesitant fuzzy multiple attribute decision making based on the proposed priority degree.

Generally speaking, let  $A = \{A_1, A_2, \dots, A_m\}$  be the discrete set of alternatives, and  $C = \{C_1, C_2, \dots, C_n\}$  be the set of attributes. For each alternative  $A_i \in A$ , an expert gives a preference value  $a_{ij}$  with respect to attribute  $C_j \in C$  [64].  $w = (w_1, w_2, \dots, w_n)^T$  are the attribute weight vectors, for which  $w_j \in [0, 1], j = 1, 2, \dots, n$  and  $\sum_{j=1}^{n} w_j = 1$ . Note that  $a_{ij}$  represents the assessment information given by an expert about the *j*th attribute for alternative  $A_i$ , where  $a_{ij}$  is a hesitant fuzzy element, and all preference values for the alternatives make up the decision-making matrix  $A = (a_{ij})_{m \times n}$ .

In the following, a new method for multiple attribute decision making problems is proposed, in which the attribute weight information is known and the attribute values take the form of hesitant fuzzy elements. This new approach has the following steps:

Step 1: Let  $A = (a_{ij})_{m \times n}$  be a hesitant fuzzy decision-making matrix in which  $a_{ij}$  is each alternative  $A_i \in A$  for each attribute  $C_j \in C$ , and let  $w = (w_1, w_2, \dots, w_n)^T$  be the attribute weight vector in which  $w_j \in [0, 1], j = 1, 2, \dots, n$ , and  $\sum_{i=1}^n w_j = 1$ .

Step 2: Convert  $(a_{ij})_{m \times n}$  into  $(h_{ij})_{m \times n} = (w_j \odot a_{ij})_{m \times n}$  using Definition 8.

Step 3: Let  $C = \{C_1, C_2, \dots, C_n\}$ . The hesitant fuzzy sets are constructed on *C* as follows,

$$E_{A_i} = \{ < C_j, h_{ij} > | j = 1, 2, \cdots, n \}, i = 1, 2, \cdots, m.$$

Step 4: Calculate the priority degree between  $E_{A_i}$  and  $E_{A_j}$  ( $i \neq j, i, j = 1, 2, \dots, m$ ).

Step 5: Rank the alternatives. Step 6: End.

 Table 3

 Results obtained using priority degree

		01	5 0	
	$E_{A_1}$	$E_{A_2}$	$E_{A_3}$	$E_{A_4}$
$egin{array}{c} E_{A_1} \ E_{A_2} \ E_{A_3} \ E_{A_4} \end{array}$	0.5 0.7266 0.6279 0.2328	0.2734 0.5 0.6223 0.2806	0.3721 0.3777 0.5 0.1981	0.7672 0.7194 0.8019 0.5
$E_{A_4}$	0.2328	0.2806	0.1981	0.5

#### 6. Illustrative example

In this section, a numerical example and a comparison analysis are given to show the feasibility and validity of the proposed priority degree.

**Example**(adapted from [22]). Consider a decision-making problem that requires the assessment of various engines. Suppose that there are four engine brands (alternatives)  $A_i$  (i = 1, 2, 3, 4) to be assessed, from which the best needs to be selected. Four attributes are considered:  $P_1$ : responsiveness,  $P_2$ : fuel economy,  $P_3$ : vibration, and  $P_4$ : start. Assume that the attribute weight vector is  $\omega = (0.15, 0.3, 0.2, 0.35)$ . A hesitant fuzzy decision matrix is used to display the assessment values given by the decision makers as shown in Table 1.

In the following, assuming  $X = \{P_1, P_2, P_3, P_4\}$ , the hesitant fuzzy sets are constructed as follows (Table 2):

$$\begin{split} E_{A_1} &= \{ \langle P_1, \{0.075, 0.06, 0.045\} \rangle, \langle P_2, \{0.27, 0.24, 0.21, 0.03\} \rangle, \\ \langle P_3, \{0.1, 0.08, 0.04\} \rangle, \langle P_4, \{0.315, 0.21, 0.5, 0.105\} \rangle \} \\ E_{A_2} &= \{ \langle P_1, \{0.075, 0.045\} \rangle, \langle P_2, \{0.27, 0.21, 0.18, 0.15, 0.06\} \rangle, \\ \langle P_3, \{0.16, 0.12, 0.1, 0.02\} \rangle, \langle P_4, \{0.245, 0.14, 0.105\} \rangle \} \\ E_{A_3} &= \{ \langle P_1, \{0.12, 0.105, 0.06, 0.045\} \rangle, \langle P_2, \{0.21, 0.12, 0.06\} \rangle, \\ \langle P_3, \{0.16, 0.02\} \rangle, \langle P_4, \{0.315, 0.28, 0.21\} \rangle \} \\ E_{A_4} &= \{ \langle P_1, \{0.135, 0.105, 0.09, 0.045, 0.105\} \rangle, \\ \langle P_2, \{0.12, 0.105, 0.09, 0.06\} \rangle, \langle P_3, \{0.135, 0.12, 0.105\} \rangle, \\ \langle P_4, \{0.135, 0.105, 0.09, 0.045\} \rangle \} \end{split}$$

Compute the priority degree of each using Eq.(5), the results for which are shown in Table 3.

Analyzing the above priority degrees, the ranking of the alternatives is as follows:

 $A_3 \succ_{(0.6223)} A_2 \succ_{(0.7266)} A_1 \succ_{(0.7672)} A_4,$ 

These results only show the degree of priority between the alternatives not the absolute order relations; that is,  $A_3$  is not necessarily the optimal alternative. Similarly,  $A_4$  is not necessarily the worst alternative.

Li et al. [22] used distance and a similarity measures to deal with this problem, the results for which were as follows:

#### Table 4

Results obtained using the distance measure  $d_{ophug}$  in [22] with  $\alpha = 0.8$ ,  $\beta = 0.2$ .

	<i>A</i> <sub>1</sub>	<i>A</i> <sub>2</sub>	<i>A</i> <sub>3</sub>	<i>A</i> <sub>4</sub>	Rankings
$\begin{array}{l} \lambda = 1 \\ \lambda = 2 \\ \lambda = 6 \\ \lambda = 10 \end{array}$	0.6814 0.6967 0.7212 0.7346	0.6639 0.6802 0.7159 0.7355	0.6195 0.6380 0.6782 0.7059	0.6675 0.6909 0.7251 0.7379	$\begin{array}{c} A_{3} \succ A_{2} \succ A_{4} \succ A_{1} \\ A_{3} \succ A_{2} \succ A_{4} \succ A_{1} \\ A_{3} \succ A_{2} \succ A_{1} \succ A_{4} \\ A_{3} \succ A_{1} \succ A_{2} \succ A_{4} \end{array}$

Table 5

Results obtained using the distance measure  $d_{\omega g}$  in [22].

	<i>A</i> <sub>1</sub>	<i>A</i> <sub>2</sub>	A <sub>3</sub>	<i>A</i> <sub>4</sub>	Rankings
$\lambda = 1$	0.4779	0.5027	0.4292	0.3558	$A_4 \succ A_3 \succ A_1 \succ A_2$
$\lambda = 2$ $\lambda = 6$	0.5378 0.6599	0.5451 0.6476	0.5052 0.6704	0.4129 0.5699	$A_4 \succ A_3 \succ A_1 \succ A_2$ $A_4 \succ A_2 \succ A_1 \succ A_3$
$\lambda = 10$	0.7213	0.7046	0.7373	0.6537	$A_4 \succ A_2 \succ A_1 \succ A_3$

Results obtained using the score function in Definition 6.

$Score(A_1) = 0.1508$	$Score(A_2) = 0.1193$
-----------------------	-----------------------

 $Score(A_3) = 0.1427$   $Score(A_4) = 0.1009$ 

 $Score(A_1) > Score(A_3) > Score(A_2) > Score(A_4)$ 

According to Definition 6, we conclude

 $A_1 \succ A_3 \succ A_2 \succ A_4$ .

The above result is still too absolutely, contrast to the proposed method, which is short of flexible and can led to the decision information loss.

 $\alpha$  and  $\beta$  are the preference ratio between the hesitance degree and the membership values. When the ratio of the hesitance degree is greater than the membership values, the result is similar to that when using the proposed priority degree. Otherwise, the result is different from that obtained using the distance measure in [22].

The results shown in Tables 4 and 5 are absolutely order relations. Compared to the results obtained using the priority degree in Table 3, it can be concluded that the proposed priority degree formula better conforms to the actual situation, it is more flexible and retains the decision making information. In contrast, Tables 4 and 5 indicate that using distance and similar measures to determine the HFS order is inflexible and could lead to a loss of decision making information.

#### 7. Conclusions

In this paper, we analyzed the existing order relations for HFSs and provided a priority degree definition. Then, some desirable properties for the proposed priority degree formula were studied. For computation convenience, a new operator between the hesitant fuzzy elements was proposed. Based on the presented priority degree, a new multiple attribute decision making method was obtained. Finally, an illustrative example was given to show the rationality of the proposed priority degree.

#### Acknowledgments

The authors want to thank the anonymous referees for the valuable comments that have led to improvements in this paper. This research was supported by the National Foundation of China(No.71261001) and Guangxi Colleges and Universities Key Laboratory of Mathematics and Its Applications.

#### References

- [1] Zadeh LA. Fuzzy sets. Inform Contr 1965;8:338–56.
- [2] Atanassov K. Intuitionistic fuzzy sets. Fuzzy Sets Syst 1986;20:87-96.
- [3] Zadeh LA. The concept of a linguistic variable and its application to approximate reasoning-1. Inf Sci 1975;8:199–249.
- [4] Dubois D, Prade H. Fuzzy sets and systems: theory and applications. New York: Academic Press; 1980.
- [5] Yager RR. On the theory of bags. Int J Gen Syst 1986;13:23-37.
- [6] Xu ZS, Xia MM. Distance and similarity measures for hesitant fuzzy sets. Inf Sci 2011a;181:2128–38.
- [7] Torra V. Hesitant fuzzy sets. Int J Intell Syst 2010a;25:529-39. 543.
- [8] Torra V, Narukawa Y. On hesitant fuzzy sets and decision. In: The 18th IEEE international conference on fuzzy systems, Jeju island, Korea, vol. 544; 2009. p. 1378–82. 545.
- [9] Bedregal B, Reiser R, Bustince H, Molina CL, Torra V. Aggregation functions for typical hesitant fuzzy elements and the action of automorphisms. Inf Sci 2014b;255:82–99.
- [10] Chen N, Xu ZS, Xia MM. Interval-valued hesitant preference relations and their applications to group decision making. Knowl-Based Syst 2013b;37:528–40.
- [11] Chen N, Xu ZS, Xia MM. Correlation coefficients of hesitant fuzzy sets and their applications to clustering analysis. Appl Math Modell 2013a;37:2197–211.
- [12] Qian G, Wang H, Feng XQ. Generalized hesitant fuzzy sets and their application in decision support system. Knowl-Based Syst 2013;37:357–65.
- [13] Rodriguez RM, Martinez L, Herrera F. Hesitant fuzzy linguistic term sets for decision making. IEEE Trans Fuzzy Syst 2012;20:109–19.
- [14] Wang H, Xu ZS. Admissible orders of typical hesitant fuzzy elements and their application in ordered information fusion in multi-criteria decision making. Inf Fusion 2016;29:98–104.
- [15] Farhadinia B. Multiple criteria decision-making methods with completely unknown weights in hesitant fuzzy linguistic term setting. Knowl-Based Syst 2016b;93:135–44.
- [16] Farhadinia B. Hesitant fuzzy set lexicographical ordering and its application to multi-attribute decision making. Inf Sci 2016a;327:233–45.
- [17] Xu ZS, Xia MM. Hesitant fuzzy entropy measures and their use in multi-attribute decision making. Int J Intell Syst 2012;27:799–822.
- [18] Qin JD, Liu XW, Pedrycz W. Frank aggregation operators and their application to hesitant fuzzy multiple attribute decision making. Appl Soft Comput 2016;41:428–52.
- [19] Jin F, Ni ZW, Chen HY. Note on "hesitant fuzzy prioritized operators and their application to multiple attribute decision making". Knowl-Based Syst 2016;96:115–19.
- [20] Zhu B, Xu ZS, Xia MM. Hesitant fuzzy geometric Bonferroni means. Inf Sci 2012a;205:72–85.
- [21] Li D, Zeng W, Li J. New distance and similarity measures on hesitant fuzzy sets and their applications in multiple criteria decision making. Eng Appl Artif Intell 2015a;40:11–16.
- [22] Li D, Zeng W, Zhao Y. Note on distance measure of hesitant fuzzy sets. Inf Sci 2015b;321:103–15.
- [23] Dgenci M. A new distance measure for interval valued intuitionistic fuzzy sets and its application to group decision making problems with incomplete weights information. Appl Soft Comput 2016;41:120–34.
- [24] Chang YH, Yeh CH, Chang YW. A new method selection approach for fuzzy group multi-criteria decision making. Appl Soft Comput 2013;13:2179–87.
- [25] Kaya T, Kahraman C. An integrated fuzzy AHP-ELECTRE methodology for environmental impact assessment. Expert Syst Appl 2011;38:8553–62.
- [26] Kuo MS, Liang GS. A novel hybrid decision-making model for selecting locations in a fuzzy environment. Math Comput Modell 2011;54:88–104.
- [27] James G, Dolan MD. Multi-criteria clinical decision support: a primer on the use of multiple criteria decision making methods to promote evidence-based, patient-centered healthcare. Patient 2010;3(4):229–48.
- [28] Lennon E, Farr J, Besser R. Evaluation of multi-attribute decision making systems applied during the concept design of mew microplasma devices. Expert Syst Appl 2013;40(16):6321–9.
- [29] Cavus N. The application of a multi-attribute decision-making algorithm to learning management systems evaluation. Br J Educ Technol 2011;42(1):19–30.
- [30] Vaidogas ER, Sakenaite J. Multi-attribute decision-making in economics of fire protection. Eng Econ 2011;22(3):262–70.
- [31] Xia MM, Xu ZS. Hesitant fuzzy information aggregation in decision making. Int J Approx Reason 2011;52:395–407.
- [32] Yu D, Wu Y, Zhou W. Multi-criteria decision making based on choquet integral under hesitant fuzzy environment. J Comput Inf Syst 2011;7(12):4506–13.
- [33] Wei G. Hesitant fuzzy prioritized operators and their application to multiple attribute decision making. Knowl-Based Syst 2012;31:176–82.
- [34] Yu D, Wu Y, Zhou W. Generalized hesitant fuzzy Bonferroni mean and its application in multi-criteria group decision making. J Inf Comput Sci 2012;9(2):267–74.
- [35] Zhu B, Xu ZS. Hesitant fuzzy Bonferroni means for multicriteria decision making. J Oper Res Soc 2013;64(12):1831–40.
- [36] Zhu B, Xu ZS, Xia MM. Hesitant fuzzy geometric Bonferroni means. Inf Sci 2012b;205:72–85.
- [37] Xia MM, Xu ZS, Chen N. Some hesitant fuzzy aggregation operators with their application in group decision making. Group Decis Negot 2013;22(2):259–79.
- [38] Bedregal B, Reiser R, Bustince H, lopez C, Torra V. Aggregation functions for typical hesitant fuzzy elements and the action of automorphisms. Inf Sci 2014a;256(1):82–97.

- [39] Xu ZS, Xia MM. Distance and similarity measures for hesitant fuzzy sets. Inf Sci 2011b;181(11):2128-38.
- [40] Zhou, X., & Li, O. Some new similarity measures for hesitant fuzzy sets and their applications in multiple attribute decision making. Comput. Res. Repository. In press.
- Peng DH, Gao CY, Gao ZF. Generalized hesitant fuzzy synergetic weighted [41] distance measures and their application to multiple criteria decision-making. Appl Math Model 2013;37(8):5837-50.
- [42] Rathi R, Khanduja D, Sharma SK. A fuzzy-MADM based approach for prioritising six sigma projects in the indian auto sector. Int J Manage SciEng Manage 2016. doi:10.1080/17509653.2016.1154486.
- Alcantud JCR, de Andrs Calle R, Torrecillas MJM. Hesitant fuzzy worth: an in-[43] novative ranking methodology for hesitant fuzzy subsets. Appl Soft Comput 2016:38:232-43.
- [44] Thillaigovindan N, Shanthi SA, Naidu JV. A better score function for multiple criteria decision making in fuzzy environment with criteria choice under risk. Expert Syst Appl 2016;59:78-85.
- [45] Zhang YJ, Xie A, Wu YT. A hesitant fuzzy multiple attribute decision making method based on linear programming and TOPSIS. IFAC-PapersOnLine 2015:48-28:427-31
- [46] Baykasoglu A, Subulan K, Karaslan FS. A new fuzzy linear assignment method for multi-attribute decision making with an application to spare parts inventory classification. Appl Soft Comput 2016;42:1-17.
- Huang KY, Li I-H. A multi-attribute decision-making model for the robust clas-[47] sification of multiple inputs and outputs datasets with uncertainty. Appl Soft Comput 2016;38:176-89.
- [48] Rodriguez RM, Martinez L, Torra V, Xu ZS, Herrera F. Hesitant fuzzy sets: state of the art and future directions. Int J Intell Syst 2014a;29:495-524.
- [49] Farhadinia B. Information measures hesitant fuzzy sets and interval-valued hesitant fuzzy sets. Inf Sci 2013;240:129-44.
- [50] Zhou LG, Tao ZF, Chen HY, Liu JP. Intuitionistic fuzzy ordered weighted cosine similarity measure. Group Decis Negotiation 2014;23:879-900.
- [51] Zhou LG, Jin FF, Chen HY, Liu JP. Continuous intuitionistic fuzzy ordered weighted distance measure and its application to group decision making. Technol Econ Dev Economy 2016;22:75-99.

- [52] Wei\* G, Zhang N. A multiple criteria hesitant fuzzy decision making with shapley value-based VIKOR method. | Intell Fuzzy Syst 2014;26(2):1065-75.
- [53] Wei G, Zhao X, Wang H, Lin R. Hesitant fuzzy choquet integral aggregation operators and their applications to multiple attribute decision making. Information 2012;15(2):441-8.
- [54] Zhao X, Li Q, Wei G. Model for multiple attribute decision making based on the Einstein correlated information fusion with hesitant fuzzy information. Intell Fuzzy Syst 2014:26(6):3057-64.
- [55] Temur GT. A novel multi attribute decision making approach for location decision under high uncertainty. Appl Soft Comput 2016;40:674-82.
- [56] Ashtiani M, Azgomi MA. A hesitant fuzzy model of computational trust considering hesitancy, vagueness and uncertainty. Appl Soft Comput 2016;42:18-37.
- [57] Zhang N, Wei G. Extension of VIKOR method for decision making problem based on hesitant fuzzy set. Appl Math Model 2013;37:4938–47. [58] Wei G, Wang H, Zhao X, Lin R. Approaches to hesitant fuzzy multiple at-
- tribute decision making with incomplete weight information. J Intell Fuzzy Syst 2014:26(1):259-66.
- [59] Torra V. Hesitant fuzzy sets. Int J Intell Syst 2010b;25:529-39.
- [60] Rodriguez RM, Martinez L, Torra V, Xu ZS, Herrera F. Hesitant fuzzy sets: state of the art and future directions. Int J Intell Syst 2014b:29:495-524
- [61] Tan CQ, Yi WT, Chen XH. Hesitant fuzzy hamacher aggregation operators for
- multi-criteria decision making. Appl Soft Comput 2015;26:325–49. [62] Schubert J, Moradi F, Asadi H, Luotsinen L, Sjoberg E, Horling P, et al. Simulation-based decision support for evaluating operational plans. Oper Res Perspect 2015:2:36-56.
- [63] Ballesteros-Perez P, del Campo-Hitschfeld ML, Mora-Melia D, Dominguez D. Modeling bidding competitiveness and position performance in multi-attribute construction auctions. Oper Res Perspect 2015;2:24–35. [64] Lan JB, Chen YW, Ning MY, Wang ZX. A new linguistic aggregation operator
- and its application to multiple attribute decision making. Oper Res Perspect 2015:2:156-64.