

A Service of

ZBW

Leibniz-Informationszentrum Wirtschaft Leibniz Information Centre for Economics

Andersson, Tommy; Ehlers, Lars

## Working Paper An Algorithm for Identifying Agent-k-linked Allocations in Economies with Indivisibilities

Working Paper, No. 2014:35

**Provided in Cooperation with:** Department of Economics, School of Economics and Management, Lund University

*Suggested Citation:* Andersson, Tommy; Ehlers, Lars (2014) : An Algorithm for Identifying Agent-klinked Allocations in Economies with Indivisibilities, Working Paper, No. 2014:35, Lund University, School of Economics and Management, Department of Economics, Lund

This Version is available at: https://hdl.handle.net/10419/260131

#### Standard-Nutzungsbedingungen:

Die Dokumente auf EconStor dürfen zu eigenen wissenschaftlichen Zwecken und zum Privatgebrauch gespeichert und kopiert werden.

Sie dürfen die Dokumente nicht für öffentliche oder kommerzielle Zwecke vervielfältigen, öffentlich ausstellen, öffentlich zugänglich machen, vertreiben oder anderweitig nutzen.

Sofern die Verfasser die Dokumente unter Open-Content-Lizenzen (insbesondere CC-Lizenzen) zur Verfügung gestellt haben sollten, gelten abweichend von diesen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

#### Terms of use:

Documents in EconStor may be saved and copied for your personal and scholarly purposes.

You are not to copy documents for public or commercial purposes, to exhibit the documents publicly, to make them publicly available on the internet, or to distribute or otherwise use the documents in public.

If the documents have been made available under an Open Content Licence (especially Creative Commons Licences), you may exercise further usage rights as specified in the indicated licence.



# WWW.ECONSTOR.EU

Working Paper 2014:35

Department of Economics School of Economics and Management

An Algorithm for Identifying Agent-klinked Allocations in Economies with Indivisibilities

Tommy Andersson Lars Ehlers

October 2014



# An Algorithm for Identifying Agent-k-linked Allocations in Economies with Indivisibilities<sup>\*</sup>

Tommy Andersson<sup>†</sup>and Lars Ehlers<sup>‡</sup>

October 15, 2014

#### Abstract

We consider envy-free and budget-balanced rules that are least manipulable with respect to agents counting or with respect to utility gains, and observe that for any profile of quasi-linear preferences, the outcome of any such least manipulable envy-free rule can be obtained via agent-k-linked allocations. Given this observation, we provide an algorithm for identifying agent-k-linked allocations.

*JEL Classification:* C71, C78, D63, D71, D78. *Keywords:* least manipulable envy-free rules; algorithm.

### 1 Introduction

Policy makers often adopt social choice rules and matching mechanisms that are vulnerable to manipulation by strategic misrepresentation (e.g., voting rules, school choice mechanisms, and auction procedures). This has motivated researchers to identify rules and mechanisms that are "least manipulable" according to some predetermined measure. Two prominent measures are (i) counting the number of profiles at which a rule is manipulable (Maus et al., 2007a,2007b) and (ii) comparing via set inclusion the preference domains where different rules are manipulable (Pathak and Sönmez, 2013). Even though those measures are natural, Andersson et al. (2014a) demonstrated that in the context of assigning indivisible objects with monetary compensations among a set of agents, they do not distinguish envy-free and budget-balanced rules, and a "finer" measure is needed to identify least manipulable rules among envy-free and budget-balanced rules.<sup>1</sup>

<sup>\*</sup>Andersson thanks the Jan Wallander and Tom Hedelius foundation, and Ragnar Söderbergs Stiftelse for financial support. Ehlers thanks FQRSC (Québec) and SSHRC (Canada) for financial support.

 $<sup>^\</sup>dagger Department$  of Economics, Lund University, Box 7082, SE-220 07 Lund, Sweden; E-mail: tommy.andersson@nek.lu.se.

<sup>&</sup>lt;sup>‡</sup>Département de Sciences Économiques and CIREQ, Université de Montréal, C.P. 6128, Succursale Centre-Ville, Montréal, Québec H3C 3J7, Canada; e-mail: lars.ehlers@umontreal.ca (Corresponding author).

<sup>&</sup>lt;sup>1</sup>For more on envy-free solutions, see, e.g., Alkan et al. (1991), Aragones (1995), Foley (1967), Tadenuma and Thomson (1991,1993,1995a,1995b), and Svensson (1983).

In Andersson et al. (2014a), rule  $\varphi$  is judged to be more manipulable with respect to agents counting than rule  $\psi$  if, for each preference profile, the number of agents that can manipulate  $\varphi$  is larger than or equal to the number of agents that can manipulable  $\psi$ . Andersson et al. (2014b) and Fujinaka and Wakayama (2012) considered a different approach and calculated the maximal amount by which an agent can gain from manipulating a given rule. In this case, rule  $\varphi$  is defined to be more manipulable with respect to utility gains than rule  $\psi$  if, for each preference profile, the maximal gain that any agent can obtain by manipulating  $\varphi$  is weakly larger than the maximal gain that any agent can obtain by manipulating  $\psi$ . Even though these two finer measures appear to be quite different, they share one important feature. Namely, as observed in this paper, for any given preference profile, the outcome of least manipulable envy-free rules can be identified via agent-k-linked allocations. Here, an allocation is agent-k-linked if for each agent *i*, there is a sequence of agents from *i* to *k* such that any agent in the sequence is indifferent between his consumption bundle and the consumption bundle of the next agent in the sequence.

Even if agent-k-linked allocations have played a central role in other contexts than the above mentioned (see, e.g., Alkan et al., 1991; Velez, 2011; Fujinaka and Wakayama, 2012; Tadenuma and Thomson, 1995a, 1995b), an algorithm for identifying these allocations is missing in the literature. The main contribution of this paper is to provide an algorithm for identifying envy-free and budget-balanced agent-k-linked allocations under quasi-linear preferences.

The remaining part of the paper is organized as follows. Section 2 presents the model and some basic definitions. In Section 3, the two least manipulable envy-free and budgetbalanced rules from Andersson et al. (2014a,2014b) are introduced and it is carefully explained why agent-k-linked allocations are important for identifying the outcome of these rules. Section 4 provides the algorithm and the main convergence theorem.

### 2 The Model and Basic Definitions

Let  $N = \{1, \ldots, n\}$  and  $M = \{1, \ldots, m\}$  denote the sets of agents and objects, respectively, with |N| = |M|. Each agent  $i \in N$  consumes one bundle  $(j, x_j) \in M \times \mathbb{R}$  containing one object  $j \in M$  and some amount of money  $x_j \in \mathbb{R}$ . For each  $i \in N$ , *i*'s preferences over bundles  $(j, x_j)$  are represented by a quasi-linear utility function  $u_i$  where

$$u_i(j, x_j) = v_{ij} + x_j$$
 for some  $v_{ij} \in \mathbb{R}$ .

A list of utility functions  $u = (u_1, \ldots, u_n)$  is a (preference) profile. Let  $\mathcal{U}$  denote the set of profiles.

An allocation (a, x) is a list of |N| bundles where  $a : N \to M$  assigns object  $a_i$  to  $i \in N$ and  $x : M \to \mathbb{R}$  assigns monetary compensation  $x_j$  to  $j \in M$ . An allocation (a, x) is *feasible* if  $a_i \neq a_j$  whenever  $i \neq j$  for  $i, j \in N$ , and  $\sum_{j \in M} x_j \leq \alpha$  for some  $\alpha \in \mathbb{R}_+$ . If  $\sum_{j \in M} x_j = \alpha$ , allocation (a, x) is *budget-balanced*. Let  $\mathcal{A}$  denote the set of feasible and budget-balanced allocations. For convenience, we write "allocation" instead of "feasible allocation satisfying budget-balance". At profile  $u \in \mathcal{U}$ , allocation (a, x) is *envy-free* if  $u_i(a_i, x_{a_i}) \ge u_i(a_j, x_{a_j})$  for all  $i, j \in N$ . Let  $\mathcal{F}(u)$  denote the set of envy-free allocations at profile  $u \in \mathcal{U}$ .

A rule is a non-empty correspondence  $\varphi$  choosing for each  $u \in \mathcal{U}$  a non-empty set of allocations  $\varphi(u)$  such that  $u_i(a_i, x_{a_i}) = u_i(b_i, y_{b_i})$  for all  $i \in N$  and all  $(a, x), (b, y) \in \varphi(u)$ . A rule  $\varphi$  is envy-free if  $\varphi(u) \subseteq \mathcal{F}(u)$  for each  $u \in \mathcal{U}$ . Given  $u \in \mathcal{U}$ , a rule  $\varphi$  is manipulable at u by agent  $i \in N$  if there exists  $(\hat{u}_i, u_{-i}) \in \mathcal{U}$  and two allocations  $(a, x) \in \varphi(u)$  and  $(b, y) \in \varphi(\hat{u}_i, u_{-i})$  such that  $u_i(b_i, y_{b_i}) > u_i(a_i, x_{a_i})$ . If rule  $\varphi$  is not manipulable by any agent at u, then  $\varphi$  is non-manipulable at u.

We use the following concepts for describing indifference relations at any allocation (Andersson et al., 2014a).

**Definition 1.** Let  $(a, x) \in \mathcal{A}$  and  $u \in \mathcal{U}$ .

- (i) For any  $i, j \in N$ , we write  $i \rightarrow_{(a,x)} j$  if  $u_i(a_i, x_{a_i}) = u_i(a_j, x_{a_i})$ ,
- (ii) An *indifference chain* at (a, x) consists of a tuple of distinct agents  $g = (i_0, \ldots, i_k)$  such that  $i_0 \rightarrow_{(a,x)} \cdots \rightarrow_{(a,x)} i_k$ ,
- (iii) Agent  $i \in N$  is *linked* to agent  $k \in N$  at (a, x) if there exists an indifference chain  $(i_0, \ldots, i_t)$  at (a, x) with  $i = i_0$  and  $i_t = k$ ,
- (iv) Allocation (a, x) is agent-k-linked if each agent  $i \in N$  is linked to agent  $k \in N$ .

**Definition 2.** Let  $(a, x) \in \mathcal{A}$ . An *indifference component* at (a, x) is a non-empty set  $G \subseteq N$  such that for all  $i, k \in G$  there exists an indifference chain at (a, x) in G, say  $g = (i_0, ..., i_k)$  with  $\{i_0, ..., i_k\} \subseteq G$ , such that  $i = i_0$  and  $i_k = k$ , and there exists no  $G' \supseteq G$  satisfying the previous property at (a, x).

**Lemma 1** (Svensson, 2009). Let  $u \in \mathcal{U}$ . If  $(a, x), (b, y) \in \mathcal{F}(u)$ , then  $(a, y), (b, x) \in \mathcal{F}(u)$ .

## 3 Least Manipulable Envy-Free Rules

Note the following two facts for any  $k \in N$  and any  $u \in \mathcal{U}^2$ ,

- (1) there exist allocations in  $\mathcal{F}(u)$  maximizing k's utility in  $\mathcal{F}(u)$ . Such allocations will be called agent-k-preferred. Moreover,  $(a^*, x^*) \in \mathcal{F}(u)$  is agent-k-linked if and only if  $(a^*, x^*)$  maximizes agent k's utility in  $\mathcal{F}(u)$ ;
- (2) for any envy-free rule  $\varphi$ , there exists  $(\hat{u}_i, u_{-i}) \in \mathcal{U}$  such that some  $(a^*, x^*) \in \varphi(\hat{u}_i, u_{-i})$  is agent-k-linked (under u).

<sup>&</sup>lt;sup>2</sup>The first part of Fact (1) is from Alkan et al. (1991), and the second part of Fact (1) as well as Fact (2) are from Andersson et al. (2014a).

Given a rule  $\varphi$  and  $u \in \mathcal{U}$ , let  $P^{\varphi}(u)$  denote the set of agents who can manipulate  $\varphi$  at u. Rule  $\varphi$  is non-manipulable at u if

$$|P^{\varphi}(u)| = 0. \tag{1}$$

Because condition (1) is never satisfied for all profiles by envy-free and budget-balanced rules (Green and Laffont, 1979), one approach is to search for rules where  $|P^{\varphi}(u)|$  is minimized for each profile u.

**Definition 3.** Envy-free rule  $\varphi$  is least manipulable with respect to agents counting if for any envy-free rule  $\psi$ , we have  $|P^{\varphi}(u)| \leq |P^{\psi}(u)|$  for all  $u \in \mathcal{U}$ .

Andersson et al. (2014a) show the following: first, by their Lemma 4, the set of indifference components is invariant for any two envy-free allocations; and second, agent kcannot manipulate an envy-free rule iff all allocations chosen by the rule are agent-k-linked (or equivalently, agent-k-preferred). An immediate consequence is now Andersson et al. (2014a, Theorem 3) which states that the least manipulable envy-free rules with respect to agents counting are exactly "maximally preferred" envy-free rules: for each profile uwe choose some agent k belonging to an indifference component with maximal cardinality and then a non-empty subset of agent-k-linked allocations. Note that such allocations are agent-i-linked for any agent i belonging to the same indifference component as agent k. Hence, to identify the outcome of a least manipulable envy-free rule with respect to agents counting, envy-free agent-k-linked allocations must be identified (and then indifference components with maximal cardinality may be found). Here it suffices to identify one agent-k-linked allocation for each  $k \in N$ .

Andersson et al. (2014b) and Fujinaka and Wakayama (2012) determine the maximal utility gain which each agent can obtain by manipulating an envy-free rule. For any  $u \in \mathcal{U}$  and any  $(a, x) \in \varphi(u)$ , let

$$f_k(\varphi, u) = \sup_{(\hat{u}_k, u_{-k}) \in \mathcal{U}} \max_{(b, y) \in \varphi(\hat{u}_k, u_{-k})} u_k(b_k, y_{b_k}) - u_k(a_k, x_{a_k})$$

denote agent k's maximal gain from manipulating  $\varphi$  at u.

Let  $\varphi$  be an envy-free rule,  $u \in \mathcal{U}$ ,  $k \in N$ , and  $(a, x) \in \varphi(u)$ . By Fact (1) there exist agent-k-linked  $(a^*, x^*) \in \mathcal{F}(u)$ . By Lemma 1, now  $(a, x^*) \in \mathcal{F}(u)$  and, by envy-freeness,  $u_k(a_k, x_{a_k}^*) = u_k(a_k^*, x_{a_k}^*)$  implying that  $(a, x^*)$  is agent-k-linked. Observing Fact (2), Andersson et al. (2014b, Theorem 2) under quasi-linearity implies

$$f_k(\varphi, u) = v_{ka_k} + x_{a_k}^* - (v_{ka_k} + x_{a_k}) = x_{a_k}^* - x_{a_k}.$$
(2)

Hence,  $f_k(\varphi, u)$  represents the maximal amount of money that agent k can obtain by manipulating  $\varphi$  at u.

**Definition 4.** Envy-free rule  $\varphi$  is least manipulable with respect to utility gains if for any envy-free rule  $\psi$ , we have  $\max_{i \in N} f_i(\varphi, u) \leq \max_{i \in N} f_i(\psi, u)$  for all  $u \in \mathcal{U}$ .

Andersson et al. (2014b, Theorem 5) show that (a) there exist least manipulable envy-free rules  $\varphi$  with respect to utility gains, (b) any such  $\varphi$  satisfies  $f_i(\varphi, u) = f_j(\varphi, u)$  for all

 $i, j \in N$  and all  $u \in \mathcal{U}$ , and (c) the allocations chosen by any such  $\varphi$  can be identified via agent-k-linked allocations for any profile u. More explicitly, given  $u \in \mathcal{U}$  start by identifying one agent-k-linked allocation in  $\mathcal{F}(u)$ , say  $(a^k, x^k)$ , for any  $k \in N$ . Using Lemma 1 and the above argument, we may suppose that  $a^1 = \cdots = a^n \equiv a$  (and  $(a, x^k) \in \mathcal{F}(u)$  is the above argument, we may suppose that  $a = \dots - a = a$  (and  $(a, x) \in \mathcal{F}(a)$  is agent-k-linked). By condition (2), for all  $k \in N$ ,  $x_{a_k}^k \ge x_{a_k}$  (where  $(a, x) \in \mathcal{F}(u)$ ), and  $\sum_{k \in N} x_{a_k}^k \ge \alpha$ . Thus, the compensations  $(x_{a_1}^1, \dots, x_{a_n}^n)$  need to be reduced by  $\beta \ge 0$  in order to satisfy budget-balance, i.e., we choose  $\beta \ge 0$  such that  $\sum_{k \in N} (x_{a_k}^k - \beta) = \alpha$ . Andersson et al. (2014b, Theorem 5) show that the allocation  $(a, (x_{a_k}^k - \beta)_{k \in N})$  is envy-free. Now obviously, for profile u, any envy-free rule  $\varphi$  choosing  $(a, (x_{a_k}^k - \beta)_{k \in N})$  satisfies by condition (2),  $f(\alpha, u) = \beta - f(\alpha, u)$  for all  $i, j \in N$ . Hence, the outcome of a by condition (2),  $f_i(\varphi, u) = \beta = f_i(\varphi, u)$  for all  $i, j \in N$ . Hence, the outcome of a least manipulable rule with respect to utility gains may be found via identifying envy-free agent-k-linked allocations. Again, it suffices to identify one agent-k-linked allocation for each  $k \in N$ .

#### Identification of Agent-k-linked Allocations 4

Fix  $u \in \mathcal{U}$  and  $k \in N$ . Similarly to Aragones (1995), our algorithm starts with an arbitrary envy-free allocation, say  $(a, x) \in \mathcal{F}(u)$ . This assumption is not restrictive since such allocations can be easily found in polynomial time (Klijn, 2000; Haake et al., 2003). In every step of the algorithm we keep the object assignment a fixed.

**Definition 5.** A group of agents  $C \subsetneq N$  is *isolated* at (a, x) if  $i \not\rightarrow_{(a,x)} j$  for all  $i \in N \setminus C$ and all  $j \in C$ .

An allocation cannot be agent-k-linked if agent k belongs to an isolated group  $C \subsetneq N$ because then at least one agent is not linked to agent k. The termination criterion for our algorithm will be the non-existence of an isolated group containing agent k.

Algorithm 1. Let  $(a, x) \in \mathcal{F}(u)$  and set  $K^0 = \{k\}$ . For each iteration  $t = 1, \ldots$ :

Step t. Define  $K^t \equiv K^{t-1} \cup \{i \in N \setminus K^{t-1} \mid i \to_{(a,x)} j \text{ for some } j \in K^{t-1}\}$ . If  $K^t = K^{t-1}$ , then stop. Otherwise, continue with Step t + 1.

**Lemma 2.** Algorithm 1 identifies an isolated group containing agent k in at most |N|iterations.

Proof. Let Algorithm 1 terminate at Step T. If  $K^T \neq N$ , then  $i \not\rightarrow_{(a,x)} j$  for all  $i \in N \setminus K^T$ and all  $j \in K^T$  by construction. Thus,  $K^T$  is isolated and  $k \in K^T$  since  $\{k\} = K^0 \subseteq K^T$ . Furthermore, note that  $|K^t| - |K^{t-1}| \geq 1$  for all  $t \in \{1, \ldots, T-1\}$ , and Algorithm 1

terminates in at most |N| iterations. 

Algorithm 2. Let  $(a, x) \in \mathcal{F}(u)$  and set  $K^0 = \{k\}$  and  $x^0 = x$ . Let  $x^t$  denote the compensations determined in iteration t. For each iteration  $t = 1, \ldots$ :

Step t. Run Algorithm 1 for  $(a, x^{t-1})$  and let  $N^t$  denote the output of Algorithm 1. If  $N \setminus N^t = \emptyset$ , then stop (with output  $(a, x^{t-1})$ ). Otherwise, let  $\lambda_{ij}^t \equiv u_i(a_i, x_{a_i}^{t-1}) - u_i(a_j, x_{a_j}^{t-1})$  for each  $i \in N \setminus N^t$  and each  $j \in N^t$ . Set  $\lambda^t \equiv \min_{i \in N \setminus N^t, j \in N^t} \lambda_{ij}^t$ , and define  $x^t$  by

$$\begin{aligned} x_{a_i}^t &\equiv x_{a_i}^{t-1} - \frac{|N^t|}{|N|} \cdot \lambda^t \text{ for each } i \in N \setminus N^t, \\ x_{a_j}^t &\equiv x_{a_j}^{t-1} + \frac{|N \setminus N^t|}{|N|} \cdot \lambda^t \text{ for each } j \in N^t, \end{aligned}$$

and continue to Step t + 1.

**Theorem 1.** Algorithm 2 identifies an agent-k-linked envy-free allocation in at most |N| iterations.

*Proof.* Note that the adjustment of compensations in Step t from  $x^{t-1}$  to  $x^t$  respects budget-balance because  $(a, x^0)$  is budget-balanced, and by induction, if  $(a, x^{t-1})$  is budget-balanced, then

$$\sum_{i \in N} x_{a_i}^t = \sum_{i \in N} x_{a_i}^{t-1} - \frac{|N^t|}{|N|} \cdot \lambda^t \cdot |N \setminus N^t| + \frac{|N \setminus N^t|}{|N|} \cdot \lambda^t \cdot |N^t| = \sum_{i \in N} x_{a_i}^{t-1} = \alpha.$$

Note that  $(a, x^0) \in \mathcal{F}(u)$ . By induction, we show that if  $(a, x^{t-1}) \in \mathcal{F}(u)$ , then  $(a, x^t) \in \mathcal{F}(u)$ . Equivalently, we show for all  $i, j \in N$ ,

if 
$$u_i(a_i, x_{a_i}^{t-1}) \ge u_i(a_j, x_{a_j}^{t-1})$$
, then  $u_i(a_i, x_{a_i}^t) \ge u_i(a_j, x_{a_j}^t)$ . (3)

If  $i, j \in N^t$  or  $i, j \in N \setminus N^t$ , then condition (3) is true because  $(a, x^{t-1}) \in \mathcal{F}(u)$  and the adjustments of  $x_{a_i}^{t-1}$  and  $x_{a_j}^{t-1}$  are identical. If  $i \in N^t$  and  $j \in N \setminus N^t$ , then condition (3) is true because  $(a, x^{t-1}) \in \mathcal{F}(u)$  and  $x_{a_i}^{t-1}$  is increased and  $x_{a_j}^{t-1}$  is decreased. If  $i \in N \setminus N^t$  and  $j \in N^t$ , then condition (3) is true because  $(a, x^{t-1}) \in \mathcal{F}(u)$  and  $x_{a_i}^{t-1}$  is increased and  $x_{a_j}^{t-1}$  is decreased. If  $i \in N \setminus N^t$  and  $j \in N^t$ , then condition (3) is true because  $(a, x^{t-1}) \in \mathcal{F}(u)$  and by definition of  $\lambda^t$ ,  $\lambda^t \leq \lambda_{ij}^t = u_i(a_i, x_{a_i}^{t-1}) - u_i(a_j, x_{a_j}^{t-1})$ , i.e.,

$$\begin{aligned} u_i(a_i, x_{a_i}^t) &= v_{ia_i} + x_{a_i}^t = v_{ia_i} + x_{a_i}^{t-1} - \frac{|N^t|}{|N|} \cdot \lambda^t \ge v_{ia_i} + x_{a_i}^{t-1} - \frac{|N^t|}{|N|} \cdot \lambda_{ij}^t = \\ &= u_i(a_i, (x_{a_i}^{t-1}) - \lambda_{ij}^t + \frac{|N \setminus N^t|}{|N|} \cdot \lambda_{ij}^t = u_i(a_j, x_{a_j}^{t-1}) + \frac{|N \setminus N^t|}{|N|} \cdot \lambda_{ij}^t \\ &\ge v_{ia_j} + x_{a_j}^{t-1} + \frac{|N \setminus N^t|}{|N|} \cdot \lambda^t = v_{ia_j} + x_{a_j}^t = u_i(a_j, x_{a_j}^t). \end{aligned}$$

Because  $(a, x^0) = (a, x) \in \mathcal{F}(u)$ , now condition (3) yields  $(a, x^t) \in \mathcal{F}(u)$ .

Finally, we show that Algorithm 2 terminates in at most |N| iterations. By construction of  $N^t$ , each agent  $i \in N^t$  must belong to an indifference chain  $g = (i, \ldots, k)$  at  $(a, x^{t-1})$ . Note that at Step t, for  $i \in N \setminus N^t$  and  $j \in N^t$  such that  $\lambda_{ij}^t = \lambda^t$ , all the above inequalities become equalities and we obtain  $u_i(a_i, x_{a_i}^t) = u_i(a_j, x_{a_j}^t)$ ,  $i \to_{(a,x^t)} j$  and  $i \in N^{t+1}$ . Note that  $N^t \subseteq N^{t+1}$  because for any  $i, j \in N^t$  such that  $i \to_{(a,x^{t-1})} j$ , the adjustments of  $x_{a_i}^{t-1}$ and  $x_{a_j}^{t-1}$  are identical and we also have  $i \to_{(a,x^t)} j$ . Thus,  $|N^{t+1}| - |N^t| \ge 1$  as long as  $N \setminus N^t \neq \emptyset$ . Hence, Algorithm 2 terminates in at most |N| iterations.

#### References

- Alkan, A., Demange, G., Gale, D., 1991. Fair allocation of indivisible objects and criteria of justice. Econometrica 59, 1023–1039.
- Andersson, T., Ehlers, L., Svensson, L.-G., 2014a. Budget-Balance, Fairness and Minimal Manipulability. Theoretical Econ. 9, 753–777.
- Andersson, T., Ehlers, L., Svensson, L.-G., 2014b. Least Manipulable Envy-free Rules in Economies with Indivisibilities. Math. Soc. Sci. 69, 43–49.
- Aragones, E., 1995. A derivation of the money Rawlsian solution. Soc. Choice Welfare 12, 267–276.
- Foley, D., 1967. Resource allocation and the public sector. Yale Econ. Essays 7, 45-98.
- Fujinaka, Y., T. Wakayama, 2012. Maximal Manipulation in Fair Allocation, Working Paper.
- Green, J., Laffont, J.-J., 1979. Incentives in Public Decision Making. North-Holland: Amsterdam.
- Haake, C.-J., Raith, M., Su, F., 2003. Bidding for envy-freeness: a procedural approach to n-player fair division problems. Soc. Choice Welfare 19, 723–749.
- Klijn, F., 2000. An algorithm for envy-free allocations in an economy with indivisible objects and money. Soc. Choice Welfare 17, 201–216.
- Maus, S., Peters, H., Storcken, T., 2007a. Minimal manipulability: anonymity and unanimity. Soc. Choice Welfare 29, 247–269.
- Maus, S., Peters, H., Storcken, T., 2007b. Anonymous voting and minimal manipulability. J. Econ. Theory 135, 533–544.
- Pathak, P.A., Sönmez, T., 2013. School Admissions Reform in Chicago and England: Comparing Mechanisms by their Vulnerability to Manipulation. Amer. Econ. Rev. 103, 80–106.
- Svensson, L.–G., 1983. Large indivisibles: an analysis with respect to price equilibrium and fairness. Econometrica 51, 939-954.
- Svensson, L.-G., 2009. Coalitional strategy-proofness and fairness, Econ. Theory 40, 227–245.
- Tadenuma, K., Thomson, W., 1991. No envy and consistency in economies with indivisible goods. Econometrica 59, 1755-1767.
- Tadenuma, K., Thomson, W., 1993. The fair allocation of an indivisible good when monetary compensations are possible. Math. Soc. Sci. 25, 117-132.
- Tadenuma, K., Thomson, W., 1995a. Refinements of the no-envy solution in economies with indivisible goods. Theory and Decision 39, 189-206.
- Tadenuma, K., Thomson, W., 1995b. Games of fair division. Games Econom. Behav. 9, 191-204.

Velez, R.A., 2011. Are incentives against economic justice? J. Econ. Theory 146, 326–345.