ECONSTOR Make Your Publications Visible.

A Service of

ZBW

Leibniz-Informationszentrum Wirtschaft Leibniz Information Centre for Economics

Sutopo, Wahyudi et al.

Article

Open innovation in developing an early standardization of battery swapping according to the Indonesian national standard for electric motorcycle applications

Journal of Open Innovation: Technology, Market, and Complexity

Provided in Cooperation with:

Society of Open Innovation: Technology, Market, and Complexity (SOItmC)

Suggested Citation: Sutopo, Wahyudi et al. (2022) : Open innovation in developing an early standardization of battery swapping according to the Indonesian national standard for electric motorcycle applications, Journal of Open Innovation: Technology, Market, and Complexity, ISSN 2199-8531, MDPI, Basel, Vol. 8, Iss. 4, pp. 1-23, https://doi.org/10.3390/joitmc8040219

This Version is available at: https://hdl.handle.net/10419/274520

Standard-Nutzungsbedingungen:

Die Dokumente auf EconStor dürfen zu eigenen wissenschaftlichen Zwecken und zum Privatgebrauch gespeichert und kopiert werden.

Sie dürfen die Dokumente nicht für öffentliche oder kommerzielle Zwecke vervielfältigen, öffentlich ausstellen, öffentlich zugänglich machen, vertreiben oder anderweitig nutzen.

Sofern die Verfasser die Dokumente unter Open-Content-Lizenzen (insbesondere CC-Lizenzen) zur Verfügung gestellt haben sollten, gelten abweichend von diesen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.



https://creativecommons.org/licenses/by/4.0/

Terms of use:

Documents in EconStor may be saved and copied for your personal and scholarly purposes.

You are not to copy documents for public or commercial purposes, to exhibit the documents publicly, to make them publicly available on the internet, or to distribute or otherwise use the documents in public.

If the documents have been made available under an Open Content Licence (especially Creative Commons Licences), you may exercise further usage rights as specified in the indicated licence.



WWW.ECONSTOR.EU





Article Open Innovation in Developing an Early Standardization of Battery Swapping According to the Indonesian National Standard for Electric Motorcycle Applications

Wahyudi Sutopo ^{1,*}, Dana Prianjani ², Fakhrina Fahma ³, Eko Pujiyanto ², Amran Rasli ⁴ and Tan Owee Kowang ⁵

- ¹ University Centre of Excellence for Electrical Energy Storage Technology, Universitas Sebelas Maret, Surakarta 57126, Indonesia
- ² Master Program of Industrial Engineering Department, Faculty of Engineering, Universitas Sebelas Maret, Surakarta 57126, Indonesia
- ³ Research Group Industrial Engineering and Techno-Economic, Department of Industrial Engineering, Faculty of Engineering, Universitas Sebelas Maret, Surakarta 57126, Indonesia
- ⁴ Faculty of Business and Management, Inti International University, Nilai 71800, Malaysia
- ⁵ Azman Hashim International Business School, Universiti Teknologi Malaysia, Johor Bahru 81310, Malaysia
- Correspondence: wahyudisutopo@staff.uns.ac.id

Abstract: This research aims to achieve early standardization for battery swapping in line with domestic capabilities and global standards, and to protect Indonesian battery swap stakeholders. By distributing questionnaires to 190 respondents, the Framework for Analysis, Comparison, and Testing of Standards (FACTS) approach was used to analyze stakeholder needs, compare global standards regarding battery swaps, and validate the Indonesian National Standard (SNI) framework. An open innovation approach was considered to integrate a FACTS approach with open participation, mutual understanding, and consensus to generate parameters. Therefore, characteristics of open participation, mutual understanding, and consensus were identified using FACTS to catalyze market needs as well as stakeholder needs. The relationship between SNI implementation variables, national uniqueness, and stakeholder needs was predicted using structural equation modeling (SEM). We found that the proposed constructs—i.e., electromagnetic compatibility, equipment construction requirements, marking and instruction, and protection against electric shock—positively affect SNI implementation. Meanwhile, the SNI implementation, national uniqueness, and stakeholder protection positively affect SNI acceptance. Therefore, SNI acceptance can be obtained by considering SNI implementation, national uniqueness, and stakeholder protection. The findings of this study can be used to develop an SNI battery swap test that is globally competitive, has national characteristics, and considers domestic capabilities when developing the SNI documentation.

Keywords: battery swap; early standardization; FACTS; global competitiveness; open innovation; SEM

1. Introduction

Motorcycles are oil-fueled motor vehicles with the highest use percentage among Indonesian citizens from an economic standpoint [1]. There is a sufficiently strong potential to convert from oil-fueled motorcycles to electric motorcycles in Indonesia because of the high number of motorcycle enthusiasts. Activities to immediately implement electric vehicle programs in Indonesia are supported by political, economic, technological, and social factors [2]. The Indonesian government has issued regulations for accelerating batterybased electric motor vehicle programs for road transportation. The government attempts to provide a foundation, direction, and legal certainty to encourage energy conservation in the transportation sector. As a result, this demonstrates the country's readiness to accelerate the transition from fossil-fueled to electric vehicles [3].



Citation: Sutopo, W.; Prianjani, D.; Fahma, F.; Pujiyanto, E.; Rasli, A.; Kowang, T.O. Open Innovation in Developing an Early Standardization of Battery Swapping According to the Indonesian National Standard for Electric Motorcycle Applications. *J. Open Innov. Technol. Mark. Complex.* **2022**, *8*, 219. https://doi.org/ 10.3390/joitmc8040219

Received: 6 November 2022 Accepted: 13 December 2022 Published: 15 December 2022

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2022 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https:// creativecommons.org/licenses/by/ 4.0/). Battery swapping, also known as battery-as-a-service, allows electric vehicles' owners to exchange discharged batteries for charged ones at swapping stations. Battery swapping, like most commodities, has its own supply chain system, from suppliers, orders, mass production, distribution, marketing, and service, to consumers [2]. However, battery swap testing standards must be developed before the technology can be mass-produced and used as a driving force for electric motorcycles. The early supply chain of the battery swap—i.e., the product development stage, which includes planning, design, development, and pre-production—must be considered in the development of standardization [4]. As the supervisor, developer, and coordinator of activities in the field of standardization, the national standardization body has authority over the process of developing these standards [5]. Each process of developing battery swap products—including planning, design, development, and pre-production—must follow the standard development process, which includes the formulation and setting of standard activities.

Every use of a particular product must focus on consumer protection [6]. Consumer protection is required by the law to support the conversion of oil-fueled motorcycles to electric motorcycles. A standard can be used to provide such protection. Due to the unavailability of an Indonesian National Standard for battery swap product safety and performance, battery swap research for national electric motorcycles may lack a minimum level of quality and reference. As a result, product test standards must be used as a reference. Consumers can be assured that their products are appropriate in terms of performance, safety, and production by using product test standard processes in certifications or product standard labels [6]. Furthermore, Indonesia's diverse natural conditions and its citizens' distinct habits necessitate national uniqueness.

In Indonesia, battery swapping is a new technology with broad applicability. Over time, the lifecycle of a new technology may be more or less similar to that of other innovations. Depending on the technology's market adoption, it may or may not follow the diffusion of innovation [7]. In this case, knowing when and how to apply standards successfully requires understanding of the battery swap lifecycle. A new technology's lifecycle is divided into four stages: invention, growth, maturity, and decline [8]. The invention phase is when the technology is first developed. It has a slow initial growth rate as experiments, research, and development on battery swaps and electric vehicles are carried out during this phase [9–14]. The second phase, known as the growth phase, is characterized by steady and rapid growth as the technology improves. This phenomenon occurs when the battery swap technology is widely used and developed [15–20]. At the maturity phase, the technology is mature, relatively stable, and has competitive implementations in the market. This phase is critical, as the compatibility of the technology is of high priority, and there would be a loss in market share unless compatibility is embraced [7]. The real challenge is to bring battery swap technology to market and keep it from dying in the valley of death. As a result, strategies for accelerating the commercialization of this new technology are required [21]. Therefore, it is necessary to introduce standards during the maturity phase to strengthen the technological innovation to cross the valley of death, emerge in the market, and avoid being trapped in the decline phase.

This study employed the FACTS approach, which can be applied to develop and implement standards as per the recommendations of the National Institute of Standards and Technology [22]. Various standards—such as battery cell standards, battery modules, battery management, and battery-powered wheelchairs—have been developed [23–26]. Standardization and open innovation have similar characteristics [27].

Open innovation is a topic of innovation that is increasingly being discussed. Open innovation refers to the process carried out by companies to find new technologies, innovations, research, and products externally [28]. The aim of open innovation is to tap into the R&D community, even outside the industry, in order to align the pace of internal research and innovation with external developments. Open innovation is a systematic approach to innovation management that exploits internal advantages and capabilities while inte-

grating external opportunities and sources from industry, government, universities, and society [29].

The open innovation approach was considered to integrate a FACTS approach through the interaction of inbound and outbound processes. Thus, the knowledge, experience, and needs of stakeholders can be captured in deliverable standards. In developing standards, the FACTS approach considers all relevant stakeholders' interests that represent transparency and open participation. As a result, the consensus principle in standardization allows interested parties to express their viewpoints and be accommodated accordingly.

This paper outlines a comprehensive strategy for establishing an early standardization for battery swaps in electric motorcycle applications. This research aims to develop an SNI for battery swap testing that is globally competitive, has a national character, and is within domestic capabilities using FACTS and SEM methods. The FACTS method was employed to create a globally competitive standard framework for battery swapping, while the SEM method was applied to determine which construct models can support acceptance of standard implementation so that battery swap stakeholders in Indonesia can implement the standard.

2. Literature Review

2.1. FACTS and SEM Approach

The FACTS method has been used to develop various other standards, such as for battery cells, battery modules, battery management, and wheelchairs [23–26]. The FACTS approach considers the interests of all relevant stakeholders; this approach also provides a framework for analyzing, comparing, and testing standards by structuring information through the Zachman framework. The Zachman framework is used to obtain information using the 5W1H questions (Who? What? When? Where? Why? How?). However, the FACTS method cannot determine which indicators or constructs should be the priority to be included in the standard. As a result, the SEM approach is applied to determine the relationships between constructs and indicators to identify which construct models support the adoption of standards early in the commercialization process.

SEM is a multivariate statistical technique that combines factor analysis and regression analysis to investigate the relationships between variables in a model, either between indicators and their constructs or between the constructs themselves [30,31]. Latent variables are also known as unobserved variables, constructs, and latent constructs. Manifest variables are also known as observed, measured, and indicators. SEM combines two statistical methods: psychological factor analysis and simultaneous equation modeling developed in econometrics [32].

There have been many studies using the SEM method. SEM is a powerful tool that has been utilized to explore the public acceptance, especially towards environmental sustainability [33–35]. Previous studies have also researched the acceptance and purchase of electric vehicles using the SEM method [36,37]. Other research on the development of the TAM model as an indicator of electric taxi acceptance can also be carried out using SEM [38]. Table 1 shows the position of this research compared to the existing literature.

Authors	Study Object	Number of Constructs	Number of Indicators	FACTS	SEM
Prianjani et al. [25]	LiFEPO ₄ battery cell standard	3	15	\checkmark	-
Aristyawati et al. [23]	LiFEPO ₄ battery module standard	6	-	\checkmark	-
Rahmawatie et al. [26]	LIFEPO ₄ battery management system standard	4	14	\checkmark	-
Pratiwi et al. [24]	Manual wheelchair standard	7	-	\checkmark	-
Nosi et al. [37]	The intensity of e-car purchases by millennials	6	34	-	\checkmark
Prianjani et al. [39] Conceptual model framework standardization and testing battery swapping in Indonesia		4	-	\checkmark	-
Wang et al. [40]	Public acceptance of electric vehicles	12	43	-	\checkmark
Globisch et al. [38]	Using the TAM model as an SEM indicator of electric taxi acceptance	11	-	-	\checkmark
Zhao et al. [41]	Consumers' acceptance of electric vehicles	6	27	-	\checkmark
Adu-Gyamfi et al. [42]	Investigating the adoption intention for battery swap technology for electric vehicles	7	27	-	\checkmark
Gulzari et al. [43]	A young consumer electric vehicle rental behavioral model	7	27	-	\checkmark
This study	Development of battery swap testing standards using FACTS and SEM methods	7	58	\checkmark	\checkmark

Table 1. State of the art of this study's field.

2.2. Open Innovation Dynamics

Innovation is one of the important elements that drive the success, sustainability, and competitive advantage of a company. Various innovation models continue to be developed to make it easier for companies to innovate, such as the open innovation model. The dynamics of open innovation continue to evolve over time. There have been many studies on models that can be applied to manage product development in the context of open innovation.

The main key to the success of open innovation is choosing the right partners so that economic performance and sustainability performance of innovation can be met simultaneously [44]. In addition, an effective open strategy can be implemented to achieve the desired competitive advantage from innovation management activities [45]. In open innovation, there are roles for government, industry, society, and universities in the innovation ecosystem to form dynamic micro-relationships that can then evolve into macro dynamics [46]. Furthermore, Yun et al. [47] explored the role of culture in driving the dynamics of open innovation, where open innovation is influenced by three-dimensional interactions, namely, entrepreneurship, intrapreneurship, and organizational entrepreneurship. There is a correlation between the types of networks that lead to collaboration and the types of innovation activities pursued and innovation outcomes realized [48].

Universities, which in this study are parties that actively carry out product research and development, have a large impact as a result of their engagement in open innovation. The administration of a university can target open innovation interactions and foster the emergence of specific university–industry relationships by providing professional assistance [49]. Universities can serve as a reliable intermediary to facilitate collaboration between multiple parties in a secure environment [50,51].

Innovation capabilities and market outcomes from open innovation depend on the strategy implemented. This can affect changes in the innovation efficiency curves resulting from the use of open innovation business models. Open innovation strategies appear in a variety of ways; hence, their effects are similarly diverse [52]. Therefore, strategic management of open innovation is vital for addressing dynamic capabilities as they relate to the right time to use open innovation. Thus, the positive and constraining aspects of open innovation in various circumstances can be identified [53].

3. Research Methodology

This study began with data collected from various sources and direct observation. We reviewed international battery swap standards for electric motorcycle applications, stakeholder requirements, standard technique adoption procedures, and SNI writing procedures. The interaction between standardization and open innovation was considered in the form of interactions between inbound and outbound processes. Inbound processes, which consider knowledge, experience, and stakeholders' needs, were utilized with the FACTS steps. Meanwhile, outbound processes, which consider deliverable standards that meet the current and future needs of stakeholders, were utilized for the SEM approach. The experiment was carried out at the battery swap mini-plant of the university, where battery swap components, battery cells, and battery modules are available to be installed on electric motorcycles.

This study uses variance-based SEM to develop exploratory SNI design models for electric motorcycle battery swap tests based on first-generation TAM theory [54]. The SNI battery test framework, which is the output of the FACTS approach, is the latent construct in developing the dependent variable of this study, i.e., perceived ease of use. This study is a continuation of previous research, where we developed the initial framework [39]. The initial framework used sequential mixed methods [55] and is illustrated in Figure 1.



Figure 1. Sequential mixed methodology of the study.

3.1. FACTS Approach

The SNI framework was built using the FACTS approach, implemented in four stages. Stakeholders' requirements were analyzed based on the perspectives and opinions of the stakeholders, such as the government, battery swap R&D, battery swap laboratories, battery swap factories, electric motorcycle factories, and electric motorcycle users (i.e., people who have ridden an electric motorcycle). In the second stage, technical analysis was performed by converting stakeholders' opinions into technical language.

A comparison of standards was made in the third stage by analyzing the similarities and differences in the reference standard. The Zachman framework was used to identify gaps and overlaps between the reference standard and the technical specifications of stakeholder requirements at this stage. The reference standard was IEC 62840-2:2016, containing the standard battery swap requirements for electric vehicles [56]. This standard was chosen because no international standards for the battery swap test were available. The comparison of stakeholder requirements and reference standards is shown in Table 2.

Table 2. Standard comparison.

Stakeholder Requirements	Standard Reference (Adopted from IEC 62840-2:2016)
Protection against electric shock	Chapter 7 Chapter 8
Electromagnetic compatibility	Chapter 9
Marking and instruction	Chapter 10

Based on an analysis of the similarities and differences in the reference standards, we subsequently conducted standard testing and verification of any testing standards that could meet the requirements of battery swap stakeholders for electric motorcycle applications in the final stage. The output of the FACTS approach was used to develop a questionnaire to create the SNI framework from the SEM analysis.

3.2. SEM Approach

SEM was used for the second stage of data processing. Domestic capacity was recapitulated based on the FACTS output to implement the proposed SNI for battery swap testing. This information was then used as the input for SEM. First, based on the problem or research hypothesis, a structural model (i.e., outer model) of the relationships between latent variables in the partial least squares was created. Then, a measurement model (i.e., inner model) was created to determine whether the indicator was reflective or formative. The path diagram was then created based on the outcomes of the external and internal model designs. Subsequently, estimation of parameters was carried out by iteration. The goodness of fit was measured to ensure the validity of the model. Finally, hypothesis testing was performed.

3.2.1. Structural Model

Four latent variables (i.e., constructs) were used in the model, namely, SNI implementation, stakeholder protection, national uniqueness, and SNI acceptance. The SNI implementation variable was obtained from data processing using the FACTS method, resulting in a non-equivalent adopted SNI based on IEC 62840-2: 2016. The stakeholder protection variable was generated from a literature review conducted previously. In addition, the national uniqueness variable was based on 10 goals of standardization [57]. Finally, the SNI acceptance variable was the outcome of this study. The exogenous latent variables identified were national uniqueness, stakeholder protection, electric shock protection, equipment constructional requirements, electromagnetic compatibility, and marking and instruction. Meanwhile, the endogenous latent variables were the SNI implementation and its success. Figure 2 depicts the structural model and variable direction based on TAM [54].

3.2.2. Measurement Model

The measurement model emphasizes the relationships among measured (i.e., observed) variables underlying the latent variables. In this study, all constructs have reflective indicators, which measure each construct. For each construct, a measurement model was developed and consisted of the following aspects:

- Manifest variable (indicator), which is denoted by X for indicators related to exogenous constructs or Y for indicators related to endogenous constructs;
- Loading factor (λ), which represents the direct correlation between construct and indicator;

- Latent variable or construct (ξ);
- Measurement error, which is denoted by δ for error related to exogenous constructs or ε for error related to endogenous constructs.



Figure 2. Structural model.

The residual regression value on endogenous latent variables denoted by ζ also contributes to the model. The regression coefficient between exogenous latent variables and endogenous latent variables is denoted by γ , while the relationship between two endogenous variables is denoted by β . Table 3 presents the proposed constructs and indicators in the SEM model, while Table 4 shows the measurement model for each construct. On the other hand, Figure 3 shows the path diagram of the SEM model.

Construct	Indicators	Code
	Conformity to standardization goals	A1
	Exchangeability	A2
	Diversity control	A3
	Compatibility	A4
National uniqueness	Increased empowerment of resources	A5
National uniqueness —	Communication	A6
	Security, safety, and health	A7
	Environmental conservation	A8
	Technology transfer	A9
	Reducing trade barriers	A10
	Protecting the government	B1
	Protecting battery swap R&D	B2
Drotaction of stakeholders	Protecting battery swap laboratories	В3
Frotection of stakeholders —	Protecting the battery swap industry	B4
	Protecting the electric motor industry	B5
	Protecting electric vehicle users	B6

Table 3. Cont.

Standard contains protection against electric shock C1 Standard contains constructional equipment requirements C2 Standard contains electromagnetic compatibility C3 Standard contains marking and instruction C4 Protection against direct and indirect contact C5 Protection for power supply equipment C6 SBS charging equipment protection C7 Direct contact C8 Protection in battery enclosure C9 Protective measures on energy with high voltage C11 Protective measures on energy with high voltage C11 Protection of persons in accordance with standard C16 Compliance of telecommunications network with standard C17 Compliance of telecommunications network with standard C17 Compliance of telecommunications network with standard C16 Compliance of telecommunications network with standard C18 Switch C19 Contactor C20 Circuit breakers C21 Resistance against mechanical, electrical, thermal, and environmental stresses C23 Clearances and creepage distance <td< th=""><th>Construct</th><th>Indicators</th><th>Code</th></td<>	Construct	Indicators	Code
Standard contains constructional equipment requirementsC2Standard contains electromagnetic compatibilityC3Standard contains marking and instructionC4Protection against direct and indirect contactC5Protection for power supply equipmentC6SBS charging equipment protectionC7Direct contactC8Protection regulations on couplerC10Protective measures on energy with high voltageC11Protective measures or unspected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC16Compliance of telecommunications network with standardC16Compliance of telecommunications network with standardC17Equipment constructional requirementsC23Equipment constructional requirementsC23Equipment constructional requirementsC23Equipment constructional requirementsC23Equipment constructional requirementsC23Equipment constructional requirementsC23Equipment constructional requirementsC26Equipment constructional requirementsC26Equipment constructional requirementsC23Equipment constructional requirementsC23Equipment constructional requirementsC26Equipment constructional requirementsC26Equipment constructional requirementsC26Equip		Standard contains protection against electric shock	C1
Standard contains electromagnetic compatibilityC3Standard contains marking and instructionC4Protection against direct and indirect contactC5Protection for power supply equipmentC6SBS charging equipment protectionC7Direct contactC8Protection in battery enclosureC9Protective measures on energy with high voltageC11Protective measures for unexpected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Standard Clearances and creepage distanceC24RelayC22Equipment constructional requirementsC25Minimun level of protection against mechanical impactC26Protective coating on the exposed surface in corrosion impactC27Sistance against mechanical, effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fine tests.C31Resistance to solar radiationC33		Standard contains constructional equipment requirements	C2
Standard contains marking and instructionC4Protection against direct and indirect contactC5Protection for power supply equipmentC6SBS charging equipment protectionC7Direct contactC8Protection in battery enclosureC9electric shockProtection regulations on couplerProtective measures on energy with high voltageC11Protective measures or unexpected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC16Compliance of telecommunications network with standardC17Protection of persons in accordance with standardC18SwitchC19ContactorC20Circuit breakersC21Circuit breakersC21RelayC22Equipment constructional requirementsC23Clearances and creepage distanceC24Material flammability and resistance against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to solar radiationC32Resistance to solar radiationC32		Standard contains electromagnetic compatibility	C3
Protection against direct and indirect contactC5Protection for power supply equipmentC6SBS charging equipment protectionC7Direct contactC8Protection in battery enclosureC9Protective measures on energy with high voltageC11Protective measures on energy with high voltageC11Protective measures on energy with high voltageC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Compliance of telecommunications network with standardC18SwitchC19ContactorC20Circuit breakersC21RelayC22Equipment constructional requirementsC25Minimum level of protection against mechanical impactC26Protective coating on the exposed surface in corrosion rest subject to heat and fire tests.C29External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to trackingC32Resistance to rackingC32Resistance to trackingC32Resistance to rackingC31Resistance to rackingC31Resistance to rackingC32Resistance to rackingC31 <td></td> <td>Standard contains marking and instruction</td> <td>C4</td>		Standard contains marking and instruction	C4
Protection for power supply equipmentC6SBS charging equipment protectionC7Direct contactC8Protection in battery enclosureC9Protection regulations on couplerC10Protective measures on energy with high voltageC11Protective measures on energy with high voltageC11Protective measures for unexpected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC16Compliance of telecommunications network with standardC17Compliance of telecommunications network with standardC18SwitchC19ContactorC20Circuit breakersC21RelayC22Equipment constructional requirementsC23Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to trackingC32Resistance to solar radiationC33		Protection against direct and indirect contact	C5
SBS charging equipment protectionC7Direct contactC8Protection against electric shockProtection in battery enclosureC9Protective measures on energy with high voltageC11Protective measures on energy with high voltageC11Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Compliance of telecommunications network with standardC19Control signals on the shieldingC22Equipment constructional requirementsC23Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and environmental stressesC25Protective coating on the exposed surface in corrosion testC28Equipment constructional requirementsC28Equipment solvents or liquids, vibration, and shockC29Protective coating on the exposed surface in corrosion testC28Equipment constructional impactC30Resistance to the at and fire tests.C30Consolvents or liquids, vibration, and shockC29Enclosure stability in dry heat testC29Enclosure stability in dry		Protection for power supply equipment	C6
Direct contactC8Protection against electric shockProtection in battery enclosureC9Protection regulations on couplerC10Protective measures on energy with high voltageC11Protective measures for unexpected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC16Compliance of telecommunications network with standardC17Protection of persons in accordance with standardC18Compliance of telecommunications network with standardC19ContactorC20Circuit breakersC21Circuit breakersC22Electrical measurementsC23Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and environmental stressesC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to solar radiationC32		SBS charging equipment protection	C7
Protection against electric shockProtection in battery enclosureC9Protection regulations on couplerC10Protective measures on energy with high voltageC11Protective measures for unexpected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17ContactorC20Circuit breakersC21RelayC22Equipment constructional requirementsC12Material flammability and resistance against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Resistance to solar radiationC33		Direct contact	C8
electric shockProtection regulations on couplerC10Protective measures on energy with high voltageC11Protective measures for unexpected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17SwitchC19ContactorC20Circuit breakersC21RelayC22Equipment constructional requirementsC12Minimum level of protection against mechanical impactC25Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Resistance to solar radiationC31	Protection against	Protection in battery enclosure	C9
Protective measures on energy with high voltageC11Protective measures for unexpected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Compliance with standardC18Compliance with standardC19ContactorC20ContactorC20ContactorC20Circuit breakersC21RelayC22Clearances and creepage distanceC24Clearance against mechanical, electrical, thermal, and impactC25Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Resistance to trackingC32Castance to solar radiationC34	electric shock	Protection regulations on coupler	C10
Protective measures for unexpected eventsC12Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Compliance with standardC18Compliance with standardC19ContactorC20Circuit breakersC21RelayC22Clearances and creepage distanceC24Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and impactC25Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to solar radiationC32		Protective measures on energy with high voltage	C11
Control signals on the shielding conductorsC13Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Compliance with standardC18SwitchC19ContactorC20Circuit breakersC21RelayC22Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and impactC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Resistance to trackingC32Resistance to solar radiationC33		Protective measures for unexpected events	C12
Additional protectionC14Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Compliance with standardC18SwitchC19ContactorC20Circuit breakersC21RelayC22Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and impactC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Resistance to trackingC32Castance to solar radiationC33		Control signals on the shielding conductors	C13
Manual reset of circuit breakers, residual current devices, and other equipmentC15Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Compliance with standardC18Compliance with standardC19ContactorC20ContactorC21Circuit breakersC21Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and environmental stressesC25Material flammability and resistance against mechanical impactC26Protective coating on the exposed surface in corrosion testC28Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fire tests.C30Resistance to solar radiationC31		Additional protection	C14
Protection of persons in accordance with standardC16Compliance of telecommunications network with standardC17Compliance with standardC18Compliance with standardC18SwitchC19ContactorC20Circuit breakersC21RelayC22Electrical measurementsC23Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and environmental stressesC26Minimum level of protection against mechanical impactC26Protective coating on the exposed surface in corrosion testC28Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to solar radiationC33		Manual reset of circuit breakers, residual current devices, and other equipment	C15
Compliance of telecommunications network with standardC17Compliance with standardC18Compliance with standardC19SwitchC19ContactorC20ContactorC20Circuit breakersC21RelayC22Electrical measurementsC23Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and environmental stressesC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to solar radiationC32		Protection of persons in accordance with standard	C16
Equipment constructional requirementsCompliance with standardC18SwitchC19ContactorC20Circuit breakersC21RelayC22Electrical measurementsC23Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and environmental stressesC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Resistance to trackingC32Resistance to solar radiationC33		Compliance of telecommunications network with standard	C17
Equipment constructional requirementsC19Image: Construct on the exposed surface in corrosion restC21Material flammability and resistance against effects of solvents or liquids, vibration, and shockC23Image: Construct on the exposed surface in corrosion testC23Image: Construct on the exposed surface in corrosion testC30Image: Construct on the exposed surface in corrosion testC30Image: Construct on the exposed surface in corrosion testC31Image: C		Compliance with standard	C18
Equipment constructionarC20requirementsC21Minimum level of protection against mechanical impactC23Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Call Call CallC30Call Call CallC30Call Call CallC31Call Call Call CallC31Call Call Call Call Call CallC31Call Call		Switch	C19
C1C21RelayC22C23C23C1C23C1C23C1C23C1C23C1C24Resistance against mechanical, electrical, thermal, and environmental stressesC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30C30Resistance to trackingC32Resistance to solar radiationC33		Contactor	C20
RelayC22Electrical measurementsC23Clearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and environmental stressesC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to solar radiationC32		Circuit breakers	C21
Equipment constructional requirementsC23Equipment constructional requirementsClearances and creepage distanceC24Minimum level of protection against mechanical impactC25Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to solar radiationC33		Relay	C22
Equipment constructional requirementsClearances and creepage distanceC24Resistance against mechanical, electrical, thermal, and environmental stressesC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30Resistance to trackingC32Resistance to solar radiationC33		Electrical measurements	C23
Equipment constructional requirementsResistance against mechanical, electrical, thermal, and environmental stressesC25Minimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28External parts of insulating material and parts are subject to heat and fire tests.C30C30C31C32Resistance to trackingC32C33C33		Clearances and creepage distance	C24
Equipment constructional requirementsMinimum level of protection against mechanical impactC26Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to solar radiationC33		Resistance against mechanical, electrical, thermal, and environmental stresses	C25
Material flammability and resistance against effects of solvents or liquids, vibration, and shockC27Protective coating on the exposed surface in corrosion testC28Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to solar radiationC33	Equipment constructional	Minimum level of protection against mechanical impact	C26
Protective coating on the exposed surface in corrosion testC28Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to solar radiationC33	requiremente	Material flammability and resistance against effects of solvents or liquids, vibration, and shock	C27
Enclosure stability in dry heat testC29External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to solar radiationC33		Protective coating on the exposed surface in corrosion test	C28
External parts of insulating material and parts are subject to heat and fire tests.C30Ball pressure testC31Resistance to trackingC32Resistance to solar radiationC33		Enclosure stability in dry heat test	C29
Ball pressure testC31Resistance to trackingC32Resistance to solar radiationC33		External parts of insulating material and parts are subject to heat and fire tests.	C30
Resistance to trackingC32Resistance to solar radiationC33		Ball pressure test	C31
Resistance to solar radiation C33		Resistance to tracking	C32
		Resistance to solar radiation	C33

Table	3. (Cont.
-------	------	-------

Construct	Indicators	Code
Electromagnetic	Compliance with EMC requirements of residential location	C34
companionity (EWC)	Compliance with industrial sites' EMC requirements	C35
	Marked with complete information	C36
	Legible, durable, and visible marks	C37
Marking and instruction	Prohibition of plastic usage for markings	C38
	Indication of dangerous occurrence using visual signals	C39
Conducion	Consideration of national uniqueness and stakeholder protection	C40
Conclusion	Stakeholder confidence when implementing standard	C41
	Sustainability of standard	C42

 Table 4. Measurement model for each construct.

Construct	Number of Indicators	Measurement Model
		$ \begin{aligned} X_1 &= \lambda_{X1} \ \xi_{X1} + \delta_1 \ (1) \\ X_2 &= \lambda_{X2} \ \xi_{X2} + \delta_2 \ (2) \end{aligned} $
National uniqueness (ξ_1)	$10 (X_1, \ldots, X_{10})$	
		$X_{9} = \lambda_{X9} \xi_{X9} + \delta_{9} (9)$ $X_{10} = \lambda_{X10} \xi_{X10} + \delta_{10} (10)$
		$X_{11} = \lambda_{X11} \ \xi_{11} + \delta_{11} \ (11)$
Stakeholder protection (ξ_2)	$6((X_{11},\ldots,X_{16})$	
		$X_{16} = \lambda_{X16} \ \xi_{16} + \delta_{16} \ (16)$
		$X_{17} = \lambda_{X17} \ \xi_{17} + \delta_{17} \ (17)$
Protection against electric shock (ξ_3)	$12(X_{17}, \ldots, X_{28})$	
		$X_{28} = \lambda_{X28} \ \xi_{28} + \delta_{28} \ (28)$
Equipment constructional		$X_{29} = \lambda_{X29} \ \xi_{29} + \delta_{29} \ (29)$
requirements (ξ_4)	$16(X_{29}, \ldots, X_{44})$	$X_{44} = \lambda_{X44} \xi_{44} + \delta_{44} (44)$
Electromagnetic compatibility (ξ_5)	2 (X ₄₅ , X ₄₆)	$X_{45} = \lambda_{X45} \xi_{45} + \delta_{45} (45)$ $X_{46} = \lambda_{X46} \xi_{46} + \delta_{46} (46)$
		$X_{46} = \lambda_{X46} \xi_{46} + \delta_{46} (10)$ $X_{47} = \lambda_{X47} \xi_{47} + \delta_{47} (47)$
Marking and instruction (ξ_6)	$4(X_{47}, \ldots, X_{50})$	
		$X_{50} = \lambda_{X50} \ \xi_{50} + \delta_{50} \ (50)$
		$Y_1 = \lambda_{y1} + \varepsilon_1 (51)$
SNI implementation (η_1)	$4(Y_1,, Y_4)$	
		$Y_4 = \lambda_{y4} + \varepsilon_4 \tag{54}$
		$Y_5 = \lambda_{y5} + \varepsilon_5 (55)$
SNI acceptance (η_2)	3 (Y ₅ , Y ₆ , Y ₇)	$Y_6 = \lambda_{y6} + \varepsilon_6 (56)$ $Y_7 = \lambda_{y7} + \varepsilon_7 (57)$



Figure 3. Path diagram of the SEM model.

This study was conducted using SmartPLS version 3.2.8. In this study, the variantbased SEM model was used. The parameter estimation method was partial least squares (PLS), which does not require the data to be normally distributed and can be performed simultaneously during data processing.

3.2.3. Model Evaluation

This stage was used to determine whether the overall model was appropriately fitted. We used goodness of fit as a metric to determine the model's validity. Table 5 shows the criteria for determining model validity and the values used in this study.

We integrated the FACTS and SEM approaches to analyze the dynamics of open innovation in the development of battery swap standards. In open innovation, there is interaction between inbound and outbound processes. The inbound processes allow us to explore external knowledge and the needs of various stakeholders with regard to battery swap standards. Meanwhile, the outbound processes entail the dissemination of the results of standard development to stakeholders. In developing standards, the FACTS approach considers all relevant stakeholders' interests that represent transparency and open participation. In addition, the SEM approach is used to validate stakeholder needs that have been processed through the FACTS approach. Therefore, the consensus principle in standardization allows interested parties to express their viewpoints and be accommodated accordingly.

Criteria	Description	Reference
Convergent validity of indicators	Loading factor ≥ 0.5	[58]
Convergent validity of constructs	Cronbach's alpha ≥ 0.5	[58]
Discriminant validity	Cross-loading with the \sqrt{AVE} (average variance extracted) value of a construct and the correlation of that construct with other constructs. The \sqrt{AVE} value for each construct must be greater than the correlation value between constructs and other constructs	[58]
Collinearity assessment	$VIF \ge 0.2$ or $VIF \le 5$	[59]
Path coefficient	The path coefficient values range from -1 to $+1$. The minimum path coefficient value is 0.2, and the ideal is more significant than 0.3 to express a meaningful relationship	[60]
Coefficient of determination (R^2)	Square adjusted value ≥ 0.25	[61]
Effect size f^2 Predictive relevance Q^2	Large ($f^2 = 0.35$), medium ($f^2 = 0.15$), small ($f^2 = 0.02$) Certain endogenous constructs have predictive relevance if $Q^2 = 0$	[61] [60]
Effect size q^2	Large ($q^2 = 0.35$), medium ($q^2 = 0.15$), small ($f^2 = 0.002$)	[60]
Hypothesis test	t -Value $\geq t$ -table	Hypothesis acceptance rules

Table 5. Goodness of fit.

4. Results

In this section, we evaluate items about outer model analysis, inner model analysis, and hypothesis testing.

4.1. Outer Model Analysis

In this section, the items evaluated include the convergent validity of indicators, the convergent validity of constructs, and discriminant validity. Convergent validity is used to show the correlation between indicators of the same construct. Table 6 presents the results of the calculation of outer loading for the convergent validity of indicators. At the same time, Figure 4 shows the model in which the outer loading passes the convergent validity of indicators. Next, we also evaluated the convergent validity for each construct (latent variable). This is a combination of all reliability indicators for the corresponding construct. Table 7 presents the Cronbach's alpha for each construct. We then evaluated the discriminant validity using the cross-loading method (or \sqrt{AVE} value). Table 8 shows the results of cross-loading of the latent variable.

Table 6. Convergent validity of indicators.

	The Leading Faster	Decision		
Construct	Indicators	Loading ractor	Valid	Not Valid
	A1	0.288		\checkmark
	A2	-0.022		\checkmark
	A3	0.787	\checkmark	
	A4	-0.359		\checkmark
National uniqueness	A5	0.662	\checkmark	
National uniqueness	A6	0.650	\checkmark	
	A7	0.513	\checkmark	
	A8	0.621	\checkmark	
	A9	-0.186		\checkmark
	A10	0.366		\checkmark

B1 -0.076 \checkmark B2 0.563 \checkmark B3 0.852 \checkmark B4 0.026 \checkmark B5 0.716 \checkmark B6 -0.112 \checkmark SNI implementation (1.1) 0.876 \checkmark C1.1 0.876 \checkmark \checkmark C1.2 0.374 \checkmark \checkmark C1.4 0.890 \checkmark \checkmark C1.4 0.890 \checkmark \checkmark C2.5 0.114 \checkmark \checkmark C2.4 0.647 \checkmark \checkmark C2.5 0.116 \checkmark \checkmark C2.4 0.647 \checkmark \checkmark C2.5 0.116 \checkmark \checkmark C2.4 0.647 \checkmark \sim C2.7 0.028 \checkmark \checkmark C2.8 0.337 \checkmark \checkmark C2.10 0.734 \checkmark \sim C3.1	Construct	Indicators	Loading Factor	D Valid	ecision Not Valid
		B1	-0.076		\checkmark
Stakeholder protection B3 0.852 \checkmark B4 0.026 \checkmark B5 0.716 \checkmark B6 -0.112 \checkmark SNI implementation C1.1 0.876 \checkmark C1.2 0.374 \checkmark C1.4 0.890 \checkmark C1.4 0.890 \checkmark C2.2 0.609 \checkmark C2.3 -0.132 \checkmark C2.4 0.647 \checkmark C2.5 0.116 \checkmark C2.4 0.647 \checkmark C2.5 0.116 \checkmark C2.4 0.647 \checkmark C2.4 0.647 \checkmark C2.4 0.647 \checkmark C2.5 0.116 \checkmark C2.7 0.028 \checkmark C2.10 0.734 \checkmark C2.11 0.450 \checkmark C3.1 -0.33 \checkmark C3.1 0.611 \checkmark		B2	0.563	\checkmark	
protection B4 B5 0.026 0.716 · B6 -0.112 · SNI implementation C1.2 0.374 · C1.4 0.890 · · C1.4 0.890 · · C1.4 0.890 · · C1.4 0.890 · · C2.1 0.135 · · C2.3 -0.132 · · C2.4 0.647 · · C2.5 0.116 · · C2.4 0.647 · · C2.5 0.116 · · C2.6 0.327 · · C2.6 0.327 · · C2.10 0.734 · · C2.11 0.459 · · C2.10 0.734 · · C3.1 -0.353 · · C3.1 -0.353 · ·	Stakeholder	B3	0.852		\checkmark
B5 0.716 \checkmark B6 -0.112 \checkmark SNI implementation C1.1 0.876 \checkmark C1.3 -0.114 \checkmark C1.4 0.890 \checkmark C1.4 0.890 \checkmark C1.4 0.890 \checkmark C2.2 0.609 \checkmark C2.3 -0.132 \checkmark C2.4 0.647 \checkmark C2.5 0.116 \checkmark C2.6 0.327 \checkmark C2.7 0.028 \checkmark C2.8 0.439 \checkmark C2.10 0.794 \checkmark C2.11 0.450 \checkmark C2.10 0.734 \checkmark C2.10 0.734 \checkmark C2.11 0.450 \checkmark C2.12 0.469 \checkmark C3.1 -0.233 \checkmark C3.1 0.028 \checkmark C3.1 0.214 \checkmark C3.1 0.2	protection	B4	0.026		\checkmark
	I	B5	0.716	\checkmark	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		B6	-0.112		\checkmark
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$		C1.1	0.876	\checkmark	
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	SNI implementation	C1.2	0.374		\checkmark
C1.4 0.890 \checkmark C21 0.135 \checkmark C22 0.609 \checkmark C23 -0.132 \checkmark C24 0.647 \checkmark C25 0.116 \checkmark C26 0.327 \checkmark C27 0.028 \checkmark C29 0.599 \checkmark C210 0.734 \checkmark C211 0.469 \checkmark C31 -0.353 \checkmark C32 -0.005 \checkmark C33 0.377 \checkmark C34 0.611 \checkmark C35 0.589 \checkmark C36 0.701 \checkmark C37 0.511 \checkmark C38 0.214 \checkmark C310 -0.233 \checkmark <t< td=""><td>Sivi implementation</td><td>C1.3</td><td>-0.114</td><td></td><td>\checkmark</td></t<>	Sivi implementation	C1.3	-0.114		\checkmark
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		C1.4	0.890	\checkmark	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		C2.1	0.135		\checkmark
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		C2.2	0.609	\checkmark	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		C2.3	-0.132		\checkmark
$\begin{array}{c cccc} C2.5 & 0.116 & & \checkmark \\ \mbox{Protection against} & C2.6 & 0.327 & & \checkmark \\ C2.6 & 0.327 & & \checkmark \\ clectric shock & C2.7 & 0.028 & & \checkmark \\ C2.9 & 0.599 & \checkmark & & \\ C2.9 & 0.599 & \checkmark & & \\ C2.10 & 0.734 & \checkmark & & \\ C2.11 & 0.450 & & \checkmark & & \\ C2.12 & 0.469 & & \checkmark & \\ C2.12 & 0.469 & & \checkmark & & \\ C2.12 & 0.469 & & \checkmark & & \\ C3.1 & -0.353 & & \checkmark & & \\ C3.2 & -0.005 & & \checkmark & & \\ C3.3 & 0.377 & & & \checkmark & \\ C3.4 & 0.611 & \checkmark & & \\ C3.5 & 0.589 & \checkmark & & \\ C3.6 & 0.701 & \checkmark & & \\ C3.6 & 0.701 & \checkmark & & \\ C3.6 & 0.701 & \checkmark & & \\ C3.7 & 0.511 & \checkmark & & \\ C3.8 & 0.214 & & & \checkmark & \\ C3.10 & -0.233 & & & \checkmark & \\ C3.11 & 0.533 & \checkmark & & \\ C3.12 & 0.114 & & & & \\ C3.13 & 0.102 & & & & \\ C3.14 & 0.172 & & & & \\ C3.15 & -0.253 & & & & & \\ C3.16 & -0.238 & & & & \\ \hline \end{array}$		C2.4	0.647	\checkmark	
$\begin{array}{c c c c c c c c c c c c c c c c c c c $		C2.5	0.116		\checkmark
electric shock C2.7 0.028 \checkmark C2.8 0.439 \checkmark C2.9 0.599 \checkmark C2.10 0.734 \checkmark C2.11 0.450 \checkmark C2.12 0.469 \checkmark C3.1 -0.353 \checkmark C3.2 -0.005 \checkmark C3.4 0.611 \checkmark C3.4 0.611 \checkmark C3.5 0.589 \checkmark C3.6 0.701 \checkmark C3.7 0.511 \checkmark C3.8 0.214 \checkmark constructional C3.9 0.245 \checkmark C3.10 -0.233 \checkmark \checkmark C3.11 0.533 \checkmark \sim C3.12 0.114 \checkmark \checkmark C3.14 0.172 \checkmark \sim C3.15 -0.238 \checkmark \sim C3.16 -0.238 \checkmark \sim C4.1 -0.765	Protection against	C2.6	0.327		\checkmark
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	electric shock	C2.7	0.028		\checkmark
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		C2.8	0.439		\checkmark
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		C2.9	0.599	\checkmark	
$ \begin{array}{c ccccc} C2.11 & 0.450 & \checkmark \\ C2.12 & 0.469 & \checkmark \\ \hline \\ C3.1 & -0.353 & \checkmark \\ C3.2 & -0.005 & \checkmark \\ C3.3 & 0.377 & \checkmark \\ C3.4 & 0.611 & \checkmark \\ C3.5 & 0.599 & \checkmark \\ C3.6 & 0.701 & \checkmark \\ C3.6 & 0.701 & \checkmark \\ C3.7 & 0.511 & \checkmark \\ C3.8 & 0.214 & \checkmark \\ C3.9 & 0.245 & \checkmark \\ C3.10 & -0.233 & \checkmark \\ C3.11 & 0.533 & \checkmark \\ C3.12 & 0.114 & \checkmark \\ C3.13 & 0.102 & \checkmark \\ C3.15 & -0.253 & \checkmark \\ C3.16 & -0.238 & \checkmark \\ \hline \\$		C2.10	0.734	\checkmark	
$ \begin{array}{c cccccc} C2.12 & 0.469 & \checkmark \\ \hline C3.1 & -0.353 & \checkmark \\ C3.2 & -0.005 & \checkmark \\ C3.3 & 0.377 & \checkmark \\ C3.4 & 0.611 & \checkmark \\ C3.5 & 0.589 & \checkmark \\ C3.6 & 0.701 & \checkmark \\ C3.6 & 0.701 & \checkmark \\ C3.8 & 0.214 & & \checkmark \\ C3.8 & 0.214 & & \checkmark \\ C3.9 & 0.245 & & \checkmark \\ C3.10 & -0.233 & & \checkmark \\ C3.11 & 0.533 & \checkmark \\ C3.12 & 0.114 & & \checkmark \\ C3.13 & 0.102 & & \checkmark \\ C3.15 & -0.253 & & \checkmark \\ C3.16 & -0.238 & & \checkmark \\ C3.16 & -0.238 & & \checkmark \\ \hline \\$		C2.11	0.450		\checkmark
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		C2.12	0.469		\checkmark
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		C3.1	-0.353		\checkmark
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		C3.2	-0.005		\checkmark
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		C3.3	0.377		\checkmark
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		C3.4	0.611	\checkmark	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		C3.5	0.589	\checkmark	
$ \begin{array}{cccc} & & & & & & & & & & & & & & & & & $		C3.6	0.701	\checkmark	
Equipment C3.8 0.214 \checkmark constructional C3.9 0.245 \checkmark requirements C3.10 -0.233 \checkmark C3.11 0.533 \checkmark \checkmark C3.12 0.114 \checkmark C3.13 0.102 \checkmark C3.14 0.172 \checkmark C3.15 -0.253 \checkmark C3.16 -0.238 \checkmark Electromagnetic C4.1 -0.765 \checkmark compatibility C4.2 0.977 \checkmark Marking and C5.2 0.361 \checkmark SNI acceptance C6.1 0.003 \checkmark SNI acceptance C6.1 0.003 \checkmark		C3.7	0.511	\checkmark	
$\begin{array}{cccc} constructional requirements & C3.9 & 0.245 & \checkmark \\ c3.10 & -0.233 & \checkmark \\ C3.11 & 0.533 & \checkmark \\ C3.12 & 0.114 & & \checkmark \\ C3.12 & 0.114 & & \checkmark \\ C3.13 & 0.102 & & \checkmark \\ C3.14 & 0.172 & & \checkmark \\ C3.15 & -0.253 & & \checkmark \\ C3.16 & -0.238 & & \checkmark \\ c3.16 & -0.238 & & \checkmark \\ \hline \\ \hline \\ Electromagnetic c4.1 & -0.765 & & \checkmark \\ c3.16 & -0.655 & & \checkmark \\ compatibility & C4.2 & 0.977 & \checkmark \\ \hline \\ \\ Marking and c5.2 & 0.361 & & \checkmark \\ c5.3 & 0.449 & \checkmark \\ c5.4 & -0.197 & & \checkmark \\ \hline \\ \\ SNI acceptance & \begin{array}{ccccccccccccccccccccccccccccccccccc$	Equipment	C3.8	0.214		\checkmark
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	constructional	C3.9	0.245		\checkmark
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	requirements	C3.10	-0.233		\checkmark
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		C3.11	0.533	\checkmark	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		C3.12	0.114	•	1
$\begin{array}{ccccccc} C3.14 & 0.172 & \checkmark \\ C3.15 & -0.253 & \checkmark \\ C3.16 & -0.238 & \checkmark \\ \hline \\ C3.16 & -0.238 & \checkmark \\ \hline \\ C3.16 & -0.238 & \checkmark \\ \hline \\ C4.2 & 0.977 & \checkmark \\ \hline \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$		C3 13	0.102		
$\begin{array}{c ccccc} C3.15 & -0.253 & \checkmark \\ C3.16 & -0.238 & \checkmark \\ \hline \\ C3.16 & -0.238 & \checkmark \\ \hline \\ C4.2 & 0.977 & \checkmark \\ \hline \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$		C3 14	0.172		
$\begin{array}{c ccccc} & 0.250 & & \checkmark \\ \hline C3.16 & -0.238 & \checkmark \\ \hline C4.2 & 0.977 & \checkmark \\ \hline \\ \hline \\ Marking and & C5.2 & 0.361 & & \checkmark \\ \hline \\ Marking and & C5.2 & 0.361 & & \checkmark \\ \hline \\ C5.3 & 0.449 & \checkmark \\ \hline \\ C5.4 & -0.197 & & \checkmark \\ \hline \\ SNI acceptance & C6.1 & 0.003 & & \checkmark \\ \hline \\ SNI acceptance & C6.2 & 0.640 & \checkmark \\ \hline \\ C6.3 & 0.934 & \checkmark \\ \hline \end{array}$		C3 15	-0.253		
$ \begin{array}{c cccc} Electromagnetic \\ compatibility \\ \hline C4.2 \\ \hline C4.2 \\ \hline 0.977 \\ \hline \hline$		C3.16	-0.238		\checkmark
$\begin{array}{c c} \mbox{compatibility} & \mbox{C4.2} & \mbox{0.977} & \end{subarray} & \\ \mbox{Marking and} & \mbox{C5.1} & -0.655 & \end{subarray} & \\ \mbox{C5.2} & \mbox{0.361} & \end{subarray} & \end{subarray} & \\ \mbox{C5.3} & \mbox{0.449} & \end{subarray} & \end{subarray} & \\ \mbox{C5.4} & -0.197 & \end{subarray} & \end{subarray} & \\ \mbox{SNI acceptance} & \box{C6.1} & \mbox{0.003} & \end{subarray} & subarray$	Electromagnetic	C4.1	-0.765		\checkmark
$\begin{array}{c ccccc} & C5.1 & -0.655 & \checkmark \\ Marking and & C5.2 & 0.361 & \checkmark \\ instruction & C5.3 & 0.449 & \checkmark \\ & C5.4 & -0.197 & \checkmark \\ \\ SNI \ acceptance & C6.1 & 0.003 & \checkmark \\ & C6.2 & 0.640 & \checkmark \\ & C6.3 & 0.934 & \checkmark \\ \end{array}$	compatibility	C4.2	0.977	\checkmark	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		C5.1	-0.655		\checkmark
$ \begin{array}{c ccccc} \text{instruction} & C5.3 & 0.449 & \checkmark \\ \hline C5.4 & -0.197 & \checkmark \\ \hline \\ \text{SNI acceptance} & C6.1 & 0.003 & \checkmark \\ \hline C6.2 & 0.640 & \checkmark \\ \hline C6.3 & 0.934 & \checkmark \\ \hline \end{array} $	Marking and	C5.2	0.361		\checkmark
C5.4 −0.197 ✓ SNI acceptance C6.1 0.003 ✓ C6.2 0.640 ✓ C6.3 0.934 ✓	instruction	C5.3	0.449	\checkmark	
C6.1 0.003 ✓ SNI acceptance C6.2 0.640 ✓ C6.3 0.934 ✓		C5.4	-0.197		\checkmark
SNI acceptance C6.2 0.640 √ C6.3 0.934 √		C6.1	0.003		\checkmark
C6.3 0.934 🗸	SNI acceptance	C6.2	0.640	\checkmark	
	-	C6.3	0.934	\checkmark	

 Table 6. Cont.



Figure 4. Indicators of outer loading that passed the convergent validity.

 Table 7. Convergent validity of constructs.

Constant	Crowbesh's Almhe	Decision	
Construct	Cronbach's Alpha	Valid	Not Valid
National uniqueness	0.678	\checkmark	
Stakeholder protection	0.586	\checkmark	
SNI implementation	0.844	\checkmark	
Protection against electric shock	0.648	\checkmark	
Equipment constructional requirements	0.628	\checkmark	
Electromagnetic compatibility	1.000	\checkmark	
Marking and instruction	0.564	\checkmark	
SNI acceptance	0.516	\checkmark	

Construct (Latent Variable)	Electromagnetic Compatibility	Equipment Constructional Requirements	SNI Implemen- tation	SNI Acceptance	National Uniqueness	Marking and Instruction	Stakeholder Protection	Protection against Electric Shock
Electromagnetic compatibility	1.000							
requirements		0.832						
SNI implementation		0.831	0.964					
SNI acceptance		0.542	0.561	0.886				
National uniqueness	0.528	0.661	0.469	0.736	0.810			
Marking and instruction	0.167		0.405			0.892		
Stakeholder protection	0.342	0.650	0.789	0.597	0.577		0.861	
Protection against electric shock	0.486	0.706	0.772	0.594	0.643	0.187	0.696	0.832

Table 8. Discriminant validity.

4.2. Inner Model Analysis

Inner model analysis can be performed when the outer model analysis shows valid results. Inner model analysis was carried out by assessing several items: the constructs' collinearity, the value and significance of the path coefficients, the coefficient of determination R^2 , the effect size f^2 , the predictive relevance Q^2 , and the size effect q^2 .

Collinearity assessment is used to see whether there is high collinearity or correlation in the path-building model. If the generated *VIF* value is >5, it indicates a collinearity problem. Table 9 presents the collinearity assessment for the model used in this study.

Construct	Indicators	VIF	Decision
	A3	1.700	Valid
	A5	1.184	Valid
National uniqueness	A6	1.421	Valid
	A7	1.226	Valid
	A8	1.241	Valid
Stakeholder	B2	1.048	Valid
protection	B3	1.526	Valid
protection	B5	1.532	Valid
SNII implementation	C1.1	2.140	Valid
SINI Implementation	C1.4	2.140	Valid
	C2.4	1.168	Valid
Protection against	C2.9	2.080	Valid
Protection against electric shock	C2.10	1.203	Valid
	C2.11	1.972	Valid
Equipment	C3.4	2.505	Valid
constructional	C3.5	2.401	Valid
requirements	C3.6	1.582	Valid
requirements	C3.7	2.217	Valid
Electromagnetic compatibility	C4.2	1.000	Valid
Marking and	C5.2	1.182	Valid
instruction	C5.3	1.182	Valid
SNII accontance	C6.2	1.137	Valid
	C6.3	1.137	Valid

Table 9. Collinearity assessment.

Table 10 shows the relationship between the variables stated in the hypothesis. The path coefficient values range from -1 to +1. A path coefficient value close to +1 indicates a strong positive relationship between the variables, while a path coefficient value close to -1 indicates a strong negative relationship. The generated path coefficients are presented in Table 8.

Hypothesis	Path	Path Coefficient	
H1	Electromagnetic compatibility $ ightarrow$ SNI implementation	-0.218	
H2	Equipment constructional requirements \rightarrow SNI implementation	0.513	
H3	Marking and instruction \rightarrow SNI implementation	0.244	
H4	Protection against electric shock \rightarrow SNI implementation	0.384	
H5	SNI implementation \rightarrow SNI acceptance	0.143	
H6	National uniqueness \rightarrow SNI acceptance	0.473	
H7	Stakeholder protection \rightarrow SNI acceptance	0.109	

The coefficient of determination (R^2) is used to show the predictive power of the path model. The value of R^2 ranges from 0 to 1. The value of R^2 , which is close to 1, indicates that the prediction accuracy is getting stronger. Table 11 shows the coefficients of determination for the inner model in this study.

Table 11. Coefficients of determination.

	R^2	R ² Adjusted	Accuracy
SNI implementation	0.664	0.657	Strong
SNI acceptance	0.340	0.329	Medium

The effect size f^2 can be used to determine the effect of an exogenous variable on the related endogenous variable. Table 12 presents the f^2 values for each path.

Table	12.	Path	coefficients
-------	-----	------	--------------

Hypothesis	Path	f^2	Effect Size
H1	Electromagnetic compatibility \rightarrow SNI implementation	0.121	Medium
H2	Equipment constructional requirements \rightarrow SNI implementation	0.513	Large
H3	Marking and instruction \rightarrow SNI implementation	0.168	Medium
H4	Protection against electric shock \rightarrow SNI implementation	0.283	Large
H5	SNI implementation \rightarrow SNI acceptance	0.019	Small
H6	National uniqueness \rightarrow SNI implementation	0.301	Large
H7	Stakeholder protection \rightarrow SNI acceptance	0.010	Small

The predictive relevance Q^2 aims to see how well the path model can predict the original observed value. The assessment Q^2 value is determined using the stipulation that if the value of Q^2 is more significant than zero, then a particular endogenous construct has predictive relevance. The predictive relevance values for the model are presented in Table 13.

_

Latent Variable	SSO	SSE	$Q^2 = (1 - SSE/SSO)$
Electromagnetic compatibility	190,000	190,000	0
Equipment constructional requirements	760,000	760,000	0
SNI implementation	380,000	174,968	0.540
SNI acceptance	380,000	317,710	0.164
National uniqueness	950,000	950,000	0
Marking and instruction	380,000	380,000	0
Stakeholder protection	570,000	570,000	0
Protection against electric shock	760,000	760,000	0

Table 13. Predictive relevance.

The value effect size q^2 is obtained by comparing the Q^2 value when all exogenous variables are involved in the path model analysis with the Q^2 value when one of the exogenous variables is omitted in the path model analysis. The q^2 value in this study is determined as follows:

$$q^{2} = \frac{Q_{complete}^{2} - Q_{ommited}^{2}}{1 - Q_{complete}^{2}} = \frac{0.719 - 0.180}{1 - 0.719} = 1.922$$

4.3. Hypothesis Test

Hypothesis testing in this study uses a significance level of 0.15. The proposed hypothesis has a positive direction. Therefore, the test conducted is a one-tailed test with the number of variables (k) = 8 and the number of respondents (n) = 190 [62]. A hypothesis is accepted if the following conditions are met:

• The path coefficient is in the same direction as the proposed hypothesis, which is positive for a hypothesis that says "has a positive influence" or negative for a hypothesis that says "has a negative influence".

t-Value \geq *t*-table.

The results of the hypothesis testing are presented in Table 14.

Hypothesis	Path	Path Coefficient	t-Value	t-Table	Decision
H1	Electromagnetic compatibility has a positive effect on SNI implementation	-0.218	4.237	1.042	Accepted
H2	Equipment constructional requirements have a positive effect on SNI implementation	0.513	9.315	1.042	Accepted
Н3	Marking and instruction have a positive effect on SNI implementation	0.244	3.097	1.042	Accepted
H4	Protection against electric shock has a positive effect on SNI implementation	0.384	7.479	1.042	Accepted
Н5	SNI implementation has a positive effect on SNI acceptance	0.143	1.636	1.042	Accepted
H6	National uniqueness has a positive effect on SNI acceptance	0.473	5.755	1.042	Accepted
H7	Stakeholder protection has a positive effect on SNI acceptance	0.109	1.123	1.042	Accepted

Table 14. Hypothesis test.

5. Discussions

5.1. SEM outer Model Analysis

5.1.1. Convergent Validity of Indicators

Convergent validity is a measure that shows how much the indicator has a positive correlation with other indicators of the same construct. For research indicators that are still newly developed and have not been tested, the minimum value of outer loading is 0.5 or more [58], so that indicators with an outer loading of less than 0.5 will be removed. Removal of indicators with an extreme loading value of less than 0.5 is carried out gradually, starting from the smallest outer loading value. Every time an indicator is removed, the outer loading value is rechecked until the outer loading indicator is more than 0.5. In the SEM model with reflective indicators, the direction of the causality is from the latent variable to the indicator, which means that the latent variable determines the indicators, so all reflective indicators must have a high correlation with the latent variables. Because all indicators must have a high correlation, reducing the indicator should not change the meaning of the latent variable. An outer loading value of 0.5 or more means that the indicator has a 50% contribution to building its latent variable's constructor [59].

In the latent construct of national uniqueness, five indicators were removed: A1, A2, A4, A9, and A10.

 A1 (Battery swap components, such as battery cells, modules, and packs, must have passed the safety test)

A1 has the purpose represented by A7, which contains "test standards for swap battery products which aim to ensure safety and health for users of swap battery products". Therefore, if A1 is removed, it does not change the meaning of the construct of national uniqueness.

• A2 (Standard dimensions of swapped batteries' size, voltage, and electric current are required at all battery swap charging stations throughout Indonesia to produce equivalent performance and power without making changes or adjustments.)

The A2 indicator has the intent and purpose represented by the A5 indicator, which contains "the use of swap batteries to reduce the waste of resources (time, people, and capital)". Reduced waste of resources when using swapped batteries can be obtained if the minimum standard is implemented; hence, there are no significant differences between battery swap brands. The differences between battery swap brands can directly affect consumers and disrupt the supply chain's flow [2]. Therefore, if A2 is removed, it does not change the meaning of the construct of national uniqueness.

 A4 (Process suitability of swapped batteries for concurrent use with other relevant products without creating unnecessary interactions)

The purpose of the A4 indicator can be represented by A3, which contains the "application of standard dimensions of size, voltage and electric current of swap batteries to all battery swap stations to minimize unnecessary differences". Applying the minimum specifications for swapped batteries can minimize the differences that can harm consumers if there is more than one battery swap brand that consumers can use [63].

Three indicators were removed in the latent construct of stakeholder protection because B2, B3, and B5 can represent them, and each stakeholder can represent more than one perspective [22]. The removed indicators were as follows:

- B1 (The application of the battery swap test standard is expected to protect the interests of the government)
- B4 (The application of the battery swap test standard is expected to protect the interests of battery swap manufacturers)
- B6 (The application of the battery swap test standard is expected to protect the interests of electric motorcycle users)

Meanwhile, two indicators were removed in the latent construct of SNI implementation. These indicators included C1.2 (Battery test standards contain equipment constructional requirements) and C1.3 (Battery test standards contain electromagnetic compatibility). The question for C1.2 and C1.3 is a question of redundancy that contains the effects of the equipment constructional requirements and electromagnetic compatibility constructs on the SNI implementation construct, which can be calculated during model analysis in SEM. Therefore, the elimination of C1.2 and C1.3 does not affect the meaning of the SNI implementation construct.

Furthermore, we removed several indicators from the remaining constructs. The elimination of these indicators was based on the survey conducted at the lithium battery R&D center in Indonesia. This elimination indicates that battery swap stakeholders in Indonesia have not completely fulfilled the requirements stated in these indicators. However, several requirements can be fulfilled, but the stakeholders have not followed the reference standard rules. For example, C2.1 was removed because stakeholders in Indonesia have developed a battery that is safe against electric shock but is not compliant with IEC 60204-1:2016. C2.3 was removed because stakeholders have developed a battery that protects SBS charging equipment but is not compliant with IEC 61851-23:2014. Table 15 shows the reference standards that stakeholders have not fulfilled for each removed indicator.

Removed Indicators Construct Standards C2.1 IEC 60204-1:2016 C2.3 IEC 61851-23:2014 C2.5 IPXXB C2.6 **IPXXB** Protection against electric shock C2.7 IEC 60364-4-41: 2005+AMD: 2017 CSV C2.8 IEC 60364-4-41:2005 IEC 60364 series, IEC 60479 series, IEC TR 60755:2017, C2.11, C2.12 IEC 61008 series, IEC 61009 series, IEC 60947-2 IEC 61439-1:2011 C3.1 C3.2 IEC 60947-3:2008+AMD1:2012+AMD2:2015 CSV IEC 60947-4-1:2018 C3.3 C3.9 IEC 62262:2002 Equipment constructional C3.12 IEC 61439-1:2011 requirements C3.13 IEC 60695-2-11 C3.14 IEC 60695-10-2 C3.15 IEC 60112:2003+AMD1:2009 CSV IEC 61439-1:2011 C3.16 C4.1 IEC 61000 series, IEC 61851-21-2:2018 Electromagnetic compatibility

Table 15. Unfulfilled reference standards.

5.1.2. Convergent Validity of Constructs

A construct is valid if its Cronbach's alpha value is above 0.5 for new untested instruments [58]. In this study, all constructs had values above 0.5. Therefore, it can be said that all constructs are valid.

5.1.3. Discriminant Validity

Discriminant validity shows that a construct is different from other constructs, is unique, and captures phenomena not captured by other constructs. Discriminant validity at the construct level was determined by comparing the \sqrt{AVE} value of a construct with the construct's correlation with other constructs. The \sqrt{AVE} value for each construct must be greater than the correlation value between constructs and other constructs. This assessment

is based on the Fornell–Larcker criteria [58]. In this study, the \sqrt{AVE} value of a construct had the most significant value compared to the correlation values between constructs and other constructs. Thus, this research can be considered valid.

5.2. SEM inner Model Analysis

5.2.1. Collinearity Assessment

Collinearity assessment uses the provision that if the *VIF* value is more than five, then latent variable collinearity occurs. This study found no collinearity assessment with a VIF value below five.

5.2.2. Path Value and Significance

The path value and significance test the significance level of a path coefficient via the bootstrap procedure. The minimum path coefficient value is 0.2, and it is ideally greater than 0.3 to indicate a meaningful relationship [60]. In this study, the path coefficient value for the electromagnetic compatibility towards SNI implementation was negative.

5.2.3. Coefficient of Determination

The coefficient of determination is a value indicating the variance of the endogenous product caused by all of the exogenous variables connected to it. Chin [60] stated that the value of R^2 is high, medium, and small if it is 0.67, 0.33, and 0.19, respectively. The R^2 value used is the adjusted R^2 value for the model's number of predictors. The R^2 value of SNI implementation was 0.657, categorized as vital, while the R^2 value of the SNI acceptance variable was 0.329, categorized as moderate.

5.2.4. Effect Size f^2

The effect size f^2 was used to evaluate the SEM structural model. In this research, the relationships with a significant influence when an exogenous variable is removed were the relationships of equipment constructional requirements with SNI implementation and of protection against electric shock with SNI implementation. The relationships with moderate influence were the relationships of electromagnetic compatibility with SNI implementation and of marking and instruction with SNI implementation. The relationships with little influence were those of SNI implementation with SNI acceptance and of stakeholder protection with SNI acceptance.

5.2.5. Predictive Relevance

When the SEM path model shows predictive relevance, the path model can accurately predict data that are not used in evaluating the model. This study has a predictive relevance of 0.540 to the SNI implementation variable and of 0.180 to the SNI acceptance.

5.2.6. Effect Size q^2

Effect size q^2 was used to determine the exogenous effect on the Q^2 value of endogenous variables. In this study, the q^2 value was 0.1922, meaning that removing one of the exogenous variables in the pathway model has moderate predictive relevance for certain endogenous constructs.

5.2.7. Hypothesis Test

A hypothesis test was conducted by comparing the *t*-table and *t*-value. The research hypothesis is accepted if the *t*-value is greater than the *t*-table. In this study, all hypotheses were accepted.

5.3. Policy Implications

The findings and outputs obtained from this research can be used as a policy brief for the development of standards and to support the provision of recommendations and options in formulating policies related to the charging and exchange infrastructure for electric vehicle batteries. The results of this study can provide input for the draft SNI battery swap concept to the technical committee in charge of developing the SNI. Thus, this study can be used as a basis for considering the selection of standard parameters and is expected to support the effectiveness of standard development until the SNI is officially formulated.

This research is consistent with the principles of SNI formulation, namely, openness and consensus. It involves interested parties in the standardization of electric vehicles, including the government, battery swap R&D, battery swap laboratories, battery swap manufacturers, electric motorcycle manufacturers, and electric motorcycle users. We are open to these stakeholders so that they know about the SNI development program, and we provide equal opportunities for them to participate in the formulation of this SNI by exploring their opinions and needs related to battery swap standards and accommodating their needs in determining standard parameters. With this participation, the parties involved become aware of the importance of the current problem, so it is expected that in the future they would be willing to adopt the SNI that has been formulated and participate in the success of the electric vehicle acceleration program in Indonesia. Thus, this research supports the climate for developing electric vehicle policies and encourages the acceptance of the SNI in the community.

The dynamics of open innovation are an important aspect to pay attention to in early standardization. The engagement of various parties—such as industry, government, society, academics, and developers—comprises the interaction required in developing a standard battery swap. The engagement of stakeholders can enhance the effectiveness and capability of the early standardization process. Therefore, it can better facilitate the product development process of battery swaps.

6. Conclusions

An SNI for battery testing that is globally competitive was designed through data processing with the FACTS method, referring to international standards, namely, the IEC 62840-2: 2016 standard regarding Electric Vehicle Battery Swap Systems–Part 2: Safety Requirements. Test variables in the SNI battery test include protection against electric shock, equipment constructional requirements, electromagnetic compatibility, and marking and instruction. The SNI for battery swap testing was designed through data processing validation using SEM.

The proposed constructs—i.e., electromagnetic compatibility, equipment construction requirements, marking and instruction, and protection against electric shock—positively affect SNI implementation. Meanwhile, the SNI implementation, national uniqueness, and stakeholder protection positively affect SNI acceptance. Therefore, it can be said that SNI acceptance can be obtained by considering SNI implementation, national identity, and stakeholder protection. An SEM model was designed for formal acceptance through the development of the technology acceptance model (TAM), which considers the variables of perceived ease of use, perceived usefulness, and attitudes towards use.

The validation results using SEM indicate that all hypotheses were accepted. Because all of the hypotheses were proven correct, the research framework that was developed by applying FACTS and SEM can be used for early standardization. This means that the standardization of each process should accompany the development of battery swap products.

Standardization as a catalyst of open innovation has shown through analysis that implementation, national uniqueness, and stakeholder protection positively affect SNI acceptance. The open innovation approach was considered to integrate a FACTS and SEM approach to generate significant parameters of swappable battery standards. Further research of open innovation and standardization will be more complex not only for swappable batteries, but also for smart connected products. Thus, interoperability of standardization is a crucial area for further study. **Author Contributions:** Conceptualization, W.S. and F.F.; methodology, W.S., D.P. and E.P.; software, D.P.; validation, W.S., D.P. and F.F.; formal analysis, D.P.; data curation, D.P.; writing—original draft preparation, W.S., D.P., A.R. and T.O.K.; writing—review and editing, W.S., D.P., A.R. and T.O.K.; supervision, W.S. and E.P.; project administration, W.S. and F.F.; funding acquisition, W.S. All authors have read and agreed to the published version of the manuscript.

Funding: This research was partially supported by the LPPM (Institute for Research and Community Service) Universitas Sebelas Maret under the "*Program Flagship Prioritas Riset Nasional Untuk Perguruan Tinggi*" Program FY 2021 (Contract no.: 2883/UN27.22/PT.01.03/2021).

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Not applicable.

Acknowledgments: The authors would like to thank Universitas Sebelas Maret for supporting this research.

Conflicts of Interest: The authors declare no conflict of interest.

References

- Statistics Indonesia Number of Motor Vehicle by Type (Unit), 2018–2020. Available online: https://www.bps.go.id/indicator/17 /57/1/jumlah-kendaraan-bermotor.html (accessed on 18 June 2020).
- 2. Prianjani, D.; Sutopo, W.; Hisjam, M.; Pujiyanto, E. Sustainable supply chain planning for swap battery system: Case study electric motorcycle applications in Indonesia. *IOP Conf. Ser. Mater. Sci. Eng.* **2019**, 495, 12081. [CrossRef]
- 3. Government of the Republic of Indonesia. Acceleration of Battery-Based Electric Motorized Vehicles for Battery Electric Vehicle for Road Transportation; Government of the Republic of Indonesia: Jakarta, Indonesia, 2019.
- Sutopo, W.; Aqidawati, E.F. Learning a Supply Chain Management Course by Problem Based Learning: Case Studies in the Newspaper Industry. In Proceedings of the International Conference on Industrial Engineering and Operations Management, Bangkok, Thailand, 5–7 March 2019; pp. 5–7.
- Government of the Republic of Indonesia Laws of the Republic Indonesia Number 20 of 2014 about Standardization and Assessment of Compatibility. Available online: https://www.bsn.go.id/uploads/download/UU-20_TAHUN_2014_TENTANG_ SPK1.pdf (accessed on 10 March 2019).
- 6. Ministry of Trade of the Republic of Indonesia. *Final Report of the Standard Needs Assessment in the Dimensions of Competitiveness and Consumer Protection;* Ministry of Trade of the Republic of Indonesia: Jakarta, Indonesia, 2013.
- 7. Stella, J. The Problem with Early Standardization. Available online: https://bit.ly/31pNznM (accessed on 17 June 2020).
- 8. Riitta, S. Managing Change towards Lean Enterprises. Int. J. Oper. Prod. Manag. 1994, 14, 66–82. [CrossRef]
- Fadillah, H.; Jusuf, A.; Santosa, S.P.; Dirgantara, T. Li-ion NCA Battery Safety Assessment for Electric Vehicle Applications. In Proceedings of the 2018 5th International Conference on Electric Vehicular Technology (ICEVT), Surakarta, Indonesia, 30–31 October 2018; pp. 172–178.
- 10. McNerney, J.; Needell, Z.A.; Chang, M.T.; Miotti, M.; Trancik, J.E. TripEnergy: Estimating Personal Vehicle Energy Consumption Given Limited Travel Survey Data. *Transp. Res. Rec. J. Transp. Res. Board* 2017, 2628, 58–66. [CrossRef]
- 11. Needell, Z.A.; Trancik, J.E. Efficiently Simulating Personal Vehicle Energy Consumption in Mesoscopic Transport Models. *Transp. Res. Rec. J. Transp. Res. Board* **2018**, 2672, 163–173. [CrossRef]
- 12. Sutopo, W.; Rahmawatie, B.; Fahma, F.; Nizam, M.; Purwanto, A.; Louhenapessy, B.B.; Kadir, E.A. A technical review of BMS performance standard for electric vehicle applications in Indonesia. *Telkomnika* **2018**, *16*, 544–549. [CrossRef]
- 13. Sutopo, W.; Kadir, E.A. Designing framework for standardization case study: Lithium-ion battery module in electric vehicle application. *Int. J. Electr. Comput. Eng.* **2018**, *8*, 220. [CrossRef]
- 14. Trancik, J.E. Renewable energy: Back the renewables boom. Nature 2014, 507, 300–302. [CrossRef]
- 15. Ahmed, M.; Kim, Y.-C. Energy Trading with Electric Vehicles in Smart Campus Parking Lots. Appl. Sci. 2018, 8, 1749. [CrossRef]
- 16. Chen, P.-T.; Shen, D.-J.; Yang, C.-J.; Huang, K.D. Development of a Hybrid Electric Motorcycle that Accords Energy Efficiency and Controllability via an Inverse Differential Gear and Power Mode Switching Control. *Appl. Sci.* **2019**, *9*, 1787. [CrossRef]
- 17. Hu, J.; Jiang, X.; Jia, M.; Zheng, Y. Energy Management Strategy for the Hybrid Energy Storage System of Pure Electric Vehicle Considering Traffic Information. *Appl. Sci.* **2018**, *8*, 1266. [CrossRef]
- Lee, H.-J.; Cha, H.-J.; Won, D. Economic Routing of Electric Vehicles using Dynamic Pricing in Consideration of System Voltage. *Appl. Sci.* 2019, *9*, 4337. [CrossRef]
- 19. Long, Y.; Zhang, Y.; Sun, H.; Hou, X.; Xiao, J. A Developed Vehicle Terminal of Time-Sharing Rental Electric Vehicle Using Acoustic Communication Technology. *Appl. Sci.* 2019, *9*, 5408. [CrossRef]
- Oldenbroek, V.; Smink, G.; Salet, T.; van Wijk, A.J.M. Fuel Cell Electric Vehicle as a Power Plant: Techno-Economic Scenario Analysis of a Renewable Integrated Transportation and Energy System for Smart Cities in Two Climates. *Appl. Sci.* 2019, 10, 143. [CrossRef]

- 21. Sutopo, W.; Astuti, R.W.; Suryandari, R.T. Accelerating a Technology Commercialization; with a Discussion on the Relation between Technology Transfer Efficiency and Open Innovation. J. Open Innov. Technol. Mark. Complex. 2019, 5, 95. [CrossRef]
- Witherell, P.; Rachuri, S.; Narayanan, A.; Lee, J.H. FACTS: A Framework for Analysis, Comparison, and Testing of Standards; Systems Integration Division Engineering Laboratory, US Department of Commerce: Washington, DC, USA, 2013.
- Aristyawati, N.; Fahma, F.; Sutopo, W.; Purwanto, A.; Nizam, M.; Louhenapessy, B.B.; Mulyono, A.B. Designing framework for standardization and testing requirements for the secondary battery a case study of lithium-ion battery module in electric vehicle application. In Proceedings of the 2016 2nd International Conference of Industrial, Mechanical, Electrical, and Chemical Engineering (ICIMECE), Yogyakarta, Indonesia, 6–7 October 2016; pp. 207–212.
- 24. Pratiwi, R.A.; Fahma, F.; Sutopo, W.; Pujiyanto, E.; Ayundyahrini, M. Designing Parameter for Developing Standard of Manual Wheelchair. *Int. J. Appl. Sci. Eng.* 2018, 15, 127–134.
- Prianjani, D.; Fahma, F.; Sutopo, W.; Nizam, M.; Purwanto, A.; Louhenapessy, B.B.; Mulyono, A.B. The standard development for the National Standard of Indonesian (SNI) of the cell traction battery Lithium-ion Ferro phospate secondarry for electric vehicles applications. In Proceedings of the 2016 2nd International Conference of Industrial, Mechanical, Electrical, and Chemical Engineering (ICIMECE), Yogyakarta, Indonesia, 6–7 October 2016; pp. 213–218.
- Rahmawatie, B.; Sutopo, W.; Fahma, F.; Purwanto, A.; Nizam, M.; Louhenapessy, B.B.; Mulyono, A.B. Designing framework for standardization and testing requirements of battery management system for electric vehicle application. In Proceedings of the 2017 4th International Conference on Electric Vehicular Technology (ICEVT), Bali, Indonesia, 2–5 October 2017; pp. 7–12.
- 27. Pīlēna, A.; Mežinska, I.; Lapiņa, I. Standardization as a Catalyst for Open and Responsible Innovation. *J. Open Innov. Technol. Mark. Complex.* **2021**, *7*, 187. [CrossRef]
- 28. Chesbrough, H. Open innovation: A new paradigm for understanding industrial innovation. *Open Innov. Res. New Paradig.* **2006**, 400, 1–19.
- 29. West, J.; Gallagher, S. Challenges of open innovation: The paradox of firm investment in open-source software. *R&D Manag.* 2006, *36*, 319–331.
- 30. Kaplan, D. Structural Equation Modeling: Foundations and Extensions; Sage Publications: New York, NY, USA, 2008; Volume 10, ISBN 1452245126.
- 31. Kline, R.B. Principles and Practice of Structural Equation Modeling, 3rd ed.; Guilford: New York, NY, USA, 2011.
- Ghozali, I.; Latan, H. Partial Least Squares Konsep, Teknik dan Aplikasi Menggunakan Program Smartpls 3.0 Untuk Penelitian Empiris; Badan Penerbit UNDIP: Semarang, Indonesia, 2015.
- Pfoser, S.; Schauer, O.; Costa, Y. Acceptance of LNG as an alternative fuel: Determinants and policy implications. *Energy Policy* 2018, 120, 259–267. [CrossRef]
- Qi, W.H.; Qi, M.L.; Ji, Y.M. The effect path of public communication on public acceptance of nuclear energy. *Energy Policy* 2020, 144, 111655. [CrossRef]
- Zaman, S.; Wang, Z.; Rasool, S.F.; uz Zaman, Q.; Raza, H. Impact of critical success factors and supportive leadership on sustainable success of renewable energy projects: Empirical evidence from Pakistan. *Energy Policy* 2022, 162, 112793. [CrossRef]
- Will, C.; Schuller, A. Understanding user acceptance factors of electric vehicle smart charging. *Transp. Res. Part C Emerg. Technol.* 2016, 71, 198–214. [CrossRef]
- 37. Nosi, C.; Pucci, T.; Silvestri, C.; Aquilani, B. Does Value Co-Creation Really Matter? An Investigation of Italian Millennials Intention to Buy Electric Cars. *Sustainability* **2017**, *9*, 2159. [CrossRef]
- Globisch, J.; Dütschke, E.; Schleich, J. Acceptance of electric passenger cars in commercial fleets. *Transp. Res. Part A Policy Pract.* 2018, 116, 122–129. [CrossRef]
- 39. Prianjani, D.; Sutopo, W.; Pujiyanto, E.; Fahma, F. Designing framework for standardization and testing requirements of battery swap for electric motorcycle application in Indonesia. *Int. J. Appl. Sci. Eng.* **2018**, *15*, 141–148.
- Wang, N.; Tang, L.; Pan, H. Analysis of public acceptance of electric vehicles: An empirical study in Shanghai. *Technol. Forecast.* Soc. Chang. 2018, 126, 284–291. [CrossRef]
- 41. Zhao, X.; Ma, Y.; Shao, S.; Ma, T. What determines consumers' acceptance of electric vehicles: A survey in Shanghai, China. *Energy Econ.* **2022**, *108*, 105805. [CrossRef]
- 42. Adu-Gyamfi, G.; Song, H.; Obuobi, B.; Nketiah, E.; Wang, H.; Cudjoe, D. Who will adopt? Investigating the adoption intention for battery swap technology for electric vehicles. *Renew. Sustain. Energy Rev.* **2022**, *156*, 111979. [CrossRef]
- 43. Gulzari, A.; Wang, Y.; Prybutok, V. A green experience with eco-friendly cars: A young consumer electric vehicle rental behavioral model. *J. Retail. Consum. Serv.* 2022, 65, 102877. [CrossRef]
- 44. Rauter, R.; Globocnik, D.; Perl-Vorbach, E.; Baumgartner, R.J. Open innovation and its effects on economic and sustainability innovation performance. *J. Innov. Knowl.* **2019**, *4*, 226–233. [CrossRef]
- 45. Chesbrough, H.W.; Appleyard, M.M. Open innovation and strategy. Calif. Manage. Rev. 2007, 50, 57–76. [CrossRef]
- 46. Yun, J.; Liu, Z. Micro-and Macro-Dynamics of Open Innovation with a Quadruple-Helix Model. *Sustainability* **2019**, *11*, 3301. [CrossRef]
- 47. Yun, J.J.; Zhao, X.; Jung, K.; Yigitcanlar, T. The culture for open innovation dynamics. Sustainability 2020, 12, 5076. [CrossRef]
- Perkmann, M.; Walsh, K. University-industry relationships and open innovation: Towards a research agenda. *Int. J. Manag. Rev.* 2007, 9, 259–280. [CrossRef]

- 49. Jonsson, L.; Baraldi, E.; Larsson, L.-E.; Forsberg, P.; Severinsson, K. Targeting academic engagement in open innovation: Tools, effects and challenges for university management. *J. Knowl. Econ.* **2015**, *6*, 522–550. [CrossRef]
- 50. Striukova, L.; Rayna, T. University-industry knowledge exchange: An Exploratory Study of Open Innovation in UK Universities. *Eur. J. Innov. Manag.* 2015, *18*, 471–492. [CrossRef]
- 51. Huggins, R.; Prokop, D.; Thompson, P. Universities and open innovation: The determinants of network centrality. *J. Technol. Transf.* 2020, 45, 718–757. [CrossRef]
- 52. Sarkar, S.; Costa, A.I.A. Dynamics of open innovation in the food industry. Trends Food Sci. Technol. 2008, 19, 574–580. [CrossRef]
- 53. Bogers, M.; Chesbrough, H.; Heaton, S.; Teece, D.J. Strategic management of open innovation: A dynamic capabilities perspective. *Calif. Manage. Rev.* **2019**, *62*, 77–94. [CrossRef]
- 54. Davis, F.D.; Venkatesh, V. A critical assessment of potential measurement biases in the technology acceptance model: Three experiments. *Int. J. Hum. Comput. Stud.* **1996**, *45*, 19–45. [CrossRef]
- 55. Creswell, J.W.; Creswell, J.D. *Research Design: Qualitative, Quantitative, and Mixed Methods Approaches*; Sage Publications: New York, NY, USA, 2017; ISBN 1506386717.
- IEC 62840-2:2016; Electric Battery Swap System—Part 2: Safety Requirement. International Electrotechnical Commission [IEC]: Geneva, Switzerland, 2016. Available online: https://webstore.iec.ch/publication/25983 (accessed on 17 March 2020).
- 57. National Standardization Body. Pengantar Standardisasi, Edisi Kedua; BSN Jakarta: Jakarta, Indonesia, 2014.
- Fornell, C.; Larcker, D.F. Evaluating structural equation models with unobservable variables and measurement error. *J. Mark. Res.* 1981, 18, 39–50. [CrossRef]
- 59. Hair, J.F.; Ringle, C.M.; Sarstedt, M. PLS-SEM: Indeed a Silver Bullet. J. Mark. Theory Pract. 2011, 19, 139–152. [CrossRef]
- Chin, W.W. The partial least squares approach to structural equation modeling. In *Modern Methods for Business Research*; Psychology Press: London, UK, 1998; Volume 295, pp. 295–336, ISBN1 1135684138. ISBN2 9781135684136.
- 61. Cohen, J. Statistical Power Analysis for the Behavioral Sciences; Lawrence Erlbaum Associates: Hillsdale, NJ, USA, 1988; pp. 20–26.
- 62. Santosa, P.I. Metode Penelitian Kuantitatif: Pengembangan Hipotesis dan Pengujiannya Menggunakan SmartPLS; Andi: Yogyakarta, Indonesia, 2018.
- 63. Wang, W.N.; Li, B.; Wang, Y. Design of Battery Fast-Swap System for Electric Vehicle. *Appl. Mech. Mater.* **2014**, *628*, 190–194. [CrossRef]