

Make Your Publications Visible.

A Service of



Leibniz-Informationszentrum Wirtschaft Leibniz Information Centre

Röper, Johann W. A. et al.

Article — Published Version

Can drones save lives and money? An economic evaluation of airborne delivery of automated external defibrillators

The European Journal of Health Economics

Suggested Citation: Röper, Johann W. A. et al. (2022): Can drones save lives and money? An economic evaluation of airborne delivery of automated external defibrillators, The European Journal of Health Economics, ISSN 1618-7601, Springer Berlin Heidelberg, Vol. 24, Iss. 7, pp. 1141-1150, https://doi.org/10.1007/s10198-022-01531-0

This Version is available at: https://hdl.handle.net/10419/313213

Standard-Nutzungsbedingungen:

Die Dokumente auf EconStor dürfen zu eigenen wissenschaftlichen Zwecken und zum Privatgebrauch gespeichert und kopiert werden.

Sie dürfen die Dokumente nicht für öffentliche oder kommerzielle Zwecke vervielfältigen, öffentlich ausstellen, öffentlich zugänglich machen, vertreiben oder anderweitig nutzen.

Sofern die Verfasser die Dokumente unter Open-Content-Lizenzen (insbesondere CC-Lizenzen) zur Verfügung gestellt haben sollten, gelten abweichend von diesen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.



https://creativecommons.org/licenses/by/4.0/

Terms of use:

Documents in EconStor may be saved and copied for your personal and scholarly purposes.

You are not to copy documents for public or commercial purposes, to exhibit the documents publicly, to make them publicly available on the internet, or to distribute or otherwise use the documents in public.

If the documents have been made available under an Open Content Licence (especially Creative Commons Licences), you may exercise further usage rights as specified in the indicated licence.



ORIGINAL PAPER



Can drones save lives and money? An economic evaluation of airborne delivery of automated external defibrillators

Johann W. A. Röper¹ · Katharina Fischer¹ · Mina Carolina Baumgarten² · Karl Christian Thies³ · Klaus Hahnenkamp² · Steffen Fleßa¹

Received: 24 August 2021 / Accepted: 28 September 2022 / Published online: 30 October 2022 © The Author(s) 2022

Abstract

Background Out-of-hospital cardiac arrest is one of the most frequent causes of death in Europe. Emergency medical services often struggle to reach the patient in time, particularly in rural areas. To improve outcome, early defibrillation is required which significantly increases neurologically intact survival. Consequently, many countries place Automated External Defibrillators (AED) in accessible public locations. However, these stationary devices are frequently not available out of hours or too far away in emergencies. An innovative approach to mustering AED is the use of unmanned aerial systems (UAS), which deliver the device to the scene.

Methods This paper evaluates the economic implications of stationary AED versus airborne delivery using scenario-based cost analysis. As an example, we focus on the rural district of Vorpommern-Greifswald in Germany. Formulae are developed to calculate the cost of stationary and airborne AED networks. Scenarios include different catchment areas, delivery times and unit costs.

Results UAS-based delivery of AEDs is more cost-efficient than maintaining traditional stationary networks. The results show that equipping cardiac arrest hot spots in the district of Vorpommern-Greifswald with airborne AEDs with a response time < 4 min is an effective method to decrease the time to the first defibrillation The district of Vorpommern-Greifswald would require 45 airborne AEDs resulting in annual costs of at least 1,451,160 €.

Conclusion In rural areas, implementing an UAS-based AED system is both more effective and cost-efficient than the conventional stationary solution. When regarding urban areas and hot spots of OHCA, complementing the airborne network with stationary AEDs is advisable.

Keywords AED · Out of hospital cardiac arrest · Drone · Emergency medical care · UAS

Abbreviations

AED Automatic external defibrillator CFR Community first responder CPR Cardiopulmonary resuscitation EMS Emergency medical servicesOHCA Out-of-hospital cardiac arrestUAS Unmanned aerial systems

☑ Johann W. A. Röper jwa.roeper@gmx.de

- Department of General Business Administration and Health Care Management, Faculty of Law and Economics, University of Greifswald, Friedrich-Loeffler-Straße 70, 17489 Greifswald, Germany
- Department of Anesthesiology and Intensive Care Medicine, University of Greifswald, Ferdinand-Sauerbruch-Straße, 17489 Greifswald, Germany
- Department of Anesthesiology and Critical Care, EvKB, Bielefeld University Hospitals, Burgsteig 13, 33617 Bielefeld, Germany

Introduction

Out-of-hospital cardiac arrest (OHCA) is one of the most frequent causes of death in developed countries. In 2019, Germany recorded an incidence of 118.5 OHCA patients per 100,000 inhabitants [1, 2]. A comparison to other European countries shows that much lower mortality rates with the more favourable patient outcome can be achieved, given the right measures are taken [3]. This strongly points to a need for action and an assessment of alternatives for German emergency medical services (EMS).



OHCA occurs when the pumping function of the heart suddenly stops and blood circulation ceases. As a result, vital organs, e. g. the brain, are no longer supplied with oxygen and loose viability [4]. Therefore, immediate treatment of OHCA is critical to achieve higher chances of a positive outcome for the patient. To ensure oxygen supply, it is important to perform cardiopulmonary resuscitation (CPR) as quickly as possible. In case of shockable rhythms, defibrillation can stimulate the natural heart function. Therefore, automatic external defibrillators (AED) can help in improving OHCA outcome [5], if applied promptly.

In urban areas, the probability of survival of an OHCA is higher than in rural areas. On the one hand, the probability of OHCA being witnessed is higher in urban regions. On the other hand, EMS response times are shorter. In rural areas with low population density the EMS response time are much longer; the low population density in rural areas does not allow for a higher number of EMS stations. Furthermore, terrain (e.g. mountains, rivers or lakes) challenges access speed, as rural traffic infrastructure is often less developed compared to urban regions. This calls for innovative solutions in pre-hospital care for rural areas [6–8].

Over the last decades, a number of approaches have been implemented to reduce the therapy-free interval and the time to the first defibrillation in OHCA. Amongst these are telephone or video-assisted Cardiopulmonary Resuscitation (CPR) [9–11], Community-First-Responder (CFR)[12] concepts as well as extensive networks of publicly accessible AEDs. For example, Denmark, Sweden, and the Netherlands have already installed stationary AED networks to achieve short defibrillation intervals [13].In Germany, however, existing AEDs are often neither strategically distributed, nor available 24/7 [14].

Stationary AED networks face several functional challenges. Most people who witness cardiac arrest do not know the location of the nearest AED and have to pick it up on foot. Consequently, the access time to the device can be quite long and binds first-responding capacities, which may be needed to perform CPR. The accessibility problem can be relaxed to a certain degree by digitizing and mapping the networks [15, 16]. Still, accessibility often depends on the opening hours of the site where devices are placed. Because AEDs are frequently stolen or damaged, they are kept in safe places, e.g. in the office of facility managers. However, opening hours limit the AED's accessibility to first-responders, further reducing the stationary AED's benefits in OHCA situations. Increasing the number of stationary AEDs does not necessarily solve the problem of access outside office hours.

An innovative approach to overcome the disadvantages of stationary AED networks could be their mobilization with the help of modern technology. This requires a device that could deliver the AED with high speed to any place on demand 24 h a day at a cost lower than that of existing airborne solutions, such as helicopters [17]. Unmanned aircraft systems (UAS), are a possible way to deliver AEDs to the site of a cardiac arrest and not having first responders retrieve them in the first place [18]. It has been shown that UAS networks for AED provision can significantly reduce the time to first defibrillation [19, 20].

Besides the proven medical benefits of timely AED delivery by UAS, operating UAS-networks has also been rated as cost effective. A study published by Bauer et al. [21] rated the primary outcome of operating UAS networks by using the incremental cost-effectiveness-ratio (ICER). The ICER was calculated by the ratio of financial costs to additional life years gained compared to current EMS outcomes. In three scenarios, the coverage of a certain rural area by 80%, 90% and 100% by a UAS network was evaluated, with results showing live-saving potential and cost-effectiveness for any modelled area coverage. ICER ranged between 12.158 \in and 23.568 \in with life years gained between 1477 and 1933 years in annual average.

The results by Bauer et al. [21] are especially important to evaluate the cost-effectiveness of UAS networks in terms of additional life years gained. However, little is known about the cost-systematic of operating the necessary network of drones. Further, a comparison of the UAS network as the innovation to stationary AED-networks, representing the existing and widely used solution, has not been undertaken as of yet.

In this paper, we would like to close this research gap by comparing the cost-effectiveness of both systems. In the next section, we develop the cost functions for both alternatives. We evaluate their effectiveness by comparing their cost to the AED's access time. Afterwards, we will present the respective results and discuss the findings. The paper closes with recommendations for the German EMS.

Methods

Setting

This study aims to evaluate and improve the efficient supply of AEDs for the response to OHCA. Using a scenario-based approach to cover possible uncertainties, we compared the UAS-supported AED delivery to the common stationary network regarding their cost and efficiency in a rural district.

As time is of outstanding importance in achieving favourable OHCA outcomes, we use the delivery time of AEDs as the main impact factor of an AED system's efficiency. Using clinical outcomes such as DALYs or QALYs would be preferable, however, they are not available as of yet. Therefore, time is represented as a physical outcome in this analysis as an accepted and widely used [22–24] factor in



cost-effectiveness analysis. We calculate the cost-effectiveness by comparing the yearly costs with the respective effectiveness of the alternatives.

The analytical planning period to calculate the cost of operating an AED system is set to one year. This gives us the yearly costs (including annual depreciation acc. to straightline method) of every scenario. We choose this period to achieve comparability between the introduced scenarios. This time horizon is used as the analytical frame, which we use to develop further assumptions that form our scenario analysis.

Our analysis is based on the research project MVILIFEIDRONE—Pilot [25] in the district of Vorpommern-Greifswald in the state of Mecklenburg-Vorpommern in North-Eastern Germany. The research group MVILIFEIDRONE evaluates the feasibility of UAS-based AED delivery since 2019 and works on the implementation of drones to innovate medical transports.

With an area of 3930 km² and a population of some 236,600 (2019), the district of Vorpommern-Greifswald is rural, sparsely populated and peripheral for German standards. Consequently, the results of this analysis can be representative of other rural areas and may also give implications for peri-urban and urban settings.

Analysis

Cost modelling

This analysis assumes a cost function with interval-fixed costs to evaluate the total and unit costs per km² covered by AED services. [26] To determine the size of a provisioned area, which depends on the delivery time of the AED, and the number of AED locations, a Christaller comb pattern is applied [27]. The Christaller comb is a very formal approach, whose practical applicability can be considered critically in principle. However, there is no existing AED system in the region of experience or generally in Germany [14]. Few AEDs are deployed in Germany, their location is neither mapped or systematically structured—we cannot speak of a functional AED network. Therefore, to establish an AED network especially in rural areas, building pads for both mobile and stationary AED from scratch seems feasible and necessary. Our approach is to supply a specific area with AEDs, regardless of the population within. This corresponds to German healthcare practice, which aims to achieve an equal supply of health services in any place. This leads to the premise to operate the same amount of AEDs in a given area.

Every AED's location has an operational radius that limits the distance which can be covered within a specific response time. To avoid both overlapping and unsupplied areas of provision, the circle's curves are formed into lines, creating a hexagonal structure around the AED's location. On adjoining hexagons borders, the distance to either hexagon's centre, where the AEDs are placed, is exactly the same. Finally, the total costs to provide an AED network covering a given region are calculated by multiplying the number of hexagons, thus the number of necessary AEDs, with the cost per AED unit [26]. The hexagonal approach can be applied to both stationary and airborne AED networks.

Formula (3) calculates the stationary AED's operational radius r_s . The outward and return journeys of a first responder are taken into account, which halves the stationary AED's operational range. A stationary AED's operational range is further reduced by detours that have to be walked to retrieve the device. The airborne AED operational radius r_m , calculated by (7), only includes the outward journey as retrieval by first responders is not necessary. In contrast, UAS can minimize distances by flying the shortest way by Euclidean distance. However, times for the UAS to take off and land have to be taken into account.

The catchment areas $A_{s,m}$ for both stationary (2) and airborne AEDs (6) are calculated by radian measure and depend on their operational radii. [28] Total costs result by multiplying the unit costs with the number of AEDs needed to provide sufficient area coverage. The number of AED units is calculated by a trunc function, which gives the next higher integer of the number of AED locations.

Based on experiences made in MVILIFEIDRONE, we assume a higher technical failure risk associated with using UAS, e.g. due to crashes, technical failures or high winds. Consequently, this model assumes UAS being redundantly provisioned at a rate of 50%. This firstly ensures a high availability and balances possible deficits in technical maturity. Secondly, we assume a very conservative estimation, as data on the availability and reliability of medical UAS is neither available nor researched as of yet. Following the explanations above, the cost functions of stationary AEDs are as follows:

$$K_s = k_s \cdot trunc\left(\frac{x}{A_s}\right) \tag{1}$$

For total costs, with

$$A_s = 3 \cdot r_s^2 \cdot \sin(60) \tag{2}$$

for one stationary AED's hexagonal catchment area and

$$r_s = \frac{\left(d - a_s\right) \cdot b_s}{2} \tag{3}$$

for the operational radius.



Total costs for the coverage of a given area are, therefore, calculated as

$$K_s = k_s \cdot trunc \left[\frac{x}{3 \cdot \left(\frac{(d - a_s) \cdot b_s}{2} \right)^2 \cdot \sin(60)} \right]$$
 (4)

Total costs for airborne AEDs can be calculated as

$$K_{m} = k_{m} \cdot trunc\left\{ \left(trunc\left[\frac{x}{A_{m}}\right] \right) \cdot 1, 5 \right\}$$
 (5)

for total costs, with

$$A_m = 3 \cdot r_m^2 \cdot \sin(60) \tag{6}$$

to calculate the UAS' hexagonal catchment area and

$$r_m = (d - a_m) \cdot b_m \tag{7}$$

for the UAS´ operational radius, which determines the size of the hexagon.

Total stationary costs, therefore, are calculated as

$$K_{m} = k_{m} \cdot trunc \left\{ \left(trunc \left[\frac{x}{3 \cdot \left\{ \left(d - a_{m} \right) \cdot b_{m} \right\}^{2} \cdot \sin \left(60 \right)} \right] \right) \cdot 1, 5 \right\}$$
(8)

The models determinants are Variable: Parameter; $A_{m,s}$: Catchment area; a_s : time to find the AED; a_m : time to take off and land the UAS; b_s : Speed of a brisk walk; b_m : Speed of a UAS; d: response time; k_s : unit costs stationary AED; k_m : unit costs airborne AED; x: Area covered; k_s : Total costs area coverage with stationary AEDs; k_m : Total costs area coverage with airborne AEDs.

Fixed costs for either scenario comprise of the acquisition cost of the UAS and the AED. Costs for the UAS-pad as a fully automated ground station are integrated as well as costs for installing a stationary publicly accessible AED. Maintenance cost, which has to be conducted regularly, is regarded as sunk cost and therefore integrated into the fixed costs for both airborne and stationary solutions. Due to the high and still rising degree of automation we experienced in our field project MVILIFEIDRONE, personnel cost for piloting are not considered. In fact, they will presumably further lose in importance.

Variable costs generally depend on the cost per AED's use. For stationary AEDs, the variable costs consist of the cost of the battery and the electrodes. In the case of airborne AEDs, the costs of charging the UAS' battery would have to be added. However, considering their probable utilization, the variable costs of using the stationary or airborne AEDs are low. They can be regarded as non-relevant for decision-making and are therefore neglected.



In the second step, to illustrate the impact of different unit costs and response times on results, a sensitivity analysis is conducted. By keeping all but one model determinant constant, it gives the highest possible cost of an airborne AED scenario, that equates the cost of the stationary scenario, or vice versa. In this course, the response time d and the unit costs k_s and k_m of each scenario are regarded.

$$\begin{split} \overline{K_s}\left(\overline{k_s}, \overline{d}, \overline{a_s}, \overline{b_s}, \overline{x}\right) \\ &= k_m \cdot trunc \left\{ trunc \left[\frac{\overline{x}}{3 \cdot \left\{ \left(\overline{d} - \overline{a_m}\right) \cdot \overline{b_m} \right\}^2 \cdot \sin{(60)}} \right] \right\} \cdot 1, 5 \right\} \end{split}$$

$$\overline{K_m}\left(\overline{k_m}, \overline{d}, \overline{a_m}, \overline{b_m}, \overline{x}\right) = k_s \cdot trunc \left[\frac{\overline{x}}{3 \cdot \left\{ \frac{\left(\overline{d} - \overline{a_s}\right) \cdot \overline{b_s}}{2} \right\}^2 \cdot \sin\left(60\right)} \right]$$

Scenarios and data

As shown above, there are two ways to maintain AED networks to provide medical aid in early OHCA treatment: Stationary AEDs illustrate a conventional approach, whereas UAS-based airborne AEDs are an innovative solution. Stationary and airborne AEDs form two overarching scenarios of AED provision, onto which three variations are applied. These scenario variations are developed to understand the effects of different inputs, to cover the uncertainty of the data and thus to secure a sound decision-making. We apply the following scenario variations:

- Scenario variation I shows two alternatives to provide the region of Vorpommern-Greifswald with AEDs: either covering the whole county or identifying and concentrating on historical hot spots of OHCA
- Scenario variation II varies the medical-induced response time, which is an AED network's primary determinant,
- Scenario variation III varies unit costs of both stationary and airborne AED infrastructure.

For all scenarios modelled in this study, we assumed a brisk travelling speed for every first responder retrieving a stationary AED on foot of 0, 1 km/min. For UAS, we used an average speed of 60 km/h, which is the speed of the UAS used in the MVILIFEIDRONE – Pilot project.






Fig. 1 Costs for hot psot coverage. Own source

This average speed takes into account the time-consuming manoeuvres for take-off and landing.

Scenario variation I: covered area

The variation in area coverage resulted from data provided by the LandlRettung project. To increase the outcome of OHCAs, the project documented all OHCA cases between September 2017 and September 2019 in the district of Vorpommern-Greifswald. Using this data, hot spots with at least twelve OHCA cases within this period were identified.

Supplementary Fig. 1 shows a heat map of all recorded OHCA in Vorpommern-Greifswald. These form the underlying base for the definition of focal points, counting 409 of the 555 emergencies between 2017 and 2019. Retrospectively, almost 75% of all OHCA cases could therefore have been covered by concentrating only on a fraction of the expanse of the exemplary region. This results in two different sized areas, constituting scenario variations 1 and 2: The entire area of Vorpommern Greifswald (3930 km²) and the limited area of the focal points, as shown in Fig. 1 (680.4 km²).

Scenario variation II: response time

According to the state law of Mecklenburg-Vorpommern on the provision of emergency medical services, the legal response time for EMS is 8:55 min on average [29]. However, these response times are frequently exceeded [30]. To legitimate an AED network, the delivery time of AEDs in OHCA must undercut and improve the status quo. Therefore, modelled response times vary between three and eight minutes—from very favourable to less favourable assumptions. A response time less than three minutes does not seem feasible.

Scenario variation III: unit costs

To cover insecurities concerning unit costs, input data are varied. For the stationary AEDs, the costs for different AED types were acquired by research. The cheapest, the most expensive, and an average price were used to depict possible cost variations. The assumed lifetime of an AED is 10 years with a linear depreciation. For the UAS costings based on the results of the MVILIFEIDRONE project were added to the mean value of unit costs of an AED. Surmising ongoing technical development and the relatively simple UAS used in MVILIFEIDRONE, these known costs form the bottom line of the assumed cost scale, which assumes two further and higher values.

Industry-grade octocopter-type UAS can be acquired for $127,500 \in$. System lifetime is assumed to be 4 years and charging cost is set at $100 \in$. We assume a linear depreciation of the UAS over its lifetime. Equipped with an AED of medium cost, costs per year in the base scenario are 32,248 \in (Table 1).



Table 1 Model inputs. Own source

Scenario 1: Stat Scenario 2: Aer	•					
Scenario variation I	Scenario variation II					Scenario varia- tion III
Covered area in km ²	Response time <i>d</i> [min]		Catchment area Number of A [km ²]	EDs a_s ; a_m [min]	<i>b_s</i> ; <i>b_m</i> [km/ min]	Costs per unit [€ p.a.]
Full area coverage [3930 km ²]	a. 3 b. 4 c. 5	$r_s = \frac{(d-a_s) \cdot b_s}{2}$	$A_s = 3 \cdot r_s^2 \cdot \sin(60) trunc\left(\frac{x}{A_s}\right)$	1 min	0.1 km/min	a.170 € b.263 € c.405 €
Focal points [680.4 km ²]	d. 6 e. 7 f. 8	$r_m = (d - a_m) \cdot b_m$	$A_{m} = 3 \cdot r_{m}^{2} \cdot \sin(60) \ trunc \left(\left[trunc \left(\frac{\lambda}{A_{n}} \right) \right] \right)$ $\cdot 1.5)$	$\left(\frac{c}{m}\right)$ 1 min	1 km/min	a. 32,248 € b. 45,000 € c. 55,000

Results


Scenario 1: stationary AED

Table 2 shows both the total costs for the stationary AED scenario at full area coverage and focal point setting, depending on the variation of the response time and the unit costs. Increasing (decreasing) the response time enlarges (reduces) the radius of the catchment area and therefore reduces (increases) the number of AEDs required to cover the area of Vorpommern-Greifswald. Thus, the associated costs of covering a specific area decrease (response time $\uparrow \rightarrow$ radius $\uparrow \rightarrow$ catchment area $\uparrow \rightarrow$ number of required AEDs $\downarrow \rightarrow$ costs of area coverage \downarrow).

To equip the full area of Vorpommern-Greifswald with stationary devices, between 12,349 and 151,266 AEDs are needed, depending on the response time as depicted in scenario variation II. If the analysis focuses on the hot spots, only between 2,138 and 26,189 AEDs are required for sufficient provision, again depending on the response time. As can be expected, increasing unit costs impact total costs in both a total coverage and focal point setting. The total costs for area coverage with stationary AEDs lie between 2,099,330 € and 61,262,730 €. When considering the hot spots, the total costs per year are set between 363,460 € and 10,606,545 € depending on the unit costs and the response time.

Scenario 2: airborne AED

Besides the results for scenario 1, Table 2 also shows the results of response times and unit costs for area coverage



Cost comparison stationary and airborne AEDs

Figure 1 shows the cost for every scenario depending on the operational area based on the assumption of the lowest possible cost structures. Evidently, the application of a trunc function on fixed costs leads to an interval-fixed trend line, which, however, appears to be linear due to the figure's high scale. Comparing the two scenarios illustrates, that the airborne UAS-based scenario shows in almost any constellation less total costs than the stationary one when comparing the same response time *d*. Airborne costs only exceed the stationary scenario when comparing the highest UAS-related cost assumption with the lowest of stationary AEDs.

Focusing on varying unit cost and the cost per km² proves the higher cost efficiency of an airborne AED network over a stationary. Figure 2 shows the costs per km², which are independent of the area coverage or focal point setting. Evidently, total costs are the highest with a response time of three minutes and fall with longer time intervals. This gives insight, as to how far the airborne response time can be reduced until the airborne costs exceed the stationary cost.



 Table 2
 Unit costs per scenario and variation. Own source

		55,000 €	31,295,000	13,970,000	7,865,000	5,060,000	3,575,000	2,585,000	5,445,000	2,475,000	1,430,000	935,000	000,099	495,000
		45,000 €	25,605,000	11,430,000	6,435,000	4,140,000	2,925,000	2,115,000	4,455,000	2,025,000	1,170,000	765,000	540,000	405,000
	Costs [€ p.a.]	32,248 €	18,349,112 €	8,190,992 €	4,611,464 €	2,966,816 €	2,096,120 €	1,515,656 €	3,192,552 €	1,451,160 €	838,448 €	548,216 €	386,976 €	290,232 €
D.	Number	AEDs needed	695	254	143	92	65	47	66	45	26	17	12	6
Scenario 2: airborne AED	Catchment Number	per unit [km2]	10.39	23.38	41.56	64.95	93.53	127.30	10.39	23.38	41.56	64.95	93.53	127.30
Scenario	Radius	405 € [km]	61,262,730 2	27,228,150 3	15,315,885 4	9,802,215 5	6,807,240 6	5,001,345 7	10,606,545 2	4,714,200 3	2,651,940 4	1,697,355 5	1,178,550 6	7 265,890 7
		263 €	39,782,958	17,681,490	9,945,871	6,365,389	4,420,504	3,247,787	6,887,707	3,061,320	1,722,124	1,102,233	765,330	562,294
	Costs [€ p. a.]	170 €	25,715,220	11,429,100	6,428,890	4,114,510	2,857,360	2,099,330	4,452,130	1,978,800	1,113,160	712,470	494,700	363,460
	Number	AEDs needed	151,266	67,230	37,817	24,203	16,808	12,349	26,189	11,640	6,548	4,191	2,910	2,138
Scenario 1: stationary AED	Catchment	per unit [km²] AEDs needec	0.025	0.058	0.103	0.162	0.233	0.318	0.025	0.058	0.103	0.162	0.233	0.318
Scenario 1	Radius	AED [km]	0.1	0.15	0.2	0.25	0.3	0.35	0.1	0.15	0.2	0.25	0.3	0.35
Response	time d		3	4	5	9	7	8	3	4	5	9	7	8
			Full area	coverage	[3,930	T IIIN			Hot spots	[680.4	km²]			

In any scenario, the cost per km² operational area is lower when using an UAS. To maintain fastest availability times at the lowest assumable costs, $6543.3 \in \text{per km}^2$ for stationary AEDs are more than twice as high compared to an airborne solution with $3103.07 \in \text{If delivery times are modelled to } 6 \text{ min, a significant reduction of costs to } 496.49 \in \text{per km}^2$ for UAS-based delivery and $1046.93 \in \text{for stationary AEDs}$ can be noted.

Sensitivity

By equating the cost functions and keeping all but one parameter constant, a decision maker's indifference in choosing between the mobile or stationary alternative concerning the total costs can be determined. Variable parameters are as previously established the unit costs, the area of provision and period of help. Results are shown in Table 3.

For area coverage, the stationary AED's critical unit costs range from $121.30 \ \in \$ to $212.70 \ \in \$, to achieve indifference with the three cost levels of the mobile scenario (31,966 $\ \in \$, $45,000 \ \in \$,55,000 $\ \in \$). This means, that if the stationary AED's cost per year ranged within this interval, the mobile alternative would no longer be more advantageous. However, based on this study's research, that is not the case, costs per year for stationary AEDs range from $170 \ \in \$ upwards.

If the stationary unit costs are kept constant at the unit costs levels (170 \in , 263 \in , 405 \in), the highest possible unit costs of an UAS-based AED can be determined, that still leaves the mobile scenario with lower or equal costs to the stationary solution. When covering the total area of Vorpommern-Greifswald, unit costs would need to range between 45,193.71 \in and 107,667.36 \in to achieve indifference with the total costs of the stationary scenario.

If the hot spots only are regarded, the stationary AED must have unit costs of between $121.90 \in \text{and } 231.52 \in \text{to}$ cause indifference towards the mobile scenario, depending on the response time and the related total costs. Evidently, the unit costs are below the assumed average stationary unit costs of $263 \in \text{and}$ implicate a necessary decrease in any case. Therefore, the stationary scenario would only be advantageous compared to the mobile scenario, if unit costs were significantly lower than the average cost of a stationary AED that was used in this model.

Keeping the parameters of the stationary scenario constant, the mobile AED scenario gains indifference with unit costs between $40,384.44 \in \text{and } 107,136.82 \in \text{.}$ These costs lie mainly above the base level of mobile cost, which represents real costs determined by the MVILIFEIDRONE project. Their top line is approximately twice as high as the highest costs level assumed in this study. Consequently, the mobile scenario is always superior to the stationary AED network, as long as the unit cost per UAS stays lower than $40,384.44 \in \text{.}$







Fig. 2 Impact of unit costs. Own source

Discussion

As expected, total costs are lowest, when modelling the longest possible time interval for the AED delivery together with the lowest unit prices. However, since the provision of AEDs to OHCA is time-critical, shorter time intervals should be aimed for. This raises the question about the social willingness to pay for AED networks, to improve the outcomes of OHCA.

Given the established assumptions, this study finds that the setting of hot spots is of economic advantage, contrary to the complete coverage of a rural region with AEDs. This is substantiated in the significantly smaller area that needs to be covered. In the case of Vorpommern-Greifswald, only a sixth of the actual region would have to be covered with AEDs but would nevertheless cover about 75% of all occurring OHCA. In a two-stepped approach, covering these focal points would be the first and highly effective measure, before finding solutions to better serve the remaining expanse.

This study shows that the cost of UAS-based AED delivery is always lower than the stationary costs when comparing the same response time in corresponding scenarios. For a cost equivalence with UAS-based AEDs, the cost of stationary systems would have to be significantly reduced. It can be concluded, that even with equal system costs, mobile AED networks can achieve faster response times and therefore better medical care, than traditional stationary AED. Stationary AEDs are therefore inferior to mobile solutions.



Furthermore, the time to retrieve the AED, response times and the respective unit cost levels are assumptions that need to be further tested and validated. This holds especially true for the conjecture that UAS are a means of transport of superior speeds compared to lay persons or first responders.

Our findings show, that UAS-supported AED delivery is superior in terms of cost efficiency than the existing stationary solutions. Due to the lack of information on clinical outcomes, we chose the access time to the AED as an effect on the cost-efficiency analysis. However, using clinical outcomes such as DALYs and QALYs would be ideal. Cost efficiency analyses and comparisons of stationary to UAS-supported AED networks should be complemented, as soon as clinical data becomes available.

UAS technology is subject to rapid innovation, enhancing their utility and operational range. Therefore, technical capabilities may impact this study's findings. This holds true



Table 3 Unit costs needed to achieve indifference regarding the corresponding AED-network alternative

Base values	Unit costs sa	Unit costs stationary AEDs [€]	; [€]				Unit costs ae	Jnit costs aerial AEDs [€]				
	170		263		405		32,248		45,000		55,000	
Rescue time	Coverage	Hot spots	Coverage	Hot spots	Coverage	Hot spots	Coverage	Hot spots	Coverage	Hot spots	Coverage	Hot spots
3	121,30	121,90	169.27	170.11	206.89	207.91	45,193.71	44,971.01	69,917.33	69,572.80	107,667.36	107,136.82
4	121,84	124,60	170.01	173.97	207.79	212.63	44,996.46	43,973.33	69,612.17	68,029.33	107,197.44	104,760.00
5	121,94	128,05	170.16	178.68	207.98	218.39	44,957.27	42,813.85	69,55.55	66,235.54	107,104.09	101,997.69
9	122,58	130,81	171.05	182.53	209.06	223.10	44,722.93	41,910.00	69,189.01	64,837.24	106,545.82	99,844.41
7	124,71	132,98	174.02	185.57	212.70	226.80	43,959.38	41,225.00	68,007.75	63,777.50	104,726.77	98,212.50
∞	122,74	135,75	171.27	189.43	209.33	231.52	44,666.60	40,384.44	69,101.85	62,477.11	106,411.60	96,210.00

especially for the UAS´ travelling speed, which is poised to increase significantly in the future.

Conclusion

Our aim was to evaluate the cost of alternative solutions to improve OHCA treatment. The total costs of providing AEDs in specific areas were compared by modeling two basic scenarios of a stationary AED against that of a mobile AED. Based on the exemplary rural region of Vorpommern-Greifswald, three variations were introduced, based on innovating existing EMS structures to shorten present EMS response times, unit costs and area coverage.

The calculated costs per km² show that the coverage of a given area with mobile AEDs is less expensive and more effective than placing stationary ones under any simulated circumstance. Obviously, setting focal points leads to lower system costs than a full area coverage. This holds true for any region to be supplied with AEDs.

Based on these findings, supplying hotspots in the study region of Vorpommern-Greifswald with mobile AEDs with a four-minute flight radius is recommended as the most costefficient way to ensure a significantly shorter response time. Historically, about 75% of all past OHCA would have been covered using this strategy. Hot spot coverage would result in costs between 1,451,160 \in and 2,475,000 \in depending on the unit costs. As the UAS-based AED network is always more cost-efficient than the stationary, this recommendation also holds true for a full, yet more cost intensive, full area coverage.

A strong cost driver in this model is the redundant capacity of UAS, set to 50% in this study, which is deemed necessary regarding possible technical failures. Medical UAS networks could realize a lot of cost potential by utilizing aircraft with higher reliability, in that weather conditions and failure risks become much less influential. This would further the advantage of airborne AED deliveries over the stationary solution.

To achieve an applicability of the focal point solution to other regions, it is necessary to further map OHCA in order to identify high risk locations. Also, consideration should be given to how far the response time, and thus flight radii should be reduced, so that more lives can be saved in the shortest possible time without neglecting the economic aspect.

Still, the very low prospective utilization of the UAS network indicates the possibility of integrating possible other use cases into the network. Those could be the transport of other medical goods, such as laboratory samples or the use for situations assessments in crisis management. The availability of ED delivery to OHCA could be ensured by always carrying during one on non-related transports.



Supplementary Information The online version contains supplementary material available at https://doi.org/10.1007/s10198-022-01531-0.

Funding Open Access funding enabled and organized by Projekt DEAL.

Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit http://creativecommons.org/licenses/by/4.0/.

References

- Gräsner, J., et al.: Optimierung der Reanimationsversorgung in Deutschland. Notfall Rettungsmed. 17, 314–316 (2014)
- Gräsner, J.-T., Lefering, R., Koster, R.W.: EuReCa ONE—27 Nations, ONE Europe, ONE Registry: a prospective one month analysis of out-of-hospital cardiac arrest outcomes in 27 countries in Europe. Resuscitation 105, 188–195 (2016)
- Boyce, L.W., et al.: High survival rate of 43% in out-of-hospital cardiac arrest patients in an optimised chain of survival. Netherlands Heart J 23(1), 20–25 (2015)
- Gross, V.T., Ilknur E.: Informationen zur Laienreanimation in Deutschland. [Online] (2019). https://www.bzga.de/fileadmin/ user_upload/PDF/pressemitteilungen/daten_und_fakten/Fakte nblatt_Reanimation_Stand_Oktober_2019.pdf. Accessed 17 Feb 2021
- Brinkrolf, P., Bohn, A., Lukas, R., Heyse, M., van Aken, H. et al.: Projekt "Woche der Wiederbelebung", Öffentlichkeitsarbeit und Schulungsmaßnahmen verbessern das Wissen zur Wiederbelebung in der Bevölkerung. Anästh Intensivmed 57, 496–504 (2016)
- Møller Hansen, S., Malta Hansen, C., Folke, F., Rajan, S., Kragholm, K., et al.: Bystander defibrillation for out-of-hospital cardiac arrest in public vs residential locations. JAMA Cardiol 5, 507–514 (2017)
- Fleßa, S., et al.: Der Telenotarzt als Innovation des Rettungswesens im ländlichen Raum eine gesundheitsökonomische Analyse für den Kreis Vorpommern-Greifswald. Die Unternehmung. 3, 248–262 (2016)
- Bertelsmann Stiftung. Demographiebericht Landkreis Vorpommern-Greifswald (2018)
- 9. Trappe, H.-J.: Einsatz automatisierter externer Defibrillatoren (AED). Kardiologe 1, 28–39 (2012)
- Bein, B., Koch, T., Geldner, G., Böttiger, B.W., Gräsner, J.T.: Notfallversorgung in Deutschland, transformation und trends. Deutsches Ärzteblatt 46, 2152–2157 (2017)
- Brinkrolf, P., Hasebrook, J. P., Hahnenkamp, K.: LandlRettung: Zukunftsfähige notfallmedizinische Neuausrichtung eines Landkreises. Medizinisch Wissenschaftliche Verlagsgesellschaft, pp. 140–145 (2017)
- Auricchio, A., Gianquintieri, L., Burkart, R., Benvenuti, C., Muschietti, S., et al.: Real-life time and distance covered by lay first responders alerted by means of smartphone-application, Implications for early initiation of cardiopulmonary resuscitation and access to au-tomatic external defibrillators. Resuscitation 141, 182–187 (2019)
- Hansen, C.M., Kragholm, K., Granger, C.B., Pearson, D.A., Tyson, C., et al.: The role of bystanders, first responders, and

- emergency medical service providers in timely de-fibrillation and related outcomes after out-of-hospital cardiac arrest: Results from a statewide registry. Resuscitation **96**, 303–309 (2015)
- Baumgarten, M., et al.: Drones delivering automated external defibrillators—integrating unmanned aerial systems into the chain of survival: a simulation study in rural Germany. Reuscitation 172, 139–145 (2022)
- Sakai, T., Iwami, T., Kitamura, T., Nishiyama, C., Kawamura, T., et al.: Effectiveness of the new "Mobile AED Map" to find and retrieve an AED, A randomised controlled trial. Resuscitation 1, 69–73 (2011)
- Riyapan, S., Lubin, J.: Emergency dispatcher assistance decreases time to defibrillation in a public venue, A randomized controlled trial. Am J Emergency Med 3, 590–593 (2016)
- Röper, J., Krohn, M., Fleßa, S., Thies, K.-C.: Costing of helicopter emergency services – a strategic simulation based on the example of a German rural region. Health Econ Rev (2020). https://doi.org/ 10.1186/s13561-020-00287-8
- Claesson, A., Bäckmann, A., Ringh, M., Svensson, L., Nordberg, P., et al.: Time to delivery of an automated external defibrillator using a drone for simulated out-of-hospital cardiac arrests vs emergency medical services. JAMA 317(22), 2332–2334 (2017)
- Boutilier, J.J., Brooks, S.C., Janmohamed, A., Byers, A., Buick, J.E., Zhan, C., et al.: Optimizing a drone network to deliver automated external defibrillators. Circulation 135(25), 2454–2465 (2017). https://doi.org/10.1161/CIRCULATIONAHA.116.026318
- Pulver, A., Wei, R., Mann, C.: Locating AED enabled medical drones to enhance cardiac arrest response times. Prehosp Emerg Care. 20, 378–389 (2016). https://doi.org/10.3109/10903127. 2015.1115932
- Bauer, J., et al.: Development of unmanned aerial vehicle (UAV) networks delivering early defibrillation for out-of-hospital cardiac arrests (OHCA) in areas lacking timely access to emergency medical services (EMS) in Germany: a comparative economic study. BMJ Open (2021). https://doi.org/10.1136/bmjopen-2020-043791
- Chase, D., et al.: Using simulation to estimate the cost effectiveness of improving ambulance and thrombolysis response times after myocardial infarction. Emergency Med (2006). https://doi.org/10.1136/emj.2004.023036
- Zailani, M.A., et al.: Drone versus ambulance for blood products transportation: an economic evaluation study. BMC Health Services Res (2021). https://doi.org/10.1186/s12913-021-07321-3
- Espinoza, A., et al.: Time gain needed for in-ambulance telemedicine: cost-utility model. JMIR Mhealth Uhealth. (2017). https:// doi.org/10.2196/mhealth.8288
- Baumgarten, M., Hahnenkamp, K.: Wenn Drohnen Leben Retten. Klinik Management aktuell 2021, 61–62 (2021)
- Fleßa, S.: Systemisches Krankenhausmanagement. DeGruyter, Berlin (2018)
- Ritter, W.: Allgemeine Wirtschaftsgeographie, Eine systemtheoretisch orientierte Einführung. Oldenbourg, München (2001)
- Fleßa, S.: Kleinere Krankenhäuser im ländlichen Raum, Lösungsmodelle für eine finanzierbare Versorgung. Springer Gabler, Wiesbaden (2020)
- Land Mecklenburg-Vorpommern. Rettungsdienstgesetz Mecklenburg-Vorpommern. 9. Februar 2015.
- Landesregierung Mecklenburg-Vorpommern. Erfüllung der Hilfsfrist bei Rettungsdiensteinsätzen im Jahr 2018. Kleine Anfrage und Antwort der Landesregierung. Schwerin: Drucksache 7/3637, 6. 6 2019.

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

